

SAMSUNG

FJM

Technical Data Book

**Free Joint Multi for Europe
(R32, 50Hz, HP)**



Model : Outdoor unit (AJ****CJ*EG/EU)

Indoor unit (Wall-mounted, Wind-Free 1Way Cassette, Wind-Free 4Way Cassette(600x600), Duct)

History

Version	Modification	Date	Remark
Ver.1.0	Released FJM for Europe TDB (R32)	17.12.20	
Ver.1.1	Modified Net/Shipping Weight of indoor units	18.01.18	
Ver.2.0	Added 2018 New Line up (Outdoor Unit, Indoor Unit : Wind-Free 1Way, Wind-Free 4Way(600x600), Duct)	18.12.07	

Nomenclature

Outdoor Unit

Model Name

AJ

050

N

C

J

2

E

G

/

EU

(1)

(2)

(3)

(4)

(5)

(6)

(7)

(8)

Buyer

(1) Classification

AC	CAC
AM	DVM
AJ	FJM (Free Joint Multi)
AE	EHS

(2) Capacity

X1/10 kW (3 digits)

(3) Version

M	2017
N	2018
R	2019

(4) Product Type

S	SET (NASA)
N	Indoor Unit (NASA)
X	Outdoor Unit (NASA)
A	SET (Non NASA)
B	Indoor Unit (Non NASA)
C	Outdoor Unit (Non NASA)

(5) Product Notation

J	Free Joint Multi
P	Pack Multi
H	DVM Home

(6) Feature

2	2 Room
3	3 Room
4	4 Room
5	5 Room

(7) Rating Voltage

A	115V, 60Hz
B	220V, 60Hz
C	208~230V, 60Hz
D	200~220V, 50Hz
E	220~240V, 50Hz

(8) Mode

C	Cooling Only (R410A)
H	Heat Pump (R410A)
F	Cooling Only (R32)
G	Heat Pump (R32)

Nomenclature

Indoor Unit

Wall Mounted Type

Model Name

AR	09	N	X	W	SA	UR	N	EU
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	Buyer

(1) Classification

AR	RAC
----	-----

(2) Capacity

X 1000 Btu/h (2 digits)

(3) Version

J	2015
K	2016
M	2017
N	2018

(4) Feature 1

S	Inverter Heat Pump R410A
V	Inverter Cooling Only R410A
X	Inverter Heat Pump R32
Y	Inverter Cooling Only R32

(5) Feature 2

F	SPI not included
P	Wi-Fi + SPI
W	Wi-Fi
C	Wi-Fi + SPI + PM2.5

(6) Series

FB	FLG (A3050 Best, AR9570) 2nd
DB	DLX (A3050 Better, AR7580) 2nd
SA	STD (A3050 Good1, AR5580) 1st
SB	STD (A3050 Good1, AR5580) 2nd
NA	ENT (A3050 Good2, AR5680) 1st
PE	Maldives (A+High)
HB	New Boracay (No Pattern)
XA	Wind-Free (A3050) 1st
XB	Wind-Free (A3050) 2nd
XC	Wind-Free (A3050) 3rd

(7) Color

WK	DA White
WQ	DA White
UR	Midnight Blue
SI	Vivaldi White

(8) Product

N	Indoor Unit
X	Outdoor Unit

Nomenclature

Indoor Unit

1Way Cassette, 4Way Cassette(600x600), Duct Type

Model Name

AJ	026	R	B	1	D	E	G	/	EU
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)		Buyer

(1) Classification

AC	CAC
AM	DVM
AJ	FJM (Free Joint Multi)
AE	EHS

(2) Capacity

X1/10 kW (3 digits)

(3) Version

M	2017
N	2018
R	2019

(4) Product Type

S	SET (NASA)
N	Indoor Unit (NASA)
X	Outdoor Unit (NASA)
A	SET (Non NASA)
B	Indoor Unit (Non NASA)
C	Outdoor Unit (Non NASA)

(5) Product Notation

1	(Wind-Free) 1Way Cassette
N	(Wind-Free) 4Way Cassette (600x600)
L	Slim Duct
M	MSP Duct

(6) Feature

D	DELUXE
----------	--------

(7) Rating Voltage

A	115V, 60Hz
B	220V, 60Hz
C	208~230V, 60Hz
D	200~220V, 50Hz
E	220~240V, 50Hz


(8) Mode

C	Cooling Only (R410A)
H	Heat Pump (R410A)
F	Cooling Only (R32)
G	Heat Pump (R32)

Features & Benefits


Universal Connection

A single outdoor unit supporting up to five indoor units, the FJM system is ideal for residential spaces with multiple rooms to increase space efficiency.



New refrigerant R32

We use R-32 and reduce Refrigerant charge, so we can reduce the global warming potential and protect our Earth.



<A Comparison between R410A and R32 of FJM 5kW outdoor>

Setting to Cool or Heat only mode

This function enables the indoor units connected to the outdoor unit to operate in a specific mode. When you want to operate all indoor units with the cooling mode or heating mode.

Auto addressing & Auto pipe inspection

It can automatically set the address of the indoor unit and inspect pipes with one push of the button. Installation is very simple.

Samsung Smart Home


Control the FJM with only one application. This feature is optional to the several models



Features & Benefits

Top-class energy efficiency A+++

Featuring a suite of energy-optimizing technologies, Samsung FJM delivers top-class energy efficiency to support businesses in saving costs and the environment



Power improvement mode

The power improvement mode has the following power reduction effects.

- Reduced power at Thermo off
 - When the air conditioner operates in Cool, Dry, and Auto mode, if Thermo off is reached during cooling, the fan and display of the indoor unit are turned off after 5 minutes
 - When you operates the remote control, the indoor unit display turns on again.
- Standby mode operation
 - When all indoor units are turned off, the air conditioner recognizes it and enters the standby mode.
 - The product power consumption in the standby mode is 3.5 W or less.

Contents

1. Line-up	9
2. Specification	11
3. Electric Characteristics	31
4. Combination Table	32
5. Dimensional Drawing	38
6. Center of Gravity	51
7. Electrical Wiring Diagram	55
8. Sound Data	63
9. Fan Characteristics (PQ curve)	80
10. Operation Range	82
11. Piping Diagram	83
12. Capacity Table	86
13. Installation	135

1. Line-up

1-1. Outdoor units

Capacity (kW)	4	5	5.2	6.8
Image				
Model	AJ040NCJ2EG/EU	AJ050NCJ2EG/EU	AJ052RCJ3EG/EU	AJ068RCJ3EG/EU

1-2. Indoor units

Capacity (kW) Type	1.6	2.0	2.5	2.6	3.5	5.2
A3050 (Good1)						
Maldives						
New Boracay						
Wind-Free						
Wind-Free 1Way CASSETTE						
Wind-Free 4Way CASSETTE (600x600)						
Slim duct						
MSP duct						

1. Line-up

1-3. Combination Table (Outdoor-Indoor)

Indoor Unit \ Outdoor Unit		Model	  			
			AJ040MCJ2EH	AJ050MCJ2EH	AJ052RCJ3EG/EU	AJ068RCJ3EG/EU
Model		Capacity (kW)	4.0	5.0	5.2	6.8
 A3050 Good1	AR07/09/12NXWSAURNEU AR07/09/12MXWSAWKNEU	2.0	●	●	●	●
		2.5	●	●	●	●
		3.5	●	●	●	●
 Maldives	AR07/09/12NXFPEWQNEU	2.0	●	●	●	●
		2.5	●	●	●	●
		3.5	●	●	●	●
 New Boracay	AR07/09/12NXFHBWKNEU	2.0	●	●	●	●
		2.5	●	●	●	●
		3.5	●	●	●	●
 Wind-Free RAC	AR07/09/12NXWXCWKNEU AR07/09/12NXPXBWKNEU AR07/09/12NXWXBWKNEU AR07/09/12NXCXAWKNEU	2.0	●	●	●	●
		2.5	●	●	●	●
		3.5	●	●	●	●
 Wind-Free 1Way CASSETTE	AJ026/035RB1DEG/EU	2.6	●	●	●	●
		3.5	●	●	●	●
 Wind-Free 4Way CASSETTE (600x600)	AJ016/020/026RBNDEG/EU AJ035/052RBNDEG/EU	1.6		●	●	●
		2.0		●	●	●
		2.6		●	●	●
		3.5		●	●	●
		5.2				●
 Slim duct	AJ026/035RBLDEG/EU	2.6		●	●	●
		3.5		●	●	●
 MSP duct	AJ052RBMDEG/EU	5.2				●

2. Specification

2-1. Outdoor units

Type				Free Joint Multi		Free Joint Multi	
Model Name				AJ040NCJ2EG/EU		AJ050NCJ2EG/EU	
Power Supply			Φ, #, V, Hz	1, 2, 220~240, 50		1, 2, 220~240, 50	
Mode			-	HP		HP	
Performance	Capacity	Cooling	kW	4.0		5.0	
			Btu/h	13,600		17,100	
		Heating	kW	4.2		5.6	
			Btu/h	14,300		19,100	
Maximum number of connectable Indoor Units			EA	2		2	
Power	Power Input	Cooling	kW	0.90		1.22	
		Heating		0.90		1.28	
	Current Input	Cooling	A	4.10		5.60	
		Heating		4.10		5.90	
	Current	MCA	A	9.80		11.80	
		MFA		11.25		13.75	
Efficiency	EER	Cooling	W/W	4.44		4.10	
	COP	Heating	W/W	4.67		4.38	
	SEER (Grade)		W/W	8.54 (A+++)		8.54 (A+++)	
	SCOP (Grade)		W/W	4.64 (A++)		4.64 (A++)	
Casing	Material	Body	-	GI steel plate		GI steel plate	
		Base	-	GI steel plate		GI steel plate	
Heat exchanger	Type		-	Fin & Tube		Fin & Tube	
	Material	Fin	-	Al		Al	
		Tube	-	Cu		Cu	
	Fin Treatment		-	Anti-Corrosion		Anti-Corrosion	
Compressor	Type		-	Twin BLDC Rotary Inverter		Twin BLDC Rotary Inverter	
	Output		kW x n	4.09 x 1		4.09 x 1	
	Model Name		-	KTN130D42UFR		KTN130D42UFR	
	Oil	Type	-	ESTER OIL VG74		ESTER OIL VG74	
		Initial Charge	cc	350		350	
Fan	Type		-	Propeller Fan		Propeller Fan	
	Discharge direction		-	Front (Horizontal)		Front (Horizontal)	
	Quantity		EA	1		1	
	Air Flow Rate		m³/min	29.7		33.05	
			l/s	494		551	
	External Static Pressure	Max.	mmAq	-		-	
			Pa	-		-	
Fan Motor	Type		-	BLDC		BLDC	
	Output x n		W	40 x 1		40 x 1	

2. Specification

Type				Free Joint Multi	Free Joint Multi
Model Name				AJ040NCJ2EG/EU	AJ050NCJ2EG/EU
Piping Connections	Liquid Pipe		Type	Flare connection	Flare connection
			Φ, mm x EA	6.35 x 2	6.35 x 2
			Φ, inch x EA	1/4" x 2	1/4" x 2
	Gas Pipe		Type	Flare connection	Flare connection
			Φ, mm x EA	9.52 x 2	9.52 x 2
			Φ, inch x EA	3/8" x 2	3/8" x 2
	Heat insulation			Both Liquid & Gas pipes	Both Liquid & Gas pipes
	Installation Limitation	Total Piping Length	m	30	30
		Max. Length (OD~ID)	m	25	25
		Max. Height (ID~ID)	m	7.5	7.5
		Max. Height (OD~ID)	m	15.0	15.0
Wiring connections	Communication	Min.	mm ²	0.75	0.75
		Remark	-	F1, F2	F1, F2
Refrigerant	Type		-	R32	R32
	Factory Charging		kg	0.98	1.18
			tCO2e	0.66	0.80
Sound	Sound Pressure	Cooling	dB(A)	45	46
		Heating		46	47
	Sound Power			60	61
External Dimension	Net Weight		kg	32.0	33.0
	Shipping Weight		kg	34.0	35.0
	Net Dimensions (WxHxD)		mm	790 × 548 × 285	790 × 548 × 285
	Shipping Dimensions (WxHxD)		mm	913 × 622 × 371	913 × 622 × 371
Operating Temp. Range	Cooling		°C	-5 ~ 46	-5 ~ 46
	Heating		°C	-15 ~ 24	-15 ~ 24

NOTE

- Specifications may be subject to change without prior notice.
- 1)* Capacities are based on (Equivalent refrigerant piping : 5m, Level differences : 0m)
 - Cooling : Indoor temperature : 27°C DB, 19°C WB / Outdoor temperature : 35°C DB, 24°C WB
 - Heating : Indoor temperature : 20°C DB, 15°C WB / Outdoor temperature : 7°C DB, 6°C WB
- 2)* Select wire size based on the value of MCA
- 3)* Sound pressure level is obtained in an anechoic room.
 - Sound pressure level is a relative value, depending on the distance and acoustic environment.
 - Sound pressure level may differ depending on operation condition.
 - dBA = A-weighted sound pressure level
 - Reference acoustic pressure 0 dB = 20uPa
- 4)* Sound power level is an absolute value that a sound source generates.
 - dBA = A-weighted sound power level
 - Reference power : 1pW
 - Measured according to ISO 3741
- 5)* These products contain R32 (GWP=675) which is fluorinated greenhouse gas.

2. Specification

2-1. Outdoor units

Type				Free Joint Multi		Free Joint Multi	
Model Name				AJ052RCJ3EG/EU		AJ068RCJ3EG/EU	
Power Supply			Φ, #, V, Hz	1, 2, 220~240, 50		1, 2, 220~240, 50	
Mode			-	HP		HP	
Performance	Capacity	Cooling	kW	5.2		6.8	
			Btu/h	17,700		23,200	
		Heating	kW	6.3		8.0	
			Btu/h	21,500		27,300	
Maximum number of connectable Indoor Units			EA	3		3	
Power	Power Input	Cooling	kW	1.25		1.80	
		Heating		1.32		1.81	
	Current Input	Cooling	A	5.50		8.10	
		Heating		6.10		8.20	
	Current	MCA	A	11.90		17.50	
		MFA		13.75		20.75	
Efficiency	EER	Cooling	W/W	4.16		3.78	
	COP	Heating	W/W	4.77		4.42	
	SEER (Grade)		W/W	8.51 (A+++)		7.75 (A++)	
	SCOP (Grade)		W/W	4.60 (A++)		4.32 (A+)	
Casing	Material	Body	-	GI steel plate		GI steel plate	
		Base	-	GL steel plate		GL steel plate	
Heat exchanger	Type		-	Fin & Tube		Fin & Tube	
	Material	Fin	-	Al		Al	
		Tube	-	Cu		Cu	
	Fin Treatment		-	Anti-Corrosion		Anti-Corrosion	
Compressor	Type		-	Twin BLDC Rotary		Twin BLDC Rotary	
	Output		kW x n	4.68 x 1		7.65 x 1	
	Model Name		-	KTN150D42UFR		KTF235D22UMV	
	Oil	Type	-	ESTER OIL VG74		ESTER OIL VG74	
		Initial Charge	cc	450		670	
Fan	Type		-	Propeller Fan		Propeller Fan	
	Discharge direction		-	Front (Horizontal)		Front (Horizontal)	
	Quantity		EA	1		1	
	Air Flow Rate		m³/min	38.0		47.5	
			l/s	633		792	
	External Static Pressure	Max.	mmAq	-		-	
			Pa	-		-	
Fan Motor	Model		-	BLDC		BLDC	
	Output x n		W	125 x 1		125 x 1	

2. Specification

Type				Free Joint Multi	Free Joint Multi
Model Name				AJ052RCJ3EG/EU	AJ068RCJ3EG/EU
Piping Connections	Liquid Pipe		Type	Flare connection	Flare connection
			Φ, mm x EA	6.35 x 3	6.35 x 3
			Φ, inch x EA	1/4 x 3	1/4 x 3
	Gas Pipe		Type	Flare connection	Flare connection
			Φ, mm x EA	9.52 x 2 + 12.70	9.52 + 12.70 x 2
			Φ, inch x EA	3/8 x 2 + 1/2	3/8 + 1/2 x 2
	Heat insulation		-	Both Liquid & Gas pipes	Both Liquid & Gas pipes
	Installation Limitation	Total Piping Length	m	50	50
		Max. Length (OD~ID)	m	25	25
		Max. Height (ID~ID)	m	7.5	7.5
		Max. Height (OD~ID)	m	15	15
Wiring connections	Communication	Min.	mm ²	0.75	0.75
		Remark	-	F1, F2	F1, F2
Refrigerant	Type		-	R32	R32
	Factory Charging		kg	1.55	2.00
			tCO2e	1.05	1.35
Sound	Sound Pressure	Cooling	dB(A)	46	48
		Heating		48	50
	Sound Power			61	64
External Dimension	Net Weight		kg	44.5	57.5
	Shipping Weight		kg	47.5	61.5
	Net Dimensions (WxHxD)		mm	880 x 638 x 310	880 x 798 x 310
	Shipping Dimensions (WxHxD)		mm	1,023 x 742 x 413	1,023 x 896 x 413
Operating Temp. Range	Cooling		℃	-10 ~ 46	-10 ~ 46
	Heating		℃	-15 ~ 24	-15 ~ 24

NOTE

- Specifications may be subject to change without prior notice.
- 1)* Capacities are based on (Equivalent refrigerant piping : 5m, Level differences : 0m)
 - Cooling : Indoor temperature : 27°C DB, 19°C WB / Outdoor temperature : 35°C DB, 24°C WB
 - Heating : Indoor temperature : 20°C DB, 15°C WB / Outdoor temperature : 7°C DB, 6°C WB
- 2)* Select wire size based on the value of MCA
- 3)* Sound pressure level is obtained in an anechoic room.
 - Sound pressure level is a relative value, depending on the distance and acoustic environment.
 - Sound pressure level may differ depending on operation condition.
 - dBA = A-weighted sound pressure level
 - Reference acoustic pressure 0 dB = 20uPa
- 4)* Sound power level is an absolute value that a sound source generates.
 - dBA = A-weighted sound power level
 - Reference power : 1pW
 - Measured according to ISO 3741
- 5)* These products contain R32 (GWP=675) which is fluorinated greenhouse gas.

2. Specification

2-2. Indoor units

Wall Mounted Type - A3050 Good1

Type				A3050 Good1	A3050 Good1	A3050 Good1
Model Name				AR07NXWSAURNEU	AR09NXWSAURNEU	AR12NXWSAURNEU
Power Supply			Φ, #, V, Hz	1, 2, 220~240, 50	1, 2, 220~240, 50	1, 2, 220~240, 50
Mode			-	HP	HP	HP
Performance	Capacity	Cooling	kW	2.0	2.75	3.5
			Btu/h	6,800	9,400	11,900
		Heating	kW	2.2	3.2	3.5
			Btu/h	7,500	10,900	11,900
Power	Power Input	Cooling	W	30	30	30
		Heating		30	30	30
	Current Input	Cooling	A	0.3	0.3	0.3
		Heating		0.3	0.3	0.3
Heat exchanger	Type		-	Fin & Tube	Fin & Tube	Fin & Tube
	Material	Fin	-	Al	Al	Al
		Tube	-	Cu	Cu	Cu
	Fin Treatment		-	Green Hydrophile	Green Hydrophile	Green Hydrophile
Fan	Type		-	Cross flow Fan	Cross flow Fan	Cross flow Fan
	Quantity		EA	1	1	1
	Air Flow Rate		m³/min	8.0	9.0	10.0
			l/s	133.3	150.0	166.7
	External Static pressure	Max. (Min/Std/Max)	mmAq	-	-	-
			Pa	-	-	-
Fan Motor	Type		-	BLDC Motor	BLDC Motor	BLDC Motor
	Output x n		W	27 x1	27 x1	27 x1
Piping Connections	Liquid Pipe		Type	Flare connection	Flare connection	Flare connection
			Φ, mm (inch)	6.35 (1/4")	6.35 (1/4")	6.35 (1/4")
	Gas Pipe		Type	Flare connection	Flare connection	Flare connection
			Φ, mm (inch)	9.52 (3/8")	9.52 (3/8")	9.52 (3/8")
	Heat Insulation		-	Both Liquid & Gas pipes	Both Liquid & Gas pipes	Both Liquid & Gas pipes
Drain Pipe		Φ,mm	ID18mm Hose	ID18mm Hose	ID18mm Hose	
Wiring connections	Communication	Min.	mm²	0.75	0.75	0.75
		Remark	-	F1, F2	F1, F2	F1, F2
Refrigerant	Type		-	R32	R32	R32
	Electronic Expansion Valve		-	EEV NOT INCLUDED	EEV NOT INCLUDED	EEV NOT INCLUDED
Sound	Sound Pressure	H/M/L	dB(A)	37 / 27 / 22	37 / 27 / 22	38 / 28 / 22
	Sound Power	Cooling		54	54	56
Dimensions	Net Weight		kg	9.5	9.5	9.5
	Shipping Weight		kg	11.3	11.8	11.8
	Net Dimensions (WxHxD)		mm	826 x 261 x 261	826 x 261 x 261	826 x 261 x 261
	Shipping Dimensions (WxHxD)		mm	886 x 317 x 335	886 x 317 x 335	886 x 317 x 335
Casing	Material		-	HIPS	HIPS	HIPS

NOTE

- Specifications may be subject to change without prior notice.
- 1)* Capacities are based on (Equivalent refrigerant piping : 5m, Level differences : 0m)
 - Cooling : Indoor temperature : 27°C DB, 19°C WB / Outdoor temperature : 35°C DB, 24°C WB
 - Heating : Indoor temperature : 20°C DB, 15°C WB / Outdoor temperature : 7°C DB, 6°C WB
- 2)* Select wire size based on the value of MCA
- 3)* Sound pressure level is obtained in an anechoic room.
 - Sound pressure level is a relative value, depending on the distance and acoustic environment.
 - Sound pressure level may differ depending on operation condition.
 - dBA = A-weighted sound pressure level
 - Reference acoustic pressure 0 dB = 20uPa
- 4)* Sound power level is an absolute value that a sound source generates.
 - dBA = A-weighted sound power level
 - Reference power : 1pW
 - Measured according to ISO 3741
- 5)* These products contain R32 (GWP=675) which is fluorinated greenhouse gas.

2. Specification

2-2. Indoor units

Wall Mounted Type - A3050 Good1

Type				A3050 Good1	A3050 Good1	A3050 Good1
Model Name				AR07MXWSAWKNEU	AR09MXWSAWKNEU	AR12MXWSAWKNEU
Power Supply			Φ, #, V, Hz	1, 2, 220~240, 50	1, 2, 220~240, 50	1, 2, 220~240, 50
Mode			-	HP	HP	HP
Performance	Capacity	Cooling	kW	2.0	2.5	3.5
			Btu/h	6,800	8,500	11,900
		Heating	kW	2.2	3.2	4.0
			Btu/h	7,500	10,900	13,600
Power	Power Input	Cooling	W	30	30	30
		Heating		30	30	30
	Current Input	Cooling	A	0.3	0.3	0.3
		Heating		0.3	0.3	0.3
Heat exchanger	Type		-	Fin & Tube	Fin & Tube	Fin & Tube
	Material	Fin	-	Al	Al	Al
		Tube	-	Cu	Cu	Cu
	Fin Treatment		-	Green Hydrophile	Green Hydrophile	Green Hydrophile
Fan	Type		-	Cross flow Fan	Cross flow Fan	Cross flow Fan
	Quantity		EA	1	1	1
	Air Flow Rate		m³/min	10.0	11.0	12.0
			l/s	166.7	183.3	200.0
	External Static pressure	Max. (Min/Std/Max)	mmAq	-	-	-
			Pa	-	-	-
Fan Motor	Type		-	BLDC Motor	BLDC Motor	BLDC Motor
	Output x n		W	27 x 1	27 x 1	27 x 1
Piping Connections	Liquid Pipe		Type	Flare connection	Flare connection	Flare connection
			Φ, mm (inch)	6.35 (1/4")	6.35 (1/4")	6.35 (1/4")
	Gas Pipe		Type	Flare connection	Flare connection	Flare connection
			Φ, mm (inch)	9.52 (3/8")	9.52 (3/8")	9.52 (3/8")
	Heat Insulation		-	Both Liquid & Gas pipes	Both Liquid & Gas pipes	Both Liquid & Gas pipes
Drain Pipe		Φ,mm	ID 18mm Hose	ID 18mm Hose	ID 18mm Hose	
Wiring connections	Communication	Min.	mm²	0.75	0.75	0.75
		Remark	-	F1, F2	F1, F2	F1, F2
Refrigerant	Type		-	R32	R32	R32
	Electronic Expansion Valve		-	EEV NOT INCLUDED	EEV NOT INCLUDED	EEV NOT INCLUDED
Sound	Sound Pressure	H/M/L	dB(A)	37 / 27 / 22	37 / 27 / 22	38 / 28 / 22
	Sound Power	Cooling		54	54	56
Dimensions	Net Weight		kg	11.0	11.0	11.0
	Shipping Weight		kg	13.6	13.6	13.6
	Net Dimensions (WxHxD)		mm	896 x 261 x 261	896 x 261 x 261	896 x 261 x 261
	Shipping Dimensions (WxHxD)		mm	956 x 317 x 335	956 x 317 x 335	956 x 317 x 335
Casing	Material		-	HIPS	HIPS	HIPS

NOTE

- Specifications may be subject to change without prior notice.
- 1)* Capacities are based on (Equivalent refrigerant piping : 5m, Level differences : 0m)
 - Cooling : Indoor temperature : 27°C DB, 19°C WB / Outdoor temperature : 35°C DB, 24°C WB
 - Heating : Indoor temperature : 20°C DB, 15°C WB / Outdoor temperature : 7°C DB, 6°C WB
- 2)* Select wire size based on the value of MCA
- 3)* Sound pressure level is obtained in an anechoic room.
 - Sound pressure level is a relative value, depending on the distance and acoustic environment.
 - Sound pressure level may differ depending on operation condition.
 - dBA = A-weighted sound pressure level
 - Reference acoustic pressure 0 dB = 20uPa
- 4)* Sound power level is an absolute value that a sound source generates.
 - dBA = A-weighted sound power level
 - Reference power : 1pW
 - Measured according to ISO 3741
- 5)* These products contain R32 (GWP=675) which is fluorinated greenhouse gas.

2. Specification

2-2. Indoor units

Wall Mounted Type - Maldives

Type				Maldives	Maldives	Maldives
Model Name				AR07NXFPEWQNEU	AR09NXFPEWQNEU	AR12NXFPEWQNEU
Power Supply			Φ, #, V, Hz	1, 2, 220~240, 50	1, 2, 220~240, 50	1, 2, 220~240, 50
Mode			-	HP	HP	HP
Performance	Capacity	Cooling	kW	2.0	2.75	3.5
			Btu/h	6,800	9,400	11,900
		Heating	kW	2.2	3.2	3.5
			Btu/h	7,500	10,900	11,900
Power	Power Input	Cooling	W	30	30	30
		Heating		30	30	30
	Current Input	Cooling	A	0.3	0.3	0.3
		Heating		0.3	0.3	0.3
Heat exchanger	Type		-	Fin & Tube	Fin & Tube	Fin & Tube
	Material	Fin	-	Al	Al	Al
		Tube	-	Cu	Cu	Cu
	Fin Treatment		-	Green Hydrophile	Green Hydrophile	Green Hydrophile
Fan	Type		-	Cross flow Fan	Cross flow Fan	Cross flow Fan
	Quantity		EA	1	1	1
	Air Flow Rate		m³/min	8.0	9.0	10.0
			l/s	133.3	150.0	166.7
	External Static pressure	Max. (Min/Std/Max)	mmAq	-	-	-
			Pa	-	-	-
Fan Motor	Type		-	BLDC Motor	BLDC Motor	BLDC Motor
	Output x n		W	27 x 1	27 x 1	27 x 1
Piping Connections	Liquid Pipe		Type	Flare connection	Flare connection	Flare connection
			Φ, mm (inch)	6.35 (1/4")	6.35 (1/4")	6.35 (1/4")
	Gas Pipe		Type	Flare connection	Flare connection	Flare connection
			Φ, mm (inch)	9.52 (3/8")	9.52 (3/8")	9.52 (3/8")
	Heat Insulation		-	Both Liquid & Gas pipes	Both Liquid & Gas pipes	Both Liquid & Gas pipes
Drain Pipe		Φ,mm	ID 18mm Hose	ID 18mm Hose	ID 18mm Hose	
Wiring connections	Communication	Min.	mm²	0.75	0.75	0.75
		Remark	-	F1, F2	F1, F2	F1, F2
Refrigerant	Type		-	R32	R32	R32
	Electronic Expansion Valve		-	EEV NOT INCLUDED	EEV NOT INCLUDED	EEV NOT INCLUDED
Sound	Sound Pressure	H/M/L	dB(A)	38 / 28 / 21	38 / 28 / 21	42 / 33 / 23
	Sound Power	Cooling		56	56	59
Dimensions	Net Weight		kg	8.0	8.0	8.0
	Shipping Weight		kg	9.7	9.7	9.7
	Net Dimensions (WxHxD)		mm	820 x 285 x 215	820 x 285 x 215	820 x 285 x 215
	Shipping Dimensions (WxHxD)		mm	880 x 260 x 360	880 x 260 x 360	880 x 260 x 360
Casing	Material		-	HIPS	HIPS	HIPS

NOTE

- Specifications may be subject to change without prior notice.
- 1)* Capacities are based on (Equivalent refrigerant piping : 5m, Level differences : 0m)
 - Cooling : Indoor temperature : 27°C DB, 19°C WB / Outdoor temperature : 35°C DB, 24°C WB
 - Heating : Indoor temperature : 20°C DB, 15°C WB / Outdoor temperature : 7°C DB, 6°C WB
- 2)* Select wire size based on the value of MCA
- 3)* Sound pressure level is obtained in an anechoic room.
 - Sound pressure level is a relative value, depending on the distance and acoustic environment.
 - Sound pressure level may differ depending on operation condition.
 - dBA = A-weighted sound pressure level
 - Reference acoustic pressure 0 dB = 20uPa
- 4)* Sound power level is an absolute value that a sound source generates.
 - dBA = A-weighted sound power level
 - Reference power : 1pW
 - Measured according to ISO 3741
- 5)* These products contain R32 (GWP=675) which is fluorinated greenhouse gas.

2. Specification

2-2. Indoor units

Wall Mounted Type - New Boracay

Type				New Boracay	New Boracay	New Boracay
Model Name				AR07NXFHBWKNEU	AR09NXFHBWKNEU	AR12NXFHBWKNEU
Power Supply			Φ, #, V, Hz	1, 2, 220~240, 50	1, 2, 220~240, 50	1, 2, 220~240, 50
Mode			-	HP	HP	HP
Performance	Capacity	Cooling	kW	2.0	2.75	3.5
			Btu/h	6,800	9,400	11,900
		Heating	kW	2.2	3.2	3.5
			Btu/h	7,500	10,900	11,900
Power	Power Input	Cooling	W	30	30	30
		Heating		30	30	30
	Current Input	Cooling	A	0.3	0.3	0.3
		Heating		0.3	0.3	0.3
Heat exchanger	Type		-	Fin & Tube	Fin & Tube	Fin & Tube
	Material	Fin	-	Al	Al	Al
		Tube	-	Cu	Cu	Cu
	Fin Treatment		-	Green Hydrophile	Green Hydrophile	Green Hydrophile
Fan	Type		-	Cross flow Fan	Cross flow Fan	Cross flow Fan
	Quantity		EA	1	1	1
	Air Flow Rate		m³/min	8.0	9.0	10.0
			l/s	133.3	150.0	166.7
	External Static pressure	Max. (Min/Std/Max)	mmAq	-	-	-
			Pa	-	-	-
Fan Motor	Type		-	BLDC Motor	BLDC Motor	BLDC Motor
	Output x n		W	27 x 1	27 x 1	27 x 1
Piping Connections	Liquid Pipe		Type	Flare connection	Flare connection	Flare connection
			Φ, mm (inch)	6.35 (1/4")	6.35 (1/4")	6.35 (1/4")
	Gas Pipe		Type	Flare connection	Flare connection	Flare connection
			Φ, mm (inch)	9.52 (3/8")	9.52 (3/8")	9.52 (3/8")
	Heat Insulation		-	Both Liquid & Gas pipes	Both Liquid & Gas pipes	Both Liquid & Gas pipes
Drain Pipe		Φ,mm	ID18mm Hose	ID18mm Hose	ID18mm Hose	
Wiring connections	Communication	Min.	mm²	0.75	0.75	0.75
		Remark	-	F1, F2	F1, F2	F1, F2
Refrigerant	Type		-	R32	R32	R32
	Electronic Expansion Valve		-	EEV NOT INCLUDED	EEV NOT INCLUDED	EEV NOT INCLUDED
Sound	Sound Pressure	H/M/L	dB(A)	38 / 30 / 21	38 / 30 / 21	42 / 33 / 21
	Sound Power	Cooling		56	56	59
Dimensions	Net Weight		kg	8.2	8.2	8.2
	Shipping Weight		kg	10.2	10.2	10.2
	Net Dimensions (WxHxD)		mm	820 x 285 x 227	820 x 285 x 227	820 x 285 x 227
	Shipping Dimensions (WxHxD)		mm	880 x 280 x 363	880 x 280 x 363	880 x 280 x 363
Casing	Material		-	HIPS	HIPS	HIPS

NOTE

- Specifications may be subject to change without prior notice.
- 1)* Capacities are based on (Equivalent refrigerant piping : 5m, Level differences : 0m)
 - Cooling : Indoor temperature : 27°C DB, 19°C WB / Outdoor temperature : 35°C DB, 24°C WB
 - Heating : Indoor temperature : 20°C DB, 15°C WB / Outdoor temperature : 7°C DB, 6°C WB
- 2)* Select wire size based on the value of MCA
- 3)* Sound pressure level is obtained in an anechoic room.
 - Sound pressure level is a relative value, depending on the distance and acoustic environment.
 - Sound pressure level may differ depending on operation condition.
 - dBA = A-weighted sound pressure level
 - Reference acoustic pressure 0 dB = 20uPa
- 4)* Sound power level is an absolute value that a sound source generates.
 - dBA = A-weighted sound power level
 - Reference power : 1pW
 - Measured according to ISO 3741
- 5)* These products contain R32 (GWP=675) which is fluorinated greenhouse gas.

2. Specification

2-2. Indoor units

Wall Mounted Type - Wind-Free (A3050)

Type				Wind-Free	Wind-Free	Wind-Free
Model Name				AR07NXWCWKNEU	AR09NXWCWKNEU	AR12NXWCWKNEU
Power Supply			Φ, #, V, Hz	1, 2, 220~240, 50	1, 2, 220~240, 50	1, 2, 220~240, 50
Mode			-	HP	HP	HP
Performance	Capacity	Cooling	kW	2.0	2.75	3.5
			Btu/h	6,800	9,400	11,900
		Heating	kW	2.2	3.2	3.5
			Btu/h	7,500	10,900	11,900
Power	Power Input	Cooling	W	30	30	30
		Heating		30	30	30
	Current Input	Cooling	A	0.3	0.3	0.3
		Heating		0.3	0.3	0.3
Heat exchanger	Type		-	Fin & Tube	Fin & Tube	Fin & Tube
	Material	Fin	-	Al	Al	Al
		Tube	-	Cu	Cu	Cu
	Fin Treatment		-	Green Hydrophile	Green Hydrophile	Green Hydrophile
Fan	Type		-	Cross flow Fan	Cross flow Fan	Cross flow Fan
	Quantity		EA	1	1	1
	Air Flow Rate		m³/min	9.3	9.3	10.8
			l/s	155.0	155.0	180.0
	External Static pressure	Max. (Min/Std/Max)	mmAq	-	-	-
			Pa	-	-	-
Fan Motor	Type		-	BLDC Motor	BLDC Motor	BLDC Motor
	Output x n		W	27 x 1	27 x 1	27 x 1
Piping Connections	Liquid Pipe		Type	Flare connection	Flare connection	Flare connection
			Φ, mm (inch)	6.35 (1/4")	6.35 (1/4")	6.35 (1/4")
	Gas Pipe		Type	Flare connection	Flare connection	Flare connection
			Φ, mm (inch)	9.52 (3/8")	9.52 (3/8")	9.52 (3/8")
	Heat Insulation		-	Both Liquid & Gas pipes	Both Liquid & Gas pipes	Both Liquid & Gas pipes
Drain Pipe		Φ,mm	ID18mm Hose	ID18mm Hose	ID18mm Hose	
Wiring connections	Communication	Min.	mm²	0.75	0.75	0.75
		Remark	-	F1, F2	F1, F2	F1, F2
Refrigerant	Type		-	R32	R32	R32
	Electronic Expansion Valve		-	EEV NOT INCLUDED	EEV NOT INCLUDED	EEV NOT INCLUDED
Sound	Sound Pressure	H/M/L	dB(A)	37 / 30 / 22	37 / 30 / 22	38 / 31 / 22
	Sound Power	Cooling		56	56	58
Dimensions	Net Weight		kg	9.4	9.4	9.4
	Shipping Weight		kg	11.9	11.9	11.9
	Net Dimensions (WxHxD)		mm	828 x 267 x 265	828 x 267 x 265	828 x 267 x 265
	Shipping Dimensions (WxHxD)		mm	886 x 317 x 335	886 x 317 x 335	886 x 317 x 335
Casing	Material		-	HIPS	HIPS	HIPS

NOTE

- Specifications may be subject to change without prior notice.
- 1)* Capacities are based on (Equivalent refrigerant piping : 5m, Level differences : 0m)
 - Cooling : Indoor temperature : 27°C DB, 19°C WB / Outdoor temperature : 35°C DB, 24°C WB
 - Heating : Indoor temperature : 20°C DB, 15°C WB / Outdoor temperature : 7°C DB, 6°C WB
- 2)* Select wire size based on the value of MCA
- 3)* Sound pressure level is obtained in an anechoic room.
 - Sound pressure level is a relative value, depending on the distance and acoustic environment.
 - Sound pressure level may differ depending on operation condition.
 - dBA = A-weighted sound pressure level
 - Reference acoustic pressure 0 dB = 20uPa
- 4)* Sound power level is an absolute value that a sound source generates.
 - dBA = A-weighted sound power level
 - Reference power : 1pW
 - Measured according to ISO 3741
- 5)* These products contain R32 (GWP=675) which is fluorinated greenhouse gas.

2. Specification

2-2. Indoor units

Wall Mounted Type - Wind-Free (A3050)

Type				Wind-Free	Wind-Free	Wind-Free
Model Name				AR07NXPXBWKNEU	AR09NXPXBWKNEU	AR12NXPXBWKNEU
Power Supply			Φ, #, V, Hz	1, 2, 220~240, 50	1, 2, 220~240, 50	1, 2, 220~240, 50
Mode			-	HP	HP	HP
Performance	Capacity	Cooling	kW	2.0	2.50	3.5
			Btu/h	6,800	8,500	11,900
		Heating	kW	2.2	3.2	3.5
			Btu/h	7,500	10,900	11,900
Power	Power Input	Cooling	W	30	30	30
		Heating		30	30	30
	Current Input	Cooling	A	0.3	0.3	0.3
		Heating		0.3	0.3	0.3
Heat exchanger	Type		-	Fin & Tube	Fin & Tube	Fin & Tube
	Material	Fin	-	Al	Al	Al
		Tube	-	Cu	Cu	Cu
	Fin Treatment		-	Green Hydrophile	Green Hydrophile	Green Hydrophile
Fan	Type		-	Cross flow Fan	Cross flow Fan	Cross flow Fan
	Quantity		EA	1	1	1
	Air Flow Rate		m³/min	9.3	9.3	10.0
			l/s	155.0	155.0	166.7
	External Static pressure	Max. (Min/Std/Max)	mmAq	-	-	-
			Pa	-	-	-
Fan Motor	Type		-	BLDC Motor	BLDC Motor	BLDC Motor
	Output x n		W	27 x 1	27 x 1	27 x 1
Piping Connections	Liquid Pipe		Type	Flare connection	Flare connection	Flare connection
			Φ, mm (inch)	6.35 (1/4")	6.35 (1/4")	6.35 (1/4")
	Gas Pipe		Type	Flare connection	Flare connection	Flare connection
			Φ, mm (inch)	9.52 (3/8")	9.52 (3/8")	9.52 (3/8")
	Heat Insulation		-	Both Liquid & Gas pipes	Both Liquid & Gas pipes	Both Liquid & Gas pipes
Drain Pipe		Φ,mm	ID18mm Hose	ID18mm Hose	ID18mm Hose	
Wiring connections	Communication	Min.	mm²	0.75	0.75	0.75
		Remark	-	F1, F2	F1, F2	F1, F2
Refrigerant	Type		-	R32	R32	R32
	Electronic Expansion Valve		-	EEV NOT INCLUDED	EEV NOT INCLUDED	EEV NOT INCLUDED
Sound	Sound Pressure	H/M/L	dB(A)	37 / 30 / 22	37 / 30 / 22	38 / 31 / 22
	Sound Power	Cooling		56	56	58
Dimensions	Net Weight		kg	10.0	10.0	10.0
	Shipping Weight		kg	12.0	12.0	12.0
	Net Dimensions (WxHxD)		mm	828 x 267 x 265	828 x 267 x 265	828 x 267 x 265
	Shipping Dimensions (WxHxD)		mm	886 x 317 x 335	886 x 317 x 335	886 x 317 x 335
Casing	Material		-	HIPS	HIPS	HIPS

NOTE

- Specifications may be subject to change without prior notice.
- 1)* Capacities are based on (Equivalent refrigerant piping : 5m, Level differences : 0m)
 - Cooling : Indoor temperature : 27°C DB, 19°C WB / Outdoor temperature : 35°C DB, 24°C WB
 - Heating : Indoor temperature : 20°C DB, 15°C WB / Outdoor temperature : 7°C DB, 6°C WB
- 2)* Select wire size based on the value of MCA
- 3)* Sound pressure level is obtained in an anechoic room.
 - Sound pressure level is a relative value, depending on the distance and acoustic environment.
 - Sound pressure level may differ depending on operation condition.
 - dBA = A-weighted sound pressure level
 - Reference acoustic pressure 0 dB = 20uPa
- 4)* Sound power level is an absolute value that a sound source generates.
 - dBA = A-weighted sound power level
 - Reference power : 1pW
 - Measured according to ISO 3741
- 5)* These products contain R32 (GWP=675) which is fluorinated greenhouse gas.

2. Specification

2-2. Indoor units

Wall Mounted Type - Wind-Free (A3050)

Type				Wind-Free	Wind-Free	Wind-Free
Model Name				AR07NXWBWKNEU	AR09NXWBWKNEU	AR12NXWBWKNEU
Power Supply			Φ, #, V, Hz	1, 2, 220~240, 50	1, 2, 220~240, 50	1, 2, 220~240, 50
Mode			-	HP	HP	HP
Performance	Capacity	Cooling	kW	2.0	2.50	3.5
			Btu/h	6,800	8,500	11,900
		Heating	kW	2.2	3.2	3.5
			Btu/h	7,500	10,900	11,900
Power	Power Input	Cooling	W	30	30	30
		Heating		30	30	30
	Current Input	Cooling	A	0.3	0.3	0.3
		Heating		0.3	0.3	0.3
Heat exchanger	Type		-	Fin & Tube	Fin & Tube	Fin & Tube
	Material	Fin	-	Al	Al	Al
		Tube	-	Cu	Cu	Cu
	Fin Treatment		-	Green Hydrophile	Green Hydrophile	Green Hydrophile
Fan	Type		-	Cross flow Fan	Cross flow Fan	Cross flow Fan
	Quantity		EA	1	1	1
	Air Flow Rate		m³/min	9.3	9.3	10.0
			l/s	155.0	155.0	166.7
	External Static pressure	Max. (Min/Std/Max)	mmAq	-	-	-
			Pa	-	-	-
Fan Motor	Type		-	BLDC Motor	BLDC Motor	BLDC Motor
	Output x n		W	27 x 1	27 x 1	27 x 1
Piping Connections	Liquid Pipe		Type	Flare connection	Flare connection	Flare connection
			Φ, mm (inch)	6.35 (1/4")	6.35 (1/4")	6.35 (1/4")
	Gas Pipe		Type	Flare connection	Flare connection	Flare connection
			Φ, mm (inch)	9.52 (3/8")	9.52 (3/8")	9.52 (3/8")
	Heat Insulation		-	Both Liquid & Gas pipes	Both Liquid & Gas pipes	Both Liquid & Gas pipes
Drain Pipe		Φ,mm	ID18mm Hose	ID18mm Hose	ID18mm Hose	
Wiring connections	Communication	Min.	mm²	0.75	0.75	0.75
		Remark	-	F1, F2	F1, F2	F1, F2
Refrigerant	Type		-	R32	R32	R32
	Electronic Expansion Valve		-	EEV NOT INCLUDED	EEV NOT INCLUDED	EEV NOT INCLUDED
Sound	Sound Pressure	H/M/L	dB(A)	37 / 30 / 22	37 / 30 / 22	38 / 31 / 22
	Sound Power	Cooling		56	56	58
Dimensions	Net Weight		kg	9.4	9.4	9.4
	Shipping Weight		kg	11.9	11.9	11.9
	Net Dimensions (WxHxD)		mm	828 x 267 x 265	828 x 267 x 265	828 x 267 x 265
	Shipping Dimensions (WxHxD)		mm	886 x 317 x 335	886 x 317 x 335	886 x 317 x 335
Casing	Material		-	HIPS	HIPS	HIPS

NOTE

- Specifications may be subject to change without prior notice.
- 1)* Capacities are based on (Equivalent refrigerant piping : 5m, Level differences : 0m)
 - Cooling : Indoor temperature : 27°C DB, 19°C WB / Outdoor temperature : 35°C DB, 24°C WB
 - Heating : Indoor temperature : 20°C DB, 15°C WB / Outdoor temperature : 7°C DB, 6°C WB
- 2)* Select wire size based on the value of MCA
- 3)* Sound pressure level is obtained in an anechoic room.
 - Sound pressure level is a relative value, depending on the distance and acoustic environment.
 - Sound pressure level may differ depending on operation condition.
 - dBA = A-weighted sound pressure level
 - Reference acoustic pressure 0 dB = 20uPa
- 4)* Sound power level is an absolute value that a sound source generates.
 - dBA = A-weighted sound power level
 - Reference power : 1pW
 - Measured according to ISO 3741
- 5)* These products contain R32 (GWP=675) which is fluorinated greenhouse gas.

2. Specification

2-2. Indoor units

Wall Mounted Type - Wind-Free (A3050)

Type				Wind-Free	Wind-Free	Wind-Free
Model Name				AR07NXCXAWKNEU	AR09NXCXAWKNEU	AR12NXCXAWKNEU
Power Supply			Φ, #, V, Hz	1, 2, 220~240, 50	1, 2, 220~240, 50	1, 2, 220~240, 50
Mode			-	HP	HP	HP
Performance	Capacity	Cooling	kW	2.0	2.50	3.5
			Btu/h	6,800	8,500	11,900
		Heating	kW	2.2	3.2	4.0
			Btu/h	7,500	10,900	13,600
Power	Power Input	Cooling	W	30	30	30
		Heating		30	30	30
	Current Input	Cooling	A	0.3	0.3	0.3
		Heating		0.3	0.3	0.3
Heat exchanger	Type		-	Fin & Tube	Fin & Tube	Fin & Tube
	Material	Fin	-	Al	Al	Al
		Tube	-	Cu	Cu	Cu
	Fin Treatment		-	Green Hydrophile	Green Hydrophile	Green Hydrophile
Fan	Type		-	Cross flow Fan	Cross flow Fan	Cross flow Fan
	Quantity		EA	1	1	1
	Air Flow Rate		m³/min	9.3	9.9	10.6
			l/s	155.0	165.0	176.7
	External Static pressure	Max. (Min/Std/Max)	mmAq	-	-	-
			Pa	-	-	-
Fan Motor	Type		-	BLDC Motor	BLDC Motor	BLDC Motor
	Output x n		W	27 x 1	27 x 1	27 x 1
Piping Connections	Liquid Pipe		Type	Flare connection	Flare connection	Flare connection
			Φ, mm (inch)	6.35 (1/4")	6.35 (1/4")	6.35 (1/4")
	Gas Pipe		Type	Flare connection	Flare connection	Flare connection
			Φ, mm (inch)	9.52 (3/8")	9.52 (3/8")	9.52 (3/8")
	Heat Insulation		-	Both Liquid & Gas pipes	Both Liquid & Gas pipes	Both Liquid & Gas pipes
Drain Pipe		Φ,mm	ID18mm Hose	ID18mm Hose	ID18mm Hose	
Wiring connections	Communication	Min.	mm²	0.75	0.75	0.75
		Remark	-	F1, F2	F1, F2	F1, F2
Refrigerant	Type		-	R32	R32	R32
	Electronic Expansion Valve		-	EEV NOT INCLUDED	EEV NOT INCLUDED	EEV NOT INCLUDED
Sound	Sound Pressure	H/M/L	dB(A)	37 / 30 / 22	37 / 30 / 22	38 / 31 / 22
	Sound Power	Cooling		56	56	58
Dimensions	Net Weight		kg	11.3	11.3	11.3
	Shipping Weight		kg	13.9	13.9	13.9
	Net Dimensions (WxHxD)		mm	828 x 295 x 265	828 x 295 x 265	828 x 295 x 265
	Shipping Dimensions (WxHxD)		mm	886 x 317 x 335	886 x 317 x 335	886 x 317 x 335
Casing	Material		-	HIPS	HIPS	HIPS

NOTE

- Specifications may be subject to change without prior notice.
- 1)* Capacities are based on (Equivalent refrigerant piping : 5m, Level differences : 0m)
 - Cooling : Indoor temperature : 27°C DB, 19°C WB / Outdoor temperature : 35°C DB, 24°C WB
 - Heating : Indoor temperature : 20°C DB, 15°C WB / Outdoor temperature : 7°C DB, 6°C WB
- 2)* Select wire size based on the value of MCA
- 3)* Sound pressure level is obtained in an anechoic room.
 - Sound pressure level is a relative value, depending on the distance and acoustic environment.
 - Sound pressure level may differ depending on operation condition.
 - dBA = A-weighted sound pressure level
 - Reference acoustic pressure 0 dB = 20uPa
- 4)* Sound power level is an absolute value that a sound source generates.
 - dBA = A-weighted sound power level
 - Reference power : 1pW
 - Measured according to ISO 3741
- 5)* These products contain R32 (GWP=675) which is fluorinated greenhouse gas.

2. Specification

2-2. Indoor units

Wind-Free 1 Way Cassette

Type				(Wind-Free) 1 Way Cassette	(Wind-Free) 1 Way Cassette
Model Name				AJ026RB1DEG/EU	AJ035RB1DEG/EU
Power Supply			Φ, #, V, Hz	1, 2, 220~240, 50	1, 2, 220~240, 50
Mode			-	HP	HP
Performance	Capacity	Cooling	kW	2.6	3.5
			Btu/h	8,900	11,900
		Heating	kW	2.9	3.8
			Btu/h	9,900	13,000
Power	Power Input	Cooling	W	45	50
		Heating		45	50
	Current Input	Cooling	A	0.23	0.25
		Heating		0.23	0.25
Heat exchanger	Type		-	Fin & Tube	Fin & Tube
	Material	Fin	-	Al	Al
		Tube	-	Cu	Cu
	Fin Treatment		-	Green Hydrophile	Green Hydrophile
Fan	Type		-	Crossflow Fan	Crossflow Fan
	Quantity		EA	1	1
	Air Flow Rate		m³/min	6.2 / 5.2 / 4.2	7.6 / 6.6 / 5.6
			l/s	103.33 / 86.67 / 70.00	126.67 / 110.00 / 93.33
	External Static Pressure	Max. (Min/Std/Max)	mmAq	-	-
			Pa	-	-
Fan Motor	Type		-	AC Motor	AC Motor
	Output x n		W	17 x 1	17 x 1
Piping Connections	Liquid Pipe		Type	Flare connection	Flare connection
			Φ, mm (inch)	6.35 (1/4)	6.35 (1/4)
	Gas Pipe		Type	Flare connection	Flare connection
			Φ, mm (inch)	9.52 (3/8)	9.52 (3/8)
	Heat insulation		-	Both liquid and gas pipes	Both liquid and gas pipes
Drain Pipe		Φ,mm	VP20 (OD 26, ID 20)	VP20 (OD 26, ID 20)	
Wiring connections	Communication	Min.	mm²	0.75	0.75
		Remark	-	F1, F2	F1, F2
Refrigerant	Type		-	R32 / R410A	R32 / R410A
	Electronic Expansion Valve		-	EEV NOT INCLUDED	EEV NOT INCLUDED
Sound	Sound Pressure	H/M/L	dB(A)	32 / 29 / 26	37 / 33 / 30
	Sound Power	Cooling		50	55
External Dimension	Net Weight		kg	10.0	10.0
	Shipping Weight		kg	12.5	12.5
	Net Dimensions (WxHxD)		mm	970 x 135 x 410	970 x 135 x 410
	Shipping Dimensions (WxHxD)		mm	1,173 x 231 x 487	1,173 x 231 x 487
Casing	Material		-	ABS	ABS

2. Specification

Type			(Wind-Free) 1 Way Cassette	(Wind-Free) 1 Way Cassette
Model Name			AJ026RB1DEG/EU	AJ035RB1DEG/EU
Panel 1	Model Name	-	PC1NWFMAN	PC1NWFMAN
	Type	-	Wind-Free	Wind-Free
	Material	-	HIPS	HIPS
	Color	-	White	White
	Net Weight	kg	4.3	4.3
	Shipping Weight	kg	6.3	6.3
	Net Dimensions (W×H×D)	mm	1,198 x 35 x 500	1,198 x 35 x 500
	Shipping Dimensions (W×H×D)	mm	1,262 x 122 x 566	1,262 x 122 x 566
Panel 2	Model Name	-	PC1NUSMAN	PC1NUSMAN
	Type	-	Normal	Normal
	Material	-	HIPS	HIPS
	Color	-	White	White
	Net Weight	kg	4.2	4.2
	Shipping Weight	kg	6.1	6.1
	Net Dimensions (W×H×D)	mm	1,180 x 25 x 460	1,180 x 25 x 460
	Shipping Dimensions (W×H×D)	mm	1,250 x 126 x 530	1,250 x 126 x 530
Drain pump	Drain pump	-	INCLUDED	INCLUDED
	Max. lifting Height / Displacement	mm / liter/h	750 / 24	750 / 24
Additional Accessories	Drain pump	External Model	-	-
		Internal Model	-	-
		Max. lifting Height / Displacement	mm / liter/h	-
	Air Filter		-	Option (Removable / Washable)

NOTE

- Specifications may be subject to change without prior notice.
- 1)* Capacities are based on (Equivalent refrigerant piping : 5m, Level differences : 0m)
 - Cooling : Indoor temperature : 27°C DB, 19°C WB / Outdoor temperature : 35°C DB, 24°C WB
 - Heating : Indoor temperature : 20°C DB, 15°C WB / Outdoor temperature : 7°C DB, 6°C WB
- 2)* Select wire size based on the value of MCA
- 3)* Sound pressure level is obtained in an anechoic room.
 - Sound pressure level is a relative value, depending on the distance and acoustic environment.
 - Sound pressure level may differ depending on operation condition.
 - dBA = A-weighted sound pressure level
 - Reference acoustic pressure 0 dB = 20uPa
- 4)* Sound power level is an absolute value that a sound source generates.
 - dBA = A-weighted sound power level
 - Reference power : 1pW
 - Measured according to ISO 3741
- 5)* These products contain R32 (GWP=675) which is fluorinated greenhouse gas.

2. Specification

2-2. Indoor units

Wind-Free 4Way CASSETTE (600x600)

Type				(Wind-Free) 4Way Cassette (600x600)	(Wind-Free) 4Way Cassette (600x600)	(Wind-Free) 4Way Cassette (600x600)
Model Name				AJ016RBNDEG/EU	AJ020RBNDEG/EU	AJ026RBNDEG/EU
Power Supply			Φ, #, V, Hz	1, 2, 220~240, 50	1, 2, 220~240, 50	1, 2, 220~240, 50
Mode			-	HP	HP	HP
Performance	Capacity	Cooling	kW	1.6	2.0	2.6
			Btu/h	5,500	6,800	8,900
		Heating	kW	2.0	2.2	2.9
			Btu/h	6,800	7,500	9,900
Power	Power Input	Cooling	W	19	19	19
		Heating		19	19	19
	Current Input	Cooling	A	0.51	0.51	0.51
		Heating		0.51	0.51	0.51
Heat exchanger	Type		-	Fin & Tube	Fin & Tube	Fin & Tube
	Material	Fin	-	Al	Al	Al
		Tube	-	Cu	Cu	Cu
	Fin Treatment		-	Green Hydrophile	Green Hydrophile	Green Hydrophile
Fan	Type		-	Turbo Fan	Turbo Fan	Turbo Fan
	Quantity		EA	1	1	1
	Air Flow Rate		m³/min	9.0 / 8.2 / 6.9	9.0 / 8.2 / 6.9	9.0 / 8.2 / 6.9
			l/s	150.00 / 136.67 / 115.00	150.00 / 136.67 / 115.00	150.00 / 136.67 / 115.00
	External Static Pressure	Max. (Min/Std/Max)	mmAq	-	-	-
			Pa	-	-	-
Fan Motor	Type		-	BLDC Motor	BLDC Motor	BLDC Motor
	Output x n		W	65 x 1	65 x 1	65 x 1
Piping Connections	Liquid Pipe		Type	Flare connection	Flare connection	Flare connection
			Φ, mm (inch)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)
	Gas Pipe		Type	Flare connection	Flare connection	Flare connection
			Φ, mm (inch)	9.52 (3/8)	9.52 (3/8)	9.52 (3/8)
	Heat insulation		-	Both liquid and gas pipes	Both liquid and gas pipes	Both liquid and gas pipes
Drain Pipe		Φ,mm	VP25 (OD 32,ID 25)	VP25 (OD 32,ID 25)	VP25 (OD 32,ID 25)	
Wiring connections	Communication	Min.	mm²	0.75	0.75	0.75
		Remark	-	F1, F2	F1, F2	F1, F2
Refrigerant	Type		-	R32 / R410A	R32 / R410A	R32 / R410A
	Electronic Expansion Valve		-	EEV NOT INCLUDED	EEV NOT INCLUDED	EEV NOT INCLUDED
Sound	Sound Pressure	H/M/L	dB(A)	33 / 29 / 24	33 / 29 / 24	33 / 29 / 24
	Sound Power	Cooling		49	49	49
External Dimension	Net Weight		kg	11.5	11.5	11.5
	Shipping Weight		kg	13.5	13.5	13.5
	Net Dimensions (WxHxD)		mm	575 x 250 x 575	575 x 250 x 575	575 x 250 x 575
	Shipping Dimensions (WxHxD)		mm	623 x 298 x 653	623 x 298 x 653	623 x 298 x 653
Casing	Material		-	Polypropylene	Polypropylene	Polypropylene

2. Specification

Type			(Wind-Free) 4Way Cassette (600x600)	(Wind-Free) 4Way Cassette (600x600)	(Wind-Free) 4Way Cassette (600x600)
Model Name			AJ016RBNDEG/EU	AJ020RBNDEG/EU	AJ026RBNDEG/EU
Panel 1	Model Name	-	PC4SUFMAN	PC4SUFMAN	PC4SUFMAN
	Type	-	Wind-Free	Wind-Free	Wind-Free
	Material	-	HIPS	HIPS	HIPS
	Color	-	DA White	DA White	DA White
	Net Weight	kg	2.7	2.7	2.7
	Shipping Weight	kg	3.9	3.9	3.9
	Net Dimensions (W×H×D)	mm	620 x 57 x 620	620 x 57 x 620	620 x 57 x 620
	Shipping Dimensions (W×H×D)	mm	670 x 120 x 655	670 x 120 x 655	670 x 120 x 655
Panel 2	Model Name	-	PC4SUSMBN	PC4SUSMBN	PC4SUSMBN
	Type	-	Normal (Waffle Type)	Normal (Waffle Type)	Normal (Waffle Type)
	Material	-	HIPS	HIPS	HIPS
	Color	-	White	White	White
	Net Weight	kg	2.7	2.7	2.7
	Shipping Weight	kg	3.5	3.5	3.5
	Net Dimensions (W×H×D)	mm	620 x 45 x 620	620 x 45 x 620	620 x 45 x 620
	Shipping Dimensions (W×H×D)	mm	667 x 102 x 655	667 x 102 x 655	667 x 102 x 655
Drain pump	Drain pump	-	Included	Included	Included
	Max. lifting Height / Displacement	mm / liter/h	750 / 24	750 / 24	750 / 24
Additional Accessories	Drain pump	External Model	-	-	-
		Internal Model	-	-	-
		Max. lifting Height / Displacement	mm / liter/h	-	-
	Air Filter		-	Option (Removable / Washable)	Option (Removable / Washable)

NOTE

- Specifications may be subject to change without prior notice.
- 1)* Capacities are based on (Equivalent refrigerant piping : 5m, Level differences : 0m)
 - Cooling : Indoor temperature : 27°C DB, 19°C WB / Outdoor temperature : 35°C DB, 24°C WB
 - Heating : Indoor temperature : 20°C DB, 15°C WB / Outdoor temperature : 7°C DB, 6°C WB
- 2)* Select wire size based on the value of MCA
- 3)* Sound pressure level is obtained in an anechoic room.
 - Sound pressure level is a relative value, depending on the distance and acoustic environment.
 - Sound pressure level may differ depending on operation condition.
 - dBA = A-weighted sound pressure level
 - Reference acoustic pressure 0 dB = 20uPa
- 4)* Sound power level is an absolute value that a sound source generates.
 - dBA = A-weighted sound power level
 - Reference power : 1pW
 - Measured according to ISO 3741
- 5)* These products contain R32 (GWP=675) which is fluorinated greenhouse gas.

2. Specification

2-2. Indoor units

Wind-Free 4Way CASSETTE (600x600)

Type				(Wind-Free) 4Way Cassette (600x600)	(Wind-Free) 4Way Cassette (600x600)
Model Name				AJ035RBNDEG/EU	AJ052RBNDEG/EU
Power Supply			Φ, #, V, Hz	1, 2, 220~240, 50	1, 2, 220~240, 50
Mode			-	HP	HP
Performance	Capacity	Cooling	kW	3.5	5.2
			Btu/h	11,900	17,700
		Heating	kW	3.8	5.6
			Btu/h	13,000	19,100
Power	Power Input	Cooling	W	22	28
		Heating		22	28
	Current Input	Cooling	A	0.52	0.53
		Heating		0.52	0.53
Heat exchanger	Type		-	Fin & Tube	Fin & Tube
	Material	Fin	-	Al	Al
		Tube	-	Cu	Cu
	Fin Treatment		-	Green Hydrophile	Green Hydrophile
Fan	Type		-	Turbo Fan	Turbo Fan
	Quantity		EA	1	1
	Air Flow Rate		m³/min	10.5 / 9.0 / 7.4	10.5 / 9.0 / 7.4
			l/s	175.00 / 150.00 / 123.33	175.00 / 150.00 / 123.33
	External Static Pressure	Max. (Min/Std/Max)	mmAq	-	-
			Pa	-	-
Fan Motor	Type		-	BLDC Motor	BLDC Motor
	Output x n		W	65 x 1	65 x 1
Piping Connections	Liquid Pipe		Type	Flare connection	Flare connection
			Φ, mm (inch)	6.35 (1/4)	6.35 (1/4)
	Gas Pipe		Type	Flare connection	Flare connection
			Φ, mm (inch)	9.52 (3/8)	12.7 (1/2)
	Heat insulation		-	Both liquid and gas pipes	Both liquid and gas pipes
Drain Pipe		Φ,mm	VP25 (OD 32,ID 25)	VP25 (OD 32,ID 25)	
Wiring connections	Communication	Min.	mm²	0.75	0.75
		Remark	-	F1, F2	F1, F2
Refrigerant	Type		-	R32 / R410A	R32 / R410A
	Electronic Expansion Valve		-	EEV NOT INCLUDED	EEV NOT INCLUDED
Sound	Sound Pressure	H/M/L	dB(A)	35 / 31 / 27	39 / 36 / 32
	Sound Power	Cooling		53	55
External Dimension	Net Weight		kg	11.5	11.8
	Shipping Weight		kg	13.5	13.8
	Net Dimensions (WxHxD)		mm	575 x 250 x 575	575 x 250 x 575
	Shipping Dimensions (WxHxD)		mm	623 x 298 x 653	623 x 298 x 653
Casing	Material		-	Polypropylene	Polypropylene

2. Specification

Type			(Wind-Free) 4Way Cassette (600x600)	(Wind-Free) 4Way Cassette (600x600)
Model Name			AJ035RBNDEG/EU	AJ052RBNDEG/EU
Panel 1	Model Name	-	PC4SUFMAN	PC4SUFMAN
	Type	-	Wind-Free	Wind-Free
	Material	-	HIPS	HIPS
	Color	-	DA White	DA White
	Net Weight	kg	2.7	2.7
	Shipping Weight	kg	3.9	3.9
	Net Dimensions (W×H×D)	mm	620 x 57 x 620	620 x 57 x 620
	Shipping Dimensions (W×H×D)	mm	670 x 120 x 655	670 x 120 x 655
Panel 2	Model Name	-	PC4SUSMBN	PC4SUSMBN
	Type	-	Normal (Waffle Type)	Normal (Waffle Type)
	Material	-	HIPS	HIPS
	Color	-	White	White
	Net Weight	kg	2.7	2.7
	Shipping Weight	kg	3.5	3.5
	Net Dimensions (W×H×D)	mm	620 x 45 x 620	620 x 45 x 620
	Shipping Dimensions (W×H×D)	mm	667 x 102 x 655	667 x 102 x 655
Drain pump	Drain pump	-	Included	Included
	Max. lifting Height / Displacement	mm / liter/h	750 / 24	750 / 24
Additional Accessories	Drain pump	External Model	-	-
		Internal Model	-	-
		Max. lifting Height / Displacement	mm / liter/h	-
	Air Filter		-	Option (Removable / Washable)

NOTE

- Specifications may be subject to change without prior notice.
- 1)* Capacities are based on (Equivalent refrigerant piping : 5m, Level differences : 0m)
 - Cooling : Indoor temperature : 27°C DB, 19°C WB / Outdoor temperature : 35°C DB, 24°C WB
 - Heating : Indoor temperature : 20°C DB, 15°C WB / Outdoor temperature : 7°C DB, 6°C WB
- 2)* Select wire size based on the value of MCA
- 3)* Sound pressure level is obtained in an anechoic room.
 - Sound pressure level is a relative value, depending on the distance and acoustic environment.
 - Sound pressure level may differ depending on operation condition.
 - dBA = A-weighted sound pressure level
 - Reference acoustic pressure 0 dB = 20uPa
- 4)* Sound power level is an absolute value that a sound source generates.
 - dBA = A-weighted sound power level
 - Reference power : 1pW
 - Measured according to ISO 3741
- 5)* These products contain R32 (GWP=675) which is fluorinated greenhouse gas.

2. Specification

2-2. Indoor units

Duct - Slim Duct, MSP Duct

Type				Slim Duct	Slim Duct	MSP Duct
Model Name				AJ026RBLDEG/EU	AJ035RBLDEG/EU	AJ052RBMDEG/EU
Power Supply			Φ, #, V, Hz	1, 2, 220~240, 50	1, 2, 220~240, 50	1, 2, 220~240, 50
Mode			-	HP	HP	HP
Performance	Capacity	Cooling	kW	2.6	3.5	5.2
			Btu/h	8,900	11,900	17,700
		Heating	kW	2.9	3.8	5.6
			Btu/h	9,900	13,000	19,100
Power	Power Input	Cooling	W	80	80	170
		Heating		80	80	170
	Current Input	Cooling	A	0.4	0.4	1.04
		Heating		0.4	0.4	1.04
Heat exchanger	Type		-	Fin & Tube	Fin & Tube	Fin & Tube
	Material	Fin	-	Al	Al	Al
		Tube	-	Cu	Cu	Cu
	Fin Treatment		-	Green Hydrophile	Green Hydrophile	Green Hydrophile
Fan	Type		-	Sirroco Fan	Sirroco Fan	Sirroco Fan
	Quantity		EA	2	2	2
	Air Flow Rate		m³/min	8.6 / 7.6 / 6.6	9.8 / 8.8 / 7.8	16.3 / 15.0 / 13.5
			l/s	143 / 127 / 110	163 / 147 / 130	272 / 250 / 225
	External Static Pressure	Max. (Min/Std/Max)	mmAq	0 / 2 / 4	0 / 2 / 4	0 / 4 / 6
			Pa	0 / 19.6 / 39.2	0 / 19.6 / 39.2	0 / 39.2 / 58.8
Fan Motor	Type		-	AC Motor	AC Motor	AC Motor
	Output x n		W	25 x 1	25 x 1	200 x 1
Piping Connections	Liquid Pipe		Type	Flare connection	Flare connection	Flare connection
			Φ, mm (inch)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)
	Gas Pipe		Type	Flare connection	Flare connection	Flare connection
			Φ, mm (inch)	9.52 (3/8)	9.52 (3/8)	12.7 (1/2)
	Heat insulation		-	Both liquid and gas pipes	Both liquid and gas pipes	Both liquid and gas pipes
Drain Pipe		Φ,mm	VP25 (OD 32, ID 25)	VP25 (OD 32, ID 25)	VP25 (OD 32, ID 25)	
Wiring connections	Communication	Min.	mm²	0.75	0.75	0.75
		Remark	-	F1, F2	F1, F2	F1, F2
Refrigerant	Type		-	R32 / R410A	R32 / R410A	R32 / R410A
	Electronic Expansion Valve		-	EEV NOT INCLUDED	EEV NOT INCLUDED	EEV NOT INCLUDED
Sound	Sound Pressure	H/M/L	dB(A)	30 / 28 / 25	32 / 30 / 27	42 / 41 / 39
	Sound Power	Cooling		53	53	59
External Dimension	Net Weight		kg	23.3	23.3	28.3
	Shipping Weight		kg	27.8	27.8	33.5
	Net Dimensions (WxHxD)		mm	900 x 199 x 600	900 x 199 x 600	900 x 260 x 480
	Shipping Dimensions (WxHxD)		mm	1,151 x 280 x 709	1,151 x 280 x 709	1,170 x 340 x 595

2. Specification

Type				Slim Duct	Slim Duct	MSP Duct
Model Name				AJ026RBLDEG/EU	AJ035RBLDEG/EU	AJ052RBMDEG/EU
Casing	Material	-		EGI Steel Plate	EGI Steel Plate	EGI Steel Plate
Drain pump	Drain pump	-		-	-	-
	Max. lifting Height / Displacement	mm / liter/h		-	-	-
Additional Accessories	Drain pump	External Model	-	-	-	-
		Internal Model	-	Optional MDP-E075SEE3	Optional MDP-E075SEE3	Optional MDP-M075SGU3
		Max. lifting Height / Displacement	mm / liter/h	750/24	750/24	750/24
	Air Filter		-	Removable / Washable	Removable / Washable	Removable / Washable

NOTE

- Specifications may be subject to change without prior notice.
- 1)* Capacities are based on (Equivalent refrigerant piping : 5m, Level differences : 0m)
 - Cooling : Indoor temperature : 27°C DB, 19°C WB / Outdoor temperature : 35°C DB, 24°C WB
 - Heating : Indoor temperature : 20°C DB, 15°C WB / Outdoor temperature : 7°C DB, 6°C WB
- 2)* Select wire size based on the value of MCA
- 3)* Sound pressure level is obtained in an anechoic room.
 - Sound pressure level is a relative value, depending on the distance and acoustic environment.
 - Sound pressure level may differ depending on operation condition.
 - dBA = A-weighted sound pressure level
 - Reference acoustic pressure 0 dB = 20uPa
- 4)* Sound power level is an absolute value that a sound source generates.
 - dBA = A-weighted sound power level
 - Reference power : 1pW
 - Measured according to ISO 3741
- 5)* These products contain R32 (GWP=675) which is fluorinated greenhouse gas.

3. Electric Characteristics

Capacity (Cooling) kW	Model	Power Supply		Voltage Range		Nominal Running Current [A]		Current [A]		ODU Fan Motor
		Hz	Voltage	Min. (-15%)	Max. (+15%)					
						Cooling	Heating	MCA	MFA	kW
4.0	AJ040NCJ2EG**	50	220~240	198	264	4.1	4.1	9.8	11.25	0.04
5.0	AJ050NCJ2EG**	50	220~240	198	264	5.6	5.9	11.8	13.75	0.04
5.2	AJ052RCJ3EG**	50	220~240	198	264	5.5	6.1	11.9	13.75	0.125
6.8	AJ068RCJ3EG**	50	220~240	198	264	8.1	8.2	17.5	20.75	0.125

NOTE

- MCA : Minimum circuit amperes
- MFA : Maximum fuse amperes
- Select wire size based on the value of MCA

4. Combination Table

4-1. AJ040NCJ2EG/EU

COOLING

Outdoor unit		A	B	Cooling Capacity		Capacity			Power Consumption			Current			Effic. NOM. Cooling. At 35°C/27°C	SEASONAL EFFICIENCY (ACCORDING EN14825)	SEER	Qce
				W		W			W			A						kWh
				A	B	MIN	STD	MAX	MIN	STD	MAX	MIN	STD	MAX	EER	Class		
AJ040NCJ2EG	2 Unit	7	7	2000	2000	1300	4000	4700	300	900	1250	1.7	4.1	5.7	4.44	A+++	8.54	164
		7	9	1780	2220	1300	4000	4700	350	920	1270	1.9	4.2	5.8	4.35	A+++	8.51	165
		7	12	1450	2550	1300	4000	4700	350	930	1280	1.9	4.3	5.9	4.3	A+++	8.51	165
		9	9	2000	2000	1300	4000	4700	350	940	1290	1.9	4.3	5.9	4.26	A+++	8.51	165
		9	12	1670	2330	1300	4000	4700	350	950	1300	1.9	4.3	5.9	4.21	A+++	8.51	165

HEATING

Outdoor unit		A	B	Heating Capacity		Capacity			Power Consumption			Current			Effic. NOM. Heating. At 7°C/20°C	SEASONAL EFFICIENCY (ACCORDING EN14825)	SCOP	P design	Qhe
				W		W			W			A							
				A	B	MIN	STD	MAX	MIN	STD	MAX	MIN	STD	MAX	COP	Class		kW	kWh
AJ040NCJ2EG	2 Unit	7	7	2100	2100	1000	4200	4700	280	900	1180	1.4	4.1	5.4	4.67	A++	4.64	3.05	922
		7	9	1840	2360	1000	4200	4700	280	920	1190	1.4	4.2	5.4	4.57	A++	4.61	3.05	927
		7	12	1550	2650	1000	4200	4700	280	930	1200	1.4	4.3	5.5	4.52	A++	4.61	3.05	927
		9	9	2100	2100	1000	4200	4700	280	940	1210	1.4	4.3	5.5	4.47	A++	4.61	3.05	927
		9	12	1800	2400	1000	4200	4700	280	950	1220	1.4	4.3	5.6	4.42	A++	4.61	3.05	927

NOTE

- EER and COP declared only for the purpose of tax deductions in force at the time of the creation of this catalog.
- The above is the value for connecting with the following indoor units.
 - A3050 Good1 : AR07MXWSAWKNEU, AR09MXWSAWKNEU, AR12MXWSAWKNEU
- You can not connect a single unit.
- Power consumption include indoor unit power.

4. Combination Table

4-2. AJ050NCJ2EG/EU

COOLING

Outdoor unit		A	B	Cooling Capacity		Capacity			Power Consumption			Current			Effic. NOM. Cooling. At 35°C/27°C	SEASONAL EFFICIENCY (ACCORDING EN14825)	SEER	Qce
				W		W			W			A						kWh
				A	B	MIN	STD	MAX	MIN	STD	MAX	MIN	STD	MAX	EER	Class		
AJ050NCJ2EG	2 Unit	7	7	2000	2000	1300	4000	4700	350	980	1290	1.9	4.5	5.9	4.08	A+++	8.51	165
		7	9	2040	2560	1300	4600	5200	350	1120	1520	1.9	5.1	7	4.11	A+++	8.51	189
		7	12	1820	3180	1400	5000	5500	350	1230	1510	1.9	5.6	6.9	4.07	A+++	8.51	206
		9	9	2500	2500	1400	5000	5500	350	1220	1500	1.9	5.6	6.9	4.1	A+++	8.54	205
		9	12	2080	2920	1400	5000	5500	350	1230	1510	1.9	5.6	6.9	4.07	A+++	8.51	206
		12	12	2500	2500	1400	5000	5500	350	1240	1520	1.9	5.7	7	4.03	A+++	8.51	206

HEATING

Outdoor unit		A	B	Heating Capacity		Capacity			Power Consumption			Current			Effic. NOM. Heating. At 7°C/20°C	SEASONAL EFFICIENCY (ACCORDING EN14825)	SCOP	P design	Qhe
				W		W			W			A							
				A	B	MIN	STD	MAX	MIN	STD	MAX	MIN	STD	MAX	COP	Class	kW	kWh	
AJ050NCJ2EG	2 Unit	7	7	2200	2200	1400	4400	4700	280	1010	1210	1.4	4.6	5.5	4.36	A++	4.61	3.05	927
		7	9	2230	2870	1400	5100	5460	280	1310	1610	1.4	6	7.4	3.89	A++	4.61	4.21	1277
		7	12	2060	3540	1400	5600	6300	280	1290	1710	1.4	5.9	7.8	4.34	A++	4.61	4.21	1277
		9	9	2800	2800	1400	5600	6300	280	1280	1700	1.4	5.9	7.8	4.38	A++	4.64	4.21	1270
		9	12	2400	3200	1400	5600	6300	280	1290	1710	1.4	5.9	7.8	4.34	A++	4.61	4.21	1277
		12	12	2800	2800	1400	5600	6300	280	1300	1720	1.4	5.9	7.9	4.31	A++	4.61	4.21	1277

NOTE

- EER and COP declared only for the purpose of tax deductions in force at the time of the creation of this catalog.
- The above is the value for connecting with the following indoor units.
 - A3050 Good1 : AR07MXWSAWKNEU, AR09MXWSAWKNEU, AR12MXWSAWKNEU
- You can not connect a single unit.
- Power consumption include indoor unit power.

4. Combination Table

4-3. AJ052RCJ3EG/EU

COOLING

Outdoor unit		A	B	C	Cooling Capacity			Capacity			Power Consumption			Current			Effic. NOM. Cooling. At 35°C/27°C	SEASONAL EFFICIENCY (ACCORDING EN14825)	SEER	Qce
					W			W			W			A						
					A	B	C	MIN	STD	MAX	MIN	STD	MAX	MIN	STD	MAX	EER	Class	kWh	
AJ052MCJ3EH	2 Unit	7	7		2000	2000		1100	4000	4800	320	1160	1630	2.0	5.1	7.5	3.45	A+	6.08	230
		7	9		2040	2560		1100	4600	5520	320	1210	1850	2.0	5.4	8.5	3.80	A+	6.02	267
		7	12		1820	3180		1100	5000	6290	320	1340	2000	2.0	5.9	9.2	3.73	A++	6.12	286
		7	18		1490	3710		1200	5200	6600	320	1370	2040	2.0	6.1	9.3	3.80	A+	5.95	306
		9	9		2500	2500		1100	5000	5800	320	1350	1980	2.0	6.0	9.1	3.70	A++	6.40	273
		9	12		2080	2920		1100	5000	6400	320	1360	2020	2.0	6.0	9.2	3.68	A++	6.13	286
		9	18		1730	3470		1200	5200	6800	320	1380	2070	2.0	6.1	9.5	3.77	A+	5.95	306
		12	12		2600	2600		1100	5200	6560	320	1380	2040	2.0	6.1	9.3	3.77	A+	5.88	309
	3 Unit	7	7	7	1730	1730	1740	1450	5200	6380	330	1320	2020	2.0	5.9	9.2	3.94	A+	5.78	315
		7	7	9	1600	1600	2000	1450	5200	6490	330	1330	2040	2.0	5.9	9.3	3.91	A+	5.77	315
		7	7	12	1390	1390	2420	1450	5200	6800	330	1280	2070	2.0	5.7	9.5	4.06	A+	5.81	313
		7	9	9	1480	1860	1860	1450	5200	6600	330	1290	2040	2.0	5.7	9.3	4.03	A+	5.83	312
		7	9	12	1300	1630	2270	1450	5200	6800	330	1270	2070	2.0	5.6	9.5	4.09	A+	5.81	313
		9	9	9	1730	1730	1740	1450	5200	6800	330	1250	2070	2.0	5.5	9.5	4.16	A+	5.84	312
9		9	12	1530	1530	2140	1450	5200	6800	330	1250	2070	2.0	5.5	9.5	4.16	A++	6.11	298	

4. Combination Table

HEATING

Outdoor unit		A	B	C	Heating Capacity			Capacity			Power Consumption			Current			Effic. NOM. Heating. At 7°C/20°C	SEASONAL EFFICIENCY (ACCORDING EN14825)	SCOP	P design	Qhe
					W			W			W			A							
					A	B	C	MIN	STD	MAX	MIN	STD	MAX	MIN	STD	MAX				EER	
AJ052MCJ3EH	2 Unit	7	7		2200	2200		950	4400	5060	280	1180	1510	1.7	5.2	6.9	3.73	A+	4.00	3.05	1068
		7	9		2040	3060		950	5100	5870	280	1350	1830	1.7	6.0	8.4	3.78	A	3.95	4.21	1490
		7	12		1990	3610		950	5600	6440	280	1390	1860	1.7	6.2	8.5	4.03	A	3.94	4.91	1741
		7	18		1610	4390		950	6000	6900	280	1610	1860	1.7	7.1	8.5	3.73	A	3.88	4.28	1545
		9	9		2900	2900		950	5800	6300	280	1550	1910	1.7	6.9	8.7	3.74	A+	4.01	4.91	1715
		9	12		2620	3180		950	5800	6300	280	1550	1910	1.7	6.9	8.7	3.74	A	3.94	4.91	1741
		9	18		2240	4060		950	6300	7300	280	1690	1830	1.7	7.5	8.4	3.73	A	3.88	4.28	1545
		12	12		2950	2950		950	5900	6880	280	1580	1860	1.7	7.0	8.5	3.73	A	3.88	4.28	1548
	3 Unit	7	7	7	1930	1930	1940	1000	5800	6760	280	1420	1840	1.7	6.3	8.4	4.08	A	3.90	4.91	1760
		7	7	9	1690	1690	2520	1000	5900	6840	280	1430	1840	1.7	6.3	8.4	4.13	A	3.90	4.91	1760
		7	7	12	1650	1650	3000	1000	6300	7300	280	1410	1830	1.7	6.3	8.4	4.47	A	3.90	4.91	1760
		7	9	9	1500	2250	2250	1000	6000	6920	280	1400	1840	1.7	6.2	8.4	4.29	A	3.90	4.91	1760
		7	9	12	1460	2190	2650	1000	6300	7300	280	1360	1830	1.7	6.1	8.4	4.63	A	3.90	4.91	1760
		9	9	9	2100	2100	2100	1000	6300	7300	280	1320	1830	1.7	6.1	8.4	4.77	A	3.90	4.91	1760
		9	9	12	1850	1850	2600	1000	6300	7300	280	1320	1830	1.7	6.1	8.4	4.77	A	3.90	4.91	1762

NOTE

- EER and COP declared only for the purpose of tax deductions in force at the time of the creation of this catalog.
- The above is the value for connecting with the following indoor units.
 - A3050 F04 : AR07/09/12MXWSAWKNEU, AR18MSWSAWKNEU
- You can not connect a single unit.
- Power consumption include indoor unit power.

4. Combination Table

4-4. AJ068RCJ3EG/EU

COOLING

Outdoor unit		A	B	C	Cooling Capacity			Capacity			Power Consumption			Current			Effic. NOM. Cooling. At 35°C/27°C	SEASONAL EFFICIENCY (ACCORDING EN14825)	SEER	Qce
					W			W			W			A						
					A	B	C	MIN	STD	MAX	MIN	STD	MAX	MIN	STD	MAX	EER	Class	kWh	
AJ068MCJ3EH	2 Unit	7	7		2000	2000		1300	4000	4800	420	1260	1480	2.3	5.6	6.8	3.17	A+	5.96	235
		7	9		2000	2500		1300	4500	5520	420	1340	1680	2.3	5.9	7.7	3.36	A+	5.88	268
		7	12		2000	3500		1300	5500	6550	420	1610	2470	2.3	7.1	11.3	3.42	A+	5.66	340
		7	18		1860	4640		1300	6500	7740	420	1870	2690	2.3	8.3	12.3	3.48	A+	6.04	377
		9	9		2500	2500		1300	5000	5950	420	1450	2260	2.3	6.4	10.3	3.45	A+	5.95	294
		9	12		2500	3500		1300	6000	7140	420	1730	2670	2.3	7.7	12.2	3.47	A+	5.90	356
		9	18		2270	4530		1380	6800	8090	430	1870	2660	2.3	8.3	12.2	3.64	A+	6.02	395
		12	12		3250	3250		1300	6500	7740	420	1820	2700	2.3	8.1	12.4	3.57	A+	6.02	378
		12	18		2800	4000		1380	6800	8090	430	1870	2670	2.3	8.3	12.2	3.64	A+	6.02	394
		18	18		3400	3400		1380	6800	8090	430	1860	2660	2.3	8.3	12.2	3.66	A+	6.06	393
	3 Unit	7	7	7	2000	2000	2000	1800	6000	7400	440	1760	2650	2.3	7.8	12.1	3.41	A+	6.00	350
		7	7	9	2000	2000	2500	1800	6500	8000	440	1840	2690	2.3	8.2	12.3	3.53	A++	6.11	372
		7	7	12	1810	1810	3180	1800	6800	8400	440	1910	2700	2.3	8.5	12.4	3.56	A+	6.07	392
		7	7	18	1510	1510	3780	1800	6800	8400	440	1860	2690	2.3	8.3	12.3	3.66	A+	6.09	391
		7	9	9	1860	2320	2320	1800	6500	8000	440	1860	2690	2.3	8.3	12.3	3.49	A++	6.10	373
		7	9	12	1700	2130	2970	1800	6800	8400	440	1840	2690	2.3	8.2	12.3	3.70	A+	6.06	393
		7	9	18	1430	1790	3580	1800	6800	8400	440	1870	2690	2.3	8.3	12.3	3.64	A+	6.08	391
		7	12	12	1520	2640	2640	1800	6800	8400	440	1840	2700	2.3	8.2	12.4	3.70	A+	6.08	391
		7	12	18	1300	2270	3230	1800	6800	8400	440	1870	2700	2.3	8.3	12.4	3.64	A+	6.07	392
		9	9	9	2260	2270	2270	1800	6800	8400	440	1830	2690	2.3	8.1	12.3	3.72	A+	6.07	392
		9	9	12	2000	2000	2800	1800	6800	8400	440	1830	2700	2.3	8.1	12.4	3.72	A+	6.04	394
		9	9	18	1700	1700	3400	1800	6800	8400	440	1830	2690	2.3	8.1	12.3	3.72	A+	6.08	392
		9	12	12	1780	2510	2510	1800	6800	8400	440	1820	2700	2.3	8.1	12.4	3.74	A+	6.08	391
		9	12	18	1550	2160	3090	1800	6800	8400	440	1840	2700	2.3	8.2	12.4	3.70	A+	6.07	392
		12	12	12	2260	2270	2270	1800	6800	8400	440	1800	2710	2.3	8.1	12.4	3.78	A+	6.09	391

4. Combination Table

HEATING

Outdoor unit		A	B	C	Heating Capacity			Capacity			Power Consumption			Current			Effic. NOM. Heating. At 7°C/20°C	SEASONAL EFFICIENCY (ACCORDING EN14825)	SCOP	P design	Qhe
					W			W			W			A							
					A	B	C	MIN	STD	MAX	MIN	STD	MAX	MIN	STD	MAX	EER	Class	kWh	kWh	
AJ068MCJ3EH	2 Unit	7	7		2200	2200		1400	4400	5060	380	1210	1600	1.9	5.4	7.3	3.64	A+	4.00	3.05	1068
		7	9		2200	3300		1400	5500	6330	380	1450	2000	1.9	6.4	9.2	3.79	A	3.95	4.21	1489
		7	12		2200	4000		1400	6200	7130	380	1630	2300	1.9	7.2	10.5	3.80	A	3.88	4.52	1632
		7	18		2090	5710		1400	7800	8970	380	1940	2700	1.9	8.6	12.4	4.02	A+	4.02	5.65	1969
		9	9		3300	3300		1400	6600	7590	380	1850	2600	1.9	8.2	11.9	3.57	A+	4.00	4.91	1715
		9	12		3300	4000		1400	7300	8400	380	1910	2600	1.9	8.5	11.9	3.82	A	3.95	5.09	1801
		9	18		2770	5030		1400	7800	8970	380	2010	2800	1.9	8.9	12.8	3.88	A+	4.00	5.09	1779
		12	12		3900	3900		1400	7800	8970	380	1950	2700	1.9	8.7	12.4	4.00	A+	4.00	5.09	1779
		12	18		3200	4800		1400	8000	9200	380	2050	2800	1.9	9.1	12.8	3.90	A+	4.00	5.09	1779
		18	18		4000	4000		1400	8000	9200	380	2040	2800	1.9	9.1	12.8	3.92	A+	4.02	5.65	1971
	3 Unit	7	7	7	2200	2200	2200	1400	6600	8100	380	1710	2400	1.9	7.6	11	3.86	A	3.93	5.65	2012
		7	7	9	2200	2200	3300	1400	7700	9500	380	1780	2500	1.9	7.9	11.4	4.33	A	3.93	5.65	2012
		7	7	12	2100	2100	3800	1400	8000	9800	380	1870	2600	1.9	8.3	11.9	4.28	A	3.95	5.65	2002
		7	7	18	1690	1690	4620	1400	8000	9800	380	1910	2600	1.9	8.5	11.9	4.19	A	3.95	5.65	2002
		7	9	9	2000	3000	3000	1400	8000	9800	380	1830	2500	1.9	8.1	11.4	4.37	A+	4.00	5.65	1976
		7	9	12	1850	2780	3370	1400	8000	9800	380	1860	2600	1.9	8.3	11.9	4.30	A	3.95	5.65	2002
		7	9	18	1530	2300	4170	1400	8000	9800	380	1870	2600	1.9	8.3	11.9	4.28	A	3.95	5.65	2002
		7	12	12	1720	3140	3140	1400	8000	9800	380	1900	2600	1.9	8.4	11.9	4.21	A	3.95	5.65	2002
		7	12	18	1450	2620	3930	1400	8000	9800	380	1890	2600	1.9	8.4	11.9	4.23	A	3.95	5.65	2002
		9	9	9	2660	2670	2670	1400	8000	9800	380	1850	2600	1.9	8.2	11.9	4.32	A	3.95	5.65	2002
		9	9	12	2490	2490	3020	1400	8000	9800	380	1830	2600	1.9	8.1	11.9	4.37	A+	4.00	5.65	1978
		9	9	18	2100	2100	3800	1400	8000	9800	380	1870	2600	1.9	8.3	11.9	4.28	A+	4.00	5.65	1978
		9	12	12	2340	2830	2830	1400	8000	9800	380	1840	2600	1.9	8.2	11.9	4.35	A	3.95	5.65	2002
		9	12	18	1980	2410	3610	1400	8000	9800	380	1900	2700	1.9	8.4	12.4	4.21	A	3.95	5.65	2002
		12	12	12	2660	2670	2670	1400	8000	9800	380	1800	2600	1.9	8.0	11.9	4.44	A+	4.00	5.65	1978

NOTE


- EER and COP declared only for the purpose of tax deductions in force at the time of the creation of this catalog.
- The above is the value for connecting with the following indoor units.
 - A3050 F04 : AR07/09/12MXWSAWKNEU, AR18MSWSAWKNEU
- You can not connect a single unit.
- Power consumption include indoor unit power.

5. Dimensional Drawing

5-1. Outdoor units

- AJ040/050NCJ2EG**

Unit : mm [inches]




NO	Name	Description
1	Refrigerant gas pipe	Φ9.52 (Φ3/8) X 2EA
2	Refrigerant liquid pipe	Φ6.35 (Φ1/4) X 2EA
3	Drain hole	Connection with the provided drain plug.

5. Dimensional Drawing

5-1. Outdoor units

- AJ052RCJ3EG**

Unit : mm [inches]




NO	Name	Description
1	Refrigerant gas pipe	Φ9.52 (Φ3/8) x 2 EA
2		Φ12.7 (Φ1/2) x 1 EA
3	Refrigerant liquid pipe	Φ6.35 (Φ1/4) X 3EA
4	Drain hole	Connection with the provided drain plug.

5. Dimensional Drawing

5-1. Outdoor units

- AJ068RCJ3EG**

Unit : mm [inches]




NO	Name	Description
1	Refrigerant gas pipe	Φ9.52 (Φ3/8) x1 EA
2		Φ12.7 (Φ1/2) x 2 EA
3	Refrigerant liquid pipe	Φ6.35 (Φ1/4) X 3EA
4	Drain hole	Connection with the provided drain plug.

5. Dimensional Drawing

5-2. Indoor unit

2 A3050 Good1 : AR07/09/12NXWSAURN**

Unit : mm [inches]




NO	Name	Description
		2.0, 2.5, 3.5kW
1	Liquid pipe connection	Φ6.35 (Φ1/4)
2	Gas pipe connection	Φ9.52 (Φ3/8)
3	Drain pipe connection	ID18mm Hose
4	Power & Communication wiring conduit	-

5. Dimensional Drawing

5-2. Indoor unit

4 New Boracay : AR07/09/12NXFHBWKN**

Unit : mm [inches]




NO	Name	Description
		2.0, 2.5, 3.5kW
1	Liquid pipe connection	Φ6.35 (Φ1/4)
2	Gas pipe connection	Φ9.52 (Φ3/8)
3	Drain pipe connection	ID18mm Hose
4	Power & Communication wiring conduit	-

5. Dimensional Drawing

5-2. Indoor unit

5 Wind-Free : AR07/09/12NXCXAWKN**

Unit : mm [inches]




NO	Name	Description
		2.0, 2.5, 3.5kW
1	Liquid pipe connection	Φ6.35 (Φ1/4)
2	Gas pipe connection	Φ9.52 (Φ3/8)
3	Drain pipe connection	ID18mm Hose
4	Power & Communication wiring conduit	-

5. Dimensional Drawing

5-2. Indoor unit

6 Wind-Free : AR07/09/12NXPXBWKN**, AR07/09/12NXWXBWKN**, AR07/09/12NXWXCWKN**

Unit : mm [inches]




NO	Name	Description
		2.0, 2.5, 3.5kW
1	Liquid pipe connection	Φ6.35 (Φ1/4)
2	Gas pipe connection	Φ9.52 (Φ3/8)
3	Drain pipe connection	ID18mm Hose
4	Power & Communication wiring conduit	-

5. Dimensional Drawing

5-2. Indoor unit

7 Wind-Free 1Way Cassette : AJ026/035RB1DEG**

Units : mm [inches]



No	Name	Description	No	Name	Description
1	Gas pipe connection	Ø12.7 (1/2")	5	Air outlet louver	-
2	Liquid pipe connection	Ø6.35 (1/4")	6	Air inlet grille	-
3	Drain hose connection	VP20 (OD26, ID20)			
4	Power supply/Communication wiring conduit	-			

NOTE


- As for suspension bolt, please use M8 ~ 10. (Produced at local site)

5. Dimensional Drawing

5-2. Indoor unit

8 Wind-Free 4Way Cassette (600x600) : AJ016/020/026/035/052RBNDEG**

Units : mm [inches]



NO	Name	Description				
		1.6 kW	2.0 kW	2.6 kW	3.5 kW	5.2 kW
1	Liquid pipe connection	Φ6.35 (1/4)				
2	Gas pipe connection	Φ9.52 (3/8)				Φ12.7(1/2)
3	Drain pipe connection	VP-25 (OD 32 mm, ID 25 mm)				
4	Power & Communication wiring conduit	-				
5	Knock hole for Fresh air intake	Φ101(4), Use M4 Screw				

NOTE


- As for suspension bolt, please use M10. (Produced at local site)

5. Dimensional Drawing

5-2. Indoor unit

9 Slim Duct : AJ026/036RBLDEG**

Units : mm [inches]



NO	Name	Description
1	Gas pipe connection	Φ9.52(3/8)
2	Liquid pipe connection	Φ6.35 (1/4)
3	Drain pipe connection	VP-25 (OD 32, ID 25)
4	Knockout hole for Drain pump	Option kit
5	Conduit for power supply & Communication wiring	-
6	Air outlet duct flange	-

NOTE


- As for drain pipe, please use VP25 (PVC, O.D. 1 - 1/4 (32 mm)).
- As for suspension bolt, please use M10 or W3/8. (Produced at local site)

5. Dimensional Drawing

5-2. Indoor unit

10 MSP Duct : AJ052RBMDEG**

Units : mm [inches]




NO	Name	Description
1	Liquid pipe connection	Φ6.35 (1/4)
2	Gas pipe connection	Φ12.70(1/2)
3	Drain pipe connection	VP-25 (OD 32, ID 25)
4	Knockout hole for Drain pump	Option kit
5	Control unit	-
6	Conduit for power supply & Communication wiring	-
7	Return air side	-
8	Air outlet duct flange	-

6. Center of Gravity

6-1. Outdoor unit

1 AJ040/050/052*CJ*EG**


Unit : mm



Model	A	B	C
AJ040/050NCJ2EG**	232	223	165
AJ052RCJ3EG**	219	289	150

2 AJ068RCJ3EG**

Unit : mm




Model	A	B	C
AJ068RCJ3EG/EU	159	327	153

6. Center of Gravity

6-2. Indoor unit

1 A3050 Good1, Wind-Free


Unit : mm



Model	A	B	C
A3050 Good1 : AR07/09/12MXWSAWKN**	399	105	128
A3050 Good1 : AR07/09/12NXWSAURN**	370	105	130
Wind-Free : AR07/09/12NXWXCWKN**	380	105	140
Wind-Free : AR07/09/12NXPXBWKN** AR07/09/12NXWXBWKN** AR07/09/12NXCXAWKN**	370	105	130

2 Maldives : AR07/09/12NXFPEWQN**

Unit : mm




Model	A	B	C
2.0/2.5/3.5kW	380	100	155

6. Center of Gravity

6-2. Indoor unit

3 New Boracay : AR07/09/12NXFHBWKN**


Unit : mm



Model	A	B	C
2.0/2.5/3.5kW	375	105	155

4 Wind-Free 1Way Cassette : AJ026/035RB1DEG**

Unit : mm




Model	A	B	C	D	E
AJ026/035RB1DEG**	1,198	500	108	555	200

6. Center of Gravity

6-2. Indoor unit

5 Wind-Free 4Way Cassette (600x600) : AJ016/020/026/035/052RBNDEG**


Unit : mm



Model	A	B	C	D	E
AJ016/020/026/035/052RBNDEG**	620 [24-3/8]	266 [10-7/16]	295 [11-5/8]	320 [12-5/16]	145 [5-11/16]

6 Duct : AJ026/036RBLDEG**, AJ052RBMDEG**

Unit : mm




Model	A	B	C
AJ026/036MBLDEH**	450	335	105
AJ052MBMDEH**	430	265	130

7. Electrical Wiring Diagram

7-1 Outdoor unit

1 AJ040/050NCJ2EG/EU



MAIN PCB	Printed circuit board(MAIN PCB)
HUB PCB	Printed circuit board(HUB PCB)
DRED	Printed circuit board(DRED PCB)
RAC DETECT	Printed circuit board(RAC DETECT PCB)
HEATER	Printed circuit board(HEATER PCB)
SMPS	Printed circuit board(SMPS PCB)
EEPROM PCB	Printed circuit board(EEPROM PCB)
EMI FILTER	Printed circuit board(EMI FILTER PCB)
NOISE ABSORBER	Printed circuit board(NOISE ABSORBER PCB)
DIS-TH	Thermistor(Discharge Temp._200Kohm)
OUT-TH	Thermistor(AmbientTemp._10Kohm)
OLP-TH	Thermistor(Compressor Top Temp._200Kohm)
COND-TH	Thermistor(Cond Out Temp._10Kohm)
BLDC	Motor(BLDC FAN Motor)
EEV-A	Electronic expansion valve A
EEV-B	Electronic expansion valve B
COMP	Motor(COMPRESSOR)
4-WAY	4WAY VALVE
PIPE IN_TH1	Thermistor(EVA IN Temp._10Kohm)
PIPE IN_TH2	Thermistor(EVA IN Temp._10Kohm)
PIPE OUT_TH1	Thermistor(EVA OUT Temp._10Kohm)
PIPE OUT_TH2	Thermistor(EVA OUT Temp._10Kohm)


NOTE

- This wiring diagram applies only to the outdoor unit.
- Colors BLK : black, BRN : brown, SKY-BLU : sky-blue, GRN/YEL : green/yellow, RED : red, YEL : yellow, ORG : orange, BLU : blue, WHT: white
- For connection wiring indoor-outdoor transmission, refer to the installation manual
-  Protective earth(screw)

7. Electrical Wiring Diagram

7-1 Outdoor unit

2 AJ052/068RCJ3EG/EU



MAIN PCB	Printed circuit board(MAIN PCB)	EEV-B	Electronic expansion valve B
HUB PCB	Printed circuit board(HUB PCB)	EEV-D	Electronic expansion valve C
DRED	Printed circuit board(DRED PCB)	EEV-E	Electronic expansion valve D
RAC DETECT	Printed circuit board(RAC DETECT PCB)	COMP	Motor(COMPRESSOR)
EEPROM PCB	Printed circuit board(EEPROM PCB)	4- WAY	4WAY VALVE
EMI FILTER	Printed circuit board(EMI FILTER PCB)	PIPE IN_TH1	Thermistor(EVA IN Temp._10Kohm)
NOISE ABSORBER	Printed circuit board(NOISE ABSORBER PCB)	PIPE IN_TH2	Thermistor(EVA IN Temp._10Kohm)
DIS-TH	Thermistor(Discharge Temp._200Kohm)	PIPE IN_TH3	Thermistor(EVA IN Temp._10Kohm)
OUT-TH	Thermistor(AmbientTemp._10Kohm)	PIPE IN_TH4	Thermistor(EVA IN Temp._10Kohm)
OLP-TH	Thermistor(Compressor Top Temp._200Kohm)	PIPE OUT_TH1	Thermistor(EVA OUT Temp._10Kohm)
COND-TH	Thermistor(Cond Out Temp._10Kohm)	PIPE OUT_TH2	Thermistor(EVA OUT Temp._10Kohm)
BLDC	Motor(BLDC FAN Motor)	PIPE OUT_TH3	Thermistor(EVA OUT Temp._10Kohm)
EEV-A	Electronic expansion valve A	PIPE OUT_TH4	Thermistor(EVA OUT Temp._10Kohm)


NOTE

- This wiring diagram applies only to the outdoor unit.
- Colors BLK : black, BRN : brown, SKY-BLU : sky-blue, GRN/YEL : green/yellow, RED : red, YEL : yellow, ORG : orange, BLU : blue, WHT: white
- For connection wiring indoor-outdoor transmission, refer to the installation manual
- Protective earth(screw)

7. Electrical Wiring Diagram

7-2 Indoor unit

2 Maldives, New Boracay



SPI	LOAD(SPI)	GRILLE STEP MOTOR	Motor(STEP MOTOR)
ROOM TH	Thermistor(Room Temp_10Kohm)	LEFT/RIGHT STEP MOTOR	Motor(STEP MOTOR)
INDOOR MID PIPE-TH	Thermistor(EVA MID Temp_10Kohm)	UP/DOWN STEP MOTOR	Motor(STEP MOTOR)
INDOOR IN PIPE-TH	Thermistor(EVA IN Temp_10Kohm)	THERMAL FUSE	Terminal Block Thermal Fuse
RECEIVER	Printed circuit board(RECEIVER BOARD)	WIFI MODULE	LOAD(WIFI MODULE)
DISPLAY	Printed circuit board(DISPLAY BOARD)	SMPS MODULE	Printed circuit board(Power Supply)
BLDC	Motor(BLDC FAN MOTOR)	HUMIDITY SENSOR	SENSOR(HUMIDITY)
HALL IC	Motor(AC FAN MOTOR)		


NOTE

- This wiring diagram applies only to the outdoor unit.
- Colors BLK : black, BRN : brown, SKY-BLU : sky-blue, GRN/YEL : green/yellow, RED : red, YEL : yellow, ORG : orange, BLU : blue, WHT: white
- For connection wiring indoor-outdoor transmission 3(C), refer to the installation manual
- ⚡ Protective earth(screw)

7. Electrical Wiring Diagram

7-2 Indoor unit

3 Wind-Free 1Way Cassette



Louver L/R	STEP MOTOR(LEFT, RIGHT)	FAN MOTOR	AC FAN MOTOR	DISPLAY	Printed Circuit Board(DISPLAY BOARD)
Louver U/D	STEP MOTOR(UP, DOWN)	FLOAT SWITCH	FLOAT SWITCH	ROOM SENSOR	Thermistor(ROOM TEMP_10Kohm)
SLIDE 1	SLIDE 1	DRAIN PUMP	LOAD(DRAIN PUMP)	EVA-IN SENSOR	Thermistor(EVA IN_10Kohm)
SLIDE 2	SLIDE 2	SPI	LOAD(SPI)	EVA-OUT SENSOR	Thermistor(EVA OUT_10Kohm)
SLIDE 3	SLIDE 3	VENTILATOR	LOAD(VENTILATOR)	HUMIDITY SENSOR	SENSOR(HUMIDITY/ROOM)
EEV	Electronic Expansion Valve	CLEAN PANEL	Load(PANEL)	THERMAL FUSE	Terminal Block Thermal Fuse


NOTE

- This wiring diagram applies only to the indoor unit.
- Colors BLK : black, BRN : brown, SKY-BLU : sky-blue, GRN/YEL : green/yellow, RED : red, YEL : yellow, ORG : orange, BLU : blue, WHT:white
- For connection wiring indoor-outdoor transmission F1-F2, indoor-wired remotecontroller transmission F3-F4, refer to the installation manual
- Protective earth(screw)

7. Electrical Wiring Diagram

7-2 Indoor unit

4 Wind-Free 4Way Cassette (600x600)



Louver1	Louver1	FAN MOTOR	BLDC FAN MOTOR	DISPLAY	Printed Circuit Board(DISPLAY BOARD)
Louver2	Louver 2	FLOAT SWITCH	FLOAT SWITCH	ROOM SENSOR	Thermistor(ROOM TEMP_10kohm)
Louver3	Louver 3	DRAIN PUMP	LOAD(DRAIN PUMP)	EVA-IN SENSOR	Thermistor(EVA IN_10kohm)
Louver4	Louver 4	SPI	LOAD(SPI)	EVA-OUT SENSOR	Thermistor(EVA OUT_10kohm)
Louver5	Louver 5	VENTILATOR	LOAD(VENTILATOR)	HUMIDITY SENSOR	SENSOR(HUMIDITY/ROOM)
EEV	Electronic Expansion Valve	CLEAN PANEL	LOAD(CLEAN PANEL)	THERMAL FUSE	Terminal Block Thermal Fuse
AUTO GRILL	LOAD(AUTO GRILL)	HUMAN SENSOR	LOAD(HUMAN SENSOR)		


NOTE

- This wiring diagram applies only to the indoor unit.
- Colors BLK : black, BRN : brown, SKY-BLU : sky-blue, GRN/YEL : green/yellow, RED : red, YEL : yellow, ORG : orange, BLU : blue, WHT:white
- For connection wiring indoor-outdoor transmission F1-F2, indoor-wired remotecontroller transmission F3-F4, refer to the installation manual
- Protective earth(screw)

7. Electrical Wiring Diagram

7-2 Indoor unit

5 Slim Duct



TRANS	Transformer	INDOOR PIPE IN-TH	Thermistor(EVA IN Temp._10Kohm)	VENTILATOR	LOAD(VENTILATOR)
EXTANAL CONTROL SIGNAL	Relay	INDOOR PIPE OUT-TH	Thermistor(EVA OUT Temp._10Kohm)	HEATER DISCH	Thermistor(HEATER DISCH)
EEV	Electronic expansion valve	FLOAT S/W	FLOAT Switch	DRAIN PUMP	LOAD(DRAIN PUMP)
ROOM TH	Thermistor(Room Temp._10Kohm)	DISPLAY	Printed circuit board(DISPLAY BOARD)	FAN MOTOR	Motor(FAN Motor)


NOTE

- This wiring diagram applies only to the indoor unit.
- Colors BLK : black, BRN : brown, SKY-BLU : sky-blue, GRN/YEL : green/yellow, RED : red, YEL : yellow, ORG : orange, BLU : blue, WHT:white
- For connection wiring indoor-outdoor transmission F1-F2, indoor-wired remotecontroller transmission F3-F4, refer to the installation manual
- Protective earth(screw)

7. Electrical Wiring Diagram

7-2 Indoor unit

6 MSP Duct



TRANS	Transformer	INDOOR PIPE IN-TH	Thermistor(EVA IN Temp_10Kohm)	VENTILATOR	LOAD(VENTILATOR)
EXTANAL CONTROL SIGNAL	Relay	INDOOR PIPE OUT-TH	Thermistor(EVA OUT Temp_10Kohm)	DRAIN PUMP	LOAD(DRAIN PUMP)
DISPLAY	Printed circuit board(DISPLAY BOARD)	FLOATS/W	FLOAT Switch	FAN MOTOR	Motor(FAN Motor)
ROOMTH	Thermistor(Room Temp_10Kohm)				

NOTE

- This wiring diagram applies only to the indoor unit.
- Colors BLK : black, BRN : brown, SKY-BLU : sky-blue, GRN/YEL : green/yellow, RED : red, YEL : yellow, ORG : orange, BLU : blue, WHT:white
- For connection wiring indoor-outdoor transmission F1-F2, indoor-wired remotecontroller transmission F3-F4, refer to the installation manual
-  Protective earth(screw)

8. Sound Data

Summary


	Capacity (Cooling, kW)	Model	Sound Pressure dB(A)	Sound Power dB(A)
Outdoor	4.0	AJ040NCJ2EG**	45	60
	5.0	AJ050NCJ2EG**	46	61
	5.2	AJ052RCJ3EG**	46	61
	6.8	AJ068RCJ3EG**	48	64
Indoor	Capacity (Cooling, kW)	Model	Sound Pressure dB(A)	Sound Power dB(A)
A3050 Good1	2.0	AR07*XWSA**N**	37/27/22	54
	2.5	AR09*XWSA**N**	37/27/22	54
	3.5	AR12*XWSA**N**	38/28/22	56
Maldives	2.0	AR07NXFPEWQN**	38/28/21	56
	2.5	AR09NXFPEWQN**	38/28/21	56
	3.5	AR12NXFPEWQN**	42/33/23	59
New Boracay	2.0	AR07NXFHBWKN**	38/30/21	56
	2.5	AR09NXFHBWKN**	38/30/21	56
	3.5	AR12NXFHBWKN**	42/33/21	59
Wind-Free RAC	2.0	AR07NX*X*WKN**	37/30/22	56
	2.5	AR09NX*X*WKN**	37/30/22	56
	3.5	AR12NX*X*WKN**	38/31/22	58
Wind-Free 1Way CASSETTE	2.6	AJ026RB1DEG**	32/29/26	50
	3.5	AJ035RB1DEG**	37/33/30	55
Wind-Free 4Way CASSETTE (600x600)	1.6	AJ016RBNDEG**	33/29/24	49
	2.0	AJ020RBNDEG**	33/29/24	49
	2.6	AJ026RBNDEG**	33/29/24	49
	3.5	AJ035RBNDEG**	35/31/27	53
	5.2	AJ052RBNDEG**	39/36/32	55
Slim duct	2.6	AJ026RBLDEG**	30/28/25	53
	3.5	AJ035RBLDEG**	32/30/27	53
MSP duct	5.2	AJ052RBMDEG**	42/41/39	59

8. Sound Data

Sound Pressure level

8-1. Outdoor unit


Unit: dB(A)




Model	dBA
AJ040NCJ2EG**	45
AJ050NCJ2EG**	46
AJ052RCJ3EG**	46
AJ068RCJ3EG**	48

• NR Curve


1) AJ040NCJ2EG**




2) AJ050NCJ2EG**



3) AJ052RCJ3EG**



4) AJ068RCJ3EG**



NOTE

- Specifications may be subject to change without prior notice
 - Sound pressure level is obtained in an anechoic room.
 - Sound pressure level is a relative value, depending on the distance and acoustic environment.
 - Sound pressure level may differ depending on operation condition.
 - dBA = A-weighted sound pressure level
 - Reference acoustic pressure 0 dB = 20μPa


8. Sound Data

Sound Pressure level

8-2. Indoor unit

1 Wall Mounted Type : A3050 Good1


Unit: dB(A)




Model	High	Mid	Low
AR07*XWSA**N**	37	27	22
AR09*XWSA**N**	37	27	22
AR12*XWSA**N**	38	28	22

• NR Curve


1) AR07*XWSA**N**



2) AR09*XWSA**N**



3) AR12*XWSA**N**



NOTE

- Specifications may be subject to change without prior notice
 - Sound pressure level is obtained in an anechoic room.
 - Sound pressure level is a relative value, depending on the distance and acoustic environment.
 - Sound pressure level may differ depending on operation condition.
 - dBA = A-weighted sound pressure level
 - Reference acoustic pressure 0 dB = 20μPa


8. Sound Data

Sound Pressure level

8-2. Indoor unit

2 Wall Mounted Type : Maldives


Unit: dB(A)




Model	High	Mid	Low
AR07NXFPEWQN**	38	28	21
AR09NXFPEWQN**	38	28	21
AR12NXFPEWQN**	42	33	23

• NR Curve


1) AR07NXFPEWQN**



2) AR09NXFPEWQN**



3) AR12NXFPEWQN**



NOTE

- Specifications may be subject to change without prior notice
 - Sound pressure level is obtained in an anechoic room.
 - Sound pressure level is a relative value, depending on the distance and acoustic environment.
 - Sound pressure level may differ depending on operation condition.
 - dBA = A-weighted sound pressure level
 - Reference acoustic pressure 0 dB = 20μPa


8. Sound Data

Sound Pressure level

8-2. Indoor unit

3 Wall Mounted Type : New Boracay


Unit: dB(A)




Model	High	Mid	Low
AR07NXFHBWKN**	38	30	21
AR09NXFHBWKN**	38	30	21
AR12NXFHBWKN**	42	33	21

• NR Curve


1) AR07NXFHBWKN**



2) AR09NXFHBWKN**



3) AR12NXFHBWKN**



NOTE

- Specifications may be subject to change without prior notice
 - Sound pressure level is obtained in an anechoic room.
 - Sound pressure level is a relative value, depending on the distance and acoustic environment.
 - Sound pressure level may differ depending on operation condition.
 - dBA = A-weighted sound pressure level
 - Reference acoustic pressure 0 dB = 20μPa


8. Sound Data

Sound Pressure level

8-2. Indoor unit

4 Wall Mounted Type : Wind-Free (A3050)


Unit: dB(A)




Model	High	Mid	Low
AR07NX*X*WKN**	37	30	22
AR09NX*X*WKN**	37	30	22
AR12NX*X*WKN**	38	31	22

• NR Curve


1) AR07NX*X*WKN**



2) AR09NX*X*WKN**



3) AR12NX*X*WKN**



NOTE

- Specifications may be subject to change without prior notice
 - Sound pressure level is obtained in an anechoic room.
 - Sound pressure level is a relative value, depending on the distance and acoustic environment.
 - Sound pressure level may differ depending on operation condition.
 - dBA = A-weighted sound pressure level
 - Reference acoustic pressure 0 dB = 20μPa


8. Sound Data

Sound Pressure level

8-2. Indoor unit

5 Wind-Free 1Way Cassette


Unit: dB(A)




Model	High	Mid	Low
AJ026RB1DEG**	32	29	26
AJ035RB1DEG**	37	33	30

- NR Curve

1) AJ026RB1DEG**



2) AJ035RB1DEG**



NOTE

- Specifications may be subject to change without prior notice.
- Sound pressure level is obtained in an anechoic room.
- Sound pressure level is a relative value, depending on the distance and acoustic environment.
- Sound pressure level may differ depending on operation condition.
- dBA = A weighted sound pressure level
- Reference acoustic pressure 0 dB = 20μPa


8. Sound Data

Sound Pressure level

8-2. Indoor unit

6 Wind-Free 4Way Cassette (600x600)


Unit: dB(A)




Model	High	Mid	Low
AJ016RBNDEG**	33	29	24
AJ020RBNDEG**	33	29	24
AJ026RBNDEG**	33	29	24
AJ035RBNDEG**	35	31	27
AJ052RBNDEG**	39	36	32

• NR Curve


1) AJ016RBNDEG**




2) AJ020RBNDEG**




3) AJ026RBNDEG**



4) AJ035RBNDEG**



5) AJ052RBNDEG**




8. Sound Data

Sound Pressure level

8-2. Indoor unit

7 Slim Duct, MSP Duct


Unit: dB(A)




Model	High	Mid	Low
AJ026RBLDEG**	30	28	25
AJ035RBLDEG**	32	30	27
AJ052RBMDEG**	42	41	39

- NR Curve


1) AJ026RBLDEG**



2) AJ035RBLDEG**



3) AJ052RBMDEG**



NOTE

- Specifications may be subject to change without prior notice.
 - Sound pressure level is obtained in an anechoic room.
 - Sound pressure level is a relative value, depending on the distance and acoustic environment.
 - Sound pressure level may differ depending on operation condition.
 - dB(A) = A weighted sound pressure level
 - Reference acoustic pressure 0 dB = 20μPa

8. Sound Data

Sound Power level

8-3. Outdoor unit


Unit: dB(A)

NOTE


- Specifications may be subject to change without prior notice
 - Sound power level is an absolute value that a sound source generates.
 - dB(A) = A-weighted sound power level.
 - Reference power : 1pW.
 - Measured according to ISO 3741.

Model	Power
AJ040NCJ2EG**	60
AJ050NCJ2EG**	61
AJ052RCJ3EG**	61
AJ068RCJ3EG**	64


1) AJ040NCJ2EG**




2) AJ050NCJ2EG**



3) AJ052RCJ3EG**



4) AJ068RCJ3EG**



8. Sound Data

Sound Power level

8-4. Indoor unit

1 Wall Mounted Type : A3050 Good1


Unit: dB(A)

NOTE


- Specifications may be subject to change without prior notice
- Sound power level is an absolute value that a sound source generates.
- dB(A) = A-weighted sound power level.
- Reference power : 1pW.
- Measured according to ISO 3741.

Model	Power
AR07*XWSA**N**	54
AR09*XWSA**N**	54
AR12*XWSA**N**	56


1) AR07*XWSA**N**



2) AR09*XWSA**N**



3) AR12*XWSA**N**



8. Sound Data

Sound Power level

8-4. Indoor unit

2 Wall Mounted Type : Maldives


Unit: dB(A)

NOTE


- Specifications may be subject to change without prior notice
 - Sound power level is an absolute value that a sound source generates.
 - dB(A) = A-weighted sound power level.
 - Reference power : 1pW.
 - Measured according to ISO 3741.

Model	Power
AR07NXFPEWQN**	56
AR09NXFPEWQN**	56
AR12NXFPEWQN**	59


1) AR07NXFPEWQN**



2) AR09NXFPEWQN**



3) AR12NXFPEWQN**



8. Sound Data

Sound Power level

8-4. Indoor unit

3 Wall Mounted Type : New Boracay


Unit: dB(A)

NOTE


- Specifications may be subject to change without prior notice
 - Sound power level is an absolute value that a sound source generates.
 - dB(A) = A-weighted sound power level.
 - Reference power : 1pW.
 - Measured according to ISO 3741.

Model	Power
AR07NXFHBWKN**	56
AR09NXFHBWKN**	56
AR12NXFHBWKN**	59


1) AR07NXFHBWKN**



2) AR09NXFHBWKN**



3) AR12NXFHBWKN**



8. Sound Data

Sound Power level

8-4. Indoor unit

4 Wall Mounted Type : Wind-Free


Unit: dB(A)

NOTE


- Specifications may be subject to change without prior notice
 - Sound power level is an absolute value that a sound source generates.
 - dB(A) = A-weighted sound power level.
 - Reference power : 1pW.
 - Measured according to ISO 3741.

Model	Power
AR07NX*X*WKN**	56
AR09NX*X*WKN**	56
AR12NX*X*WKN**	58


1) AR07NX*X*WKN**



2) AR09NX*X*WKN**



3) AR12NX*X*WKN**



8. Sound Data

Sound Power level

8-4. Indoor unit

5 Wind-Free 1Way Cassette


Unit: dB(A)

NOTE


- Specifications may be subject to change without prior notice
 - Sound power level is an absolute value that a sound source generates.
 - dB(A) = A-weighted sound power level.
 - Reference power : 1pW.
 - Measured according to ISO 3741.

Model	Power
AJ026RB1DEG**	50
AJ035RB1DEG**	55

1) AJ026RB1DEG**



2) AJ035RB1DEG**



8. Sound Data

Sound Power level

8-4. Indoor unit

6 Wind-Free 4Way Cassette (600x600)


Unit: dB(A)

NOTE


- Specifications may be subject to change without prior notice
 - Sound power level is an absolute value that a sound source generates.
 - dB(A) = A-weighted sound power level.
 - Reference power : 1pW.
 - Measured according to ISO 3741.

Model	Power
AJ016RBNDEG**	49
AJ020RBNDEG**	49
AJ026RBNDEG**	49
AJ035RBNDEG**	53
AJ052RBNDEG**	55


1) AJ016RBNDEG**




2) AJ020RBNDEG**




3) AJ026RBNDEG**



4) AJ035RBNDEG**



5) AJ052RBNDEG**



8. Sound Data

Sound Power level

8-4. Indoor unit

7 Slim Duct, MSP Duct


NOTE

- Specifications may be subject to change without prior notice
 - Sound power level is an absolute value that a sound source generates.
 - dBA = A-weighted sound power level.
 - Reference power : 1pW.
 - Measured according to ISO 3741.


Unit: dB(A)

Model	Power
AJ026RBLDEG**	53
AJ035RBLDEG**	53
AJ052RBMDEG**	59


1) AJ026RBLDEG**



2) AJ035RBLDEG**




3) AJ052RBMDEG**




9. Fan Characteristics (PQ curve)

9-1 Slim Duct - AJ026RBLDEG**


1	External Static Pressure[mmAq]	Option Code
	$0 \leq SP \leq 1.0$	015201-1400Fb-200000-300000



2	External Static Pressure[mmAq]	Option Code
	$1.0 < SP \leq 3.0$ (Default)	015201-14020C-200000-300000




3	External Static Pressure[mmAq]	Option Code
	$3.0 < SP \leq 4.0$	015201-1403A2-200000-300000




9-2 Slim Duct - AJ035RBLDEG**


1	External Static Pressure[mmAq]	Option Code
	$0 \leq SP \leq 1.0$	015201-16025d-200000-300000



2	External Static Pressure[mmAq]	Option Code
	$1 < SP \leq 3.0$ (Default)	015201-16026E-200000-300000




3	External Static Pressure[mmAq]	Option Code
	$3 < SP \leq 4.0$	015203-160108-200000-300000




9. Fan Characteristics (PQ curve)

9-3. MSP Duct - AJ052RBMDEG**


1	External Static Pressure[mmAq]	Option Code
	$0 \leq SP \leq 3.0$	012221-194360-200000-300000



2	External Static Pressure[mmAq]	Option Code
	$3.0 < SP \leq 5.0$ (Default)	012221-1943A2-200000-300000





3	External Static Pressure[mmAq]	Option Code
	$5.0 < SP \leq 6.0$	012223-194105-200000-300000



10. Operation Range

AJ040NCJ2EG**, AJ050NCJ2EG**



The graphs are based on the following conditions.



1. Equivalent piping length

AJ040/050NCJ2EG** : 5m

2. Level difference 0m

3. Air flow rate High

AJ052RCJ3EG**, AJ068RCJ3EG**



The graphs are based on the following conditions.

1. Equivalent piping length

AJ052/068RCJ3EG** : 5m


2. Level difference 0m

3. Air flow rate High


11. Piping Diagram

AJ040NCJ2EG**, AJ050NCJ2EG**

Cooling System




Heating System




11. Piping Diagram

AJ052RCJ3EG**

Cooling System




Heating System




11. Piping Diagram

AJ068RCJ3EG**

Cooling System



Heating System



12. Capacity Table

11-1. AJ040NCJ2EG/EU

Cooling

Combination (Capacity Index)				Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, WB)													
							14		16		18		19		20		22		24	
							TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
2000			2000	50%	10	1.68	0.31	2.43	0.35	2.54	0.38	2.59	0.39	2.64	0.40	2.74	0.42	2.85	0.44	
					12	1.68	0.33	2.39	0.36	2.50	0.39	2.55	0.40	2.60	0.41	2.70	0.43	2.81	0.45	
					14	1.68	0.34	2.36	0.37	2.46	0.40	2.51	0.41	2.56	0.42	2.66	0.44	2.76	0.45	
					16	1.68	0.36	2.32	0.39	2.42	0.41	2.47	0.43	2.52	0.44	2.62	0.45	2.72	0.46	
					18	1.68	0.37	2.28	0.40	2.38	0.43	2.43	0.44	2.48	0.45	2.58	0.46	2.68	0.47	
					20	1.68	0.39	2.24	0.41	2.34	0.44	2.39	0.45	2.44	0.46	2.54	0.47	2.64	0.48	
					21	1.68	0.39	2.22	0.42	2.32	0.45	2.37	0.46	2.42	0.46	2.52	0.48	2.62	0.49	
					23	1.68	0.41	2.18	0.44	2.28	0.46	2.33	0.47	2.38	0.48	2.48	0.49	2.58	0.50	
					25	1.68	0.42	2.15	0.45	2.24	0.47	2.29	0.48	2.34	0.49	2.44	0.50	2.54	0.51	
					27	1.68	0.44	2.11	0.47	2.20	0.49	2.25	0.49	2.30	0.50	2.40	0.51	2.50	0.52	
					29	1.68	0.46	2.07	0.48	2.17	0.50	2.21	0.51	2.26	0.51	2.36	0.52	2.46	0.53	
					31	1.68	0.47	2.03	0.50	2.13	0.51	2.18	0.52	2.22	0.53	2.32	0.53	2.42	0.54	
					33	1.68	0.49	1.99	0.51	2.09	0.53	2.14	0.53	2.19	0.54	2.28	0.55	2.38	0.55	
					35	1.68	0.51	1.96	0.53	2.05	0.54	2.10	0.54	2.15	0.55	2.24	0.56	2.34	0.56	
					37	1.68	0.52	1.92	0.54	2.01	0.56	2.06	0.56	2.11	0.57	2.20	0.57	2.30	0.57	
					39	1.68	0.54	1.88	0.56	1.98	0.57	2.02	0.58	2.07	0.58	2.16	0.58	2.26	0.58	
					42	1.66	0.57	1.83	0.58	1.92	0.59	1.97	0.60	2.01	0.60	2.11	0.60	2.20	0.60	
					44	1.58	0.58	1.79	0.60	1.88	0.61	1.93	0.61	1.97	0.61	2.07	0.61	2.16	0.61	
					46	1.53	0.60	1.75	0.62	1.84	0.62	1.89	0.63	1.94	0.63	2.03	0.63	2.12	0.62	
2500			2500	63%	10	2.00	0.43	2.90	0.48	3.02	0.52	3.08	0.54	3.14	0.56	3.26	0.59	3.39	0.61	
					12	2.00	0.45	2.85	0.50	2.97	0.54	3.03	0.56	3.09	0.57	3.22	0.60	3.34	0.62	
					14	2.00	0.47	2.80	0.52	2.93	0.56	2.99	0.57	3.05	0.59	3.17	0.61	3.29	0.63	
					16	2.00	0.49	2.76	0.54	2.88	0.57	2.94	0.59	3.00	0.60	3.12	0.63	3.24	0.64	
					18	2.00	0.51	2.71	0.56	2.83	0.59	2.89	0.61	2.95	0.62	3.07	0.64	3.19	0.66	
					20	2.00	0.54	2.67	0.58	2.79	0.61	2.85	0.62	2.90	0.64	3.02	0.66	3.14	0.67	
					21	2.00	0.55	2.64	0.59	2.76	0.62	2.82	0.63	2.88	0.64	3.00	0.66	3.12	0.67	
					23	2.00	0.57	2.60	0.61	2.72	0.64	2.78	0.65	2.83	0.66	2.95	0.68	3.07	0.69	
					25	2.00	0.59	2.55	0.63	2.67	0.66	2.73	0.67	2.79	0.68	2.91	0.69	3.02	0.70	
					27	2.00	0.61	2.51	0.65	2.62	0.67	2.68	0.69	2.74	0.69	2.86	0.71	2.98	0.72	
					29	2.00	0.63	2.46	0.67	2.58	0.69	2.64	0.70	2.69	0.71	2.81	0.72	2.93	0.73	
					31	2.00	0.66	2.42	0.69	2.53	0.71	2.59	0.72	2.65	0.73	2.76	0.74	2.88	0.74	
					33	2.00	0.68	2.37	0.71	2.49	0.73	2.54	0.74	2.60	0.75	2.72	0.76	2.83	0.76	
					35	2.00	0.70	2.33	0.73	2.44	0.75	2.50	0.75	2.56	0.77	2.67	0.77	2.78	0.77	
					37	2.00	0.73	2.29	0.75	2.40	0.77	2.45	0.78	2.51	0.79	2.62	0.79	2.74	0.79	
					39	2.00	0.75	2.24	0.77	2.35	0.79	2.41	0.80	2.46	0.80	2.58	0.81	2.69	0.81	
					42	1.98	0.79	2.18	0.81	2.29	0.82	2.34	0.83	2.40	0.83	2.51	0.83	2.62	0.83	
					44	1.88	0.81	2.13	0.83	2.24	0.85	2.30	0.85	2.35	0.85	2.46	0.85	2.57	0.85	
					46	1.83	0.83	2.09	0.85	2.20	0.87	2.25	0.87	2.30	0.87	2.41	0.87	2.53	0.86	

12. Capacity Table

Combination (Capacity Index)				Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, WB)													
							14		16		18		19		20		22		24	
							TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
3500				3500	88%	10	2.80	0.61	4.06	0.68	4.23	0.74	4.31	0.77	4.40	0.79	4.57	0.83	4.74	0.86
						12	2.80	0.64	3.99	0.71	4.16	0.76	4.25	0.79	4.33	0.81	4.50	0.85	4.68	0.87
						14	2.80	0.67	3.93	0.73	4.10	0.79	4.18	0.81	4.26	0.83	4.44	0.87	4.61	0.89
						16	2.80	0.70	3.86	0.76	4.03	0.81	4.11	0.83	4.20	0.85	4.37	0.89	4.54	0.91
						18	2.80	0.73	3.80	0.79	3.96	0.84	4.05	0.86	4.13	0.88	4.30	0.91	4.47	0.93
						20	2.80	0.76	3.73	0.81	3.90	0.86	3.98	0.88	4.07	0.90	4.23	0.93	4.40	0.94
						21	2.80	0.77	3.70	0.83	3.87	0.87	3.95	0.89	4.03	0.91	4.20	0.94	4.37	0.95
						23	2.80	0.80	3.64	0.86	3.80	0.90	3.89	0.92	3.97	0.93	4.13	0.96	4.30	0.97
						25	2.80	0.83	3.58	0.88	3.74	0.93	3.82	0.94	3.90	0.96	4.07	0.98	4.23	0.99
						27	2.80	0.86	3.51	0.91	3.67	0.95	3.76	0.97	3.84	0.98	4.00	1.00	4.17	1.01
						29	2.80	0.89	3.45	0.94	3.61	0.98	3.69	0.99	3.77	1.01	3.93	1.02	4.10	1.03
						31	2.80	0.93	3.39	0.97	3.55	1.01	3.63	1.02	3.71	1.03	3.87	1.05	4.03	1.05
						33	2.80	0.96	3.32	1.00	3.48	1.03	3.56	1.05	3.64	1.06	3.80	1.07	3.97	1.07
						35	2.80	0.99	3.26	1.03	3.42	1.06	3.50	1.06	3.58	1.08	3.74	1.09	3.90	1.09
						37	2.80	1.03	3.20	1.06	3.36	1.09	3.43	1.10	3.51	1.11	3.67	1.12	3.83	1.12
						39	2.80	1.06	3.14	1.09	3.29	1.12	3.37	1.13	3.45	1.14	3.61	1.14	3.77	1.14
						42	2.77	1.11	3.05	1.14	3.20	1.17	3.28	1.17	3.35	1.18	3.51	1.18	3.67	1.17
						44	2.63	1.14	2.98	1.18	3.14	1.20	3.21	1.20	3.29	1.21	3.45	1.21	3.60	1.20
						46	2.56	1.18	2.92	1.21	3.07	1.23	3.15	1.23	3.23	1.23	3.38	1.23	3.54	1.22
2000	2000			4000	100%	10	3.53	0.63	4.99	0.65	5.08	0.66	5.14	0.67	5.20	0.68	5.35	0.69	5.52	0.71
						12	3.53	0.65	4.85	0.66	4.95	0.68	5.01	0.69	5.08	0.69	5.23	0.71	5.41	0.72
						14	3.53	0.66	4.72	0.68	4.83	0.70	4.89	0.70	4.96	0.71	5.12	0.72	5.31	0.74
						16	3.53	0.68	4.60	0.70	4.71	0.71	4.78	0.72	4.85	0.73	5.02	0.74	5.21	0.76
						18	3.53	0.70	4.48	0.71	4.60	0.73	4.67	0.74	4.75	0.74	4.92	0.76	5.12	0.77
						20	3.53	0.72	4.36	0.73	4.49	0.75	4.57	0.75	4.65	0.76	4.83	0.78	5.03	0.79
						21	3.53	0.73	4.31	0.74	4.44	0.76	4.52	0.76	4.60	0.77	4.78	0.78	4.99	0.80
						23	3.53	0.74	4.20	0.76	4.34	0.77	4.42	0.78	4.51	0.79	4.70	0.80	4.91	0.82
						25	3.53	0.76	4.10	0.78	4.25	0.79	4.33	0.80	4.42	0.81	4.62	0.82	4.84	0.84
						27	3.53	0.78	4.01	0.80	4.16	0.81	4.25	0.82	4.34	0.83	4.55	0.84	4.78	0.85
						29	3.53	0.80	3.92	0.82	4.08	0.83	4.17	0.84	4.27	0.85	4.48	0.86	4.72	0.87
						31	3.53	0.82	3.84	0.84	4.01	0.85	4.10	0.86	4.20	0.87	4.42	0.88	4.66	0.89
						33	3.53	0.84	3.76	0.86	3.94	0.87	4.03	0.88	4.13	0.89	4.36	0.90	4.61	0.91
						35	3.53	0.87	3.69	0.88	3.87	0.90	4.00	0.90	4.08	0.91	4.31	0.92	4.57	0.94
						37	3.53	0.89	3.62	0.90	3.81	0.92	3.91	0.92	4.02	0.93	4.26	0.94	4.53	0.96
						39	3.53	0.91	3.56	0.92	3.76	0.94	3.86	0.95	3.98	0.95	4.22	0.97	4.49	0.98
						42	3.53	0.94	3.48	0.96	3.69	0.97	3.80	0.98	3.92	0.99	4.17	1.00	4.46	1.01
						44	3.53	0.97	3.44	0.98	3.65	1.00	3.76	1.00	3.89	1.01	4.15	1.02	4.44	1.04
						46	3.53	0.99	3.39	1.01	3.61	1.02	3.73	1.03	3.86	1.03	4.13	1.05	4.42	1.06

12. Capacity Table

Combination (Capacity Index)				Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, WB)													
							14		16		18		19		20		22		24	
							TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
2000	2500			4500	113%	10	3.53	0.65	4.99	0.66	5.08	0.68	5.14	0.69	5.20	0.69	5.35	0.71	5.52	0.72
						12	3.53	0.66	4.85	0.68	4.95	0.69	5.01	0.70	5.08	0.71	5.23	0.72	5.41	0.74
						14	3.53	0.68	4.72	0.70	4.83	0.71	4.89	0.72	4.96	0.73	5.12	0.74	5.31	0.75
						16	3.53	0.70	4.60	0.71	4.71	0.73	4.78	0.74	4.85	0.74	5.02	0.76	5.21	0.77
						18	3.53	0.71	4.48	0.73	4.60	0.75	4.67	0.75	4.75	0.76	4.92	0.78	5.12	0.79
						20	3.53	0.73	4.36	0.75	4.49	0.76	4.57	0.77	4.65	0.78	4.83	0.79	5.03	0.81
						21	3.53	0.74	4.31	0.76	4.44	0.77	4.52	0.78	4.60	0.79	4.78	0.80	4.99	0.82
						23	3.53	0.76	4.20	0.78	4.34	0.79	4.42	0.80	4.51	0.81	4.70	0.82	4.91	0.83
						25	3.53	0.78	4.10	0.80	4.25	0.81	4.33	0.82	4.42	0.83	4.62	0.84	4.84	0.85
						27	3.53	0.80	4.01	0.82	4.16	0.83	4.25	0.84	4.34	0.85	4.55	0.86	4.78	0.87
						29	3.53	0.82	3.92	0.84	4.08	0.85	4.17	0.86	4.27	0.87	4.48	0.88	4.72	0.89
						31	3.53	0.84	3.84	0.86	4.01	0.87	4.10	0.88	4.20	0.89	4.42	0.90	4.66	0.91
						33	3.53	0.86	3.76	0.88	3.94	0.89	4.03	0.90	4.13	0.91	4.36	0.92	4.61	0.94
						35	3.53	0.88	3.69	0.90	3.87	0.91	4.00	0.92	4.08	0.93	4.31	0.94	4.57	0.96
						37	3.53	0.91	3.62	0.92	3.81	0.94	3.91	0.94	4.02	0.95	4.26	0.97	4.53	0.98
						39	3.53	0.93	3.56	0.94	3.76	0.96	3.86	0.97	3.98	0.97	4.22	0.99	4.49	1.00
						42	3.53	0.96	3.48	0.98	3.69	0.99	3.80	1.00	3.92	1.01	4.17	1.02	4.46	1.04
						44	3.53	0.99	3.44	1.00	3.65	1.02	3.76	1.03	3.89	1.03	4.15	1.05	4.44	1.06
						46	3.53	1.01	3.39	1.03	3.61	1.04	3.73	1.05	3.86	1.06	4.13	1.07	4.42	1.08
2000	3500			5500	138%	10	3.53	0.65	4.99	0.67	5.08	0.69	5.14	0.69	5.20	0.70	5.35	0.72	5.52	0.73
						12	3.53	0.67	4.85	0.69	4.95	0.70	5.01	0.71	5.08	0.72	5.23	0.73	5.41	0.75
						14	3.53	0.69	4.72	0.70	4.83	0.72	4.89	0.73	4.96	0.73	5.12	0.75	5.31	0.76
						16	3.53	0.70	4.60	0.72	4.71	0.74	4.78	0.74	4.85	0.75	5.02	0.77	5.21	0.78
						18	3.53	0.72	4.48	0.74	4.60	0.75	4.67	0.76	4.75	0.77	4.92	0.78	5.12	0.80
						20	3.53	0.74	4.36	0.76	4.49	0.77	4.57	0.78	4.65	0.79	4.83	0.80	5.03	0.82
						21	3.53	0.75	4.31	0.77	4.44	0.78	4.52	0.79	4.60	0.80	4.78	0.81	4.99	0.83
						23	3.53	0.77	4.20	0.78	4.34	0.80	4.42	0.81	4.51	0.82	4.70	0.83	4.91	0.84
						25	3.53	0.79	4.10	0.80	4.25	0.82	4.33	0.83	4.42	0.83	4.62	0.85	4.84	0.86
						27	3.53	0.81	4.01	0.82	4.16	0.84	4.25	0.85	4.34	0.85	4.55	0.87	4.78	0.88
						29	3.53	0.83	3.92	0.85	4.08	0.86	4.17	0.87	4.27	0.88	4.48	0.89	4.72	0.90
						31	3.53	0.85	3.84	0.87	4.01	0.88	4.10	0.89	4.20	0.90	4.42	0.91	4.66	0.92
						33	3.53	0.87	3.76	0.89	3.94	0.90	4.03	0.91	4.13	0.92	4.36	0.93	4.61	0.95
						35	3.53	0.89	3.69	0.91	3.87	0.92	4.00	0.93	4.08	0.94	4.31	0.95	4.57	0.97
						37	3.53	0.92	3.62	0.93	3.81	0.95	3.91	0.95	4.02	0.96	4.26	0.98	4.53	0.99
						39	3.53	0.94	3.56	0.96	3.76	0.97	3.86	0.98	3.98	0.98	4.22	1.00	4.49	1.01
						42	3.53	0.98	3.48	0.99	3.69	1.01	3.80	1.01	3.92	1.02	4.17	1.03	4.46	1.05
						44	3.53	1.00	3.44	1.01	3.65	1.03	3.76	1.04	3.89	1.04	4.15	1.06	4.44	1.07
						46	3.53	1.02	3.39	1.04	3.61	1.05	3.73	1.06	3.86	1.07	4.13	1.08	4.42	1.10

12. Capacity Table

Combination (Capacity Index)				Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, WB)															
							14		16		18		19		20		22		24			
							TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)		
2500	2500		5000	125%	10	3.53	0.66	4.99	0.68	5.08	0.69	5.14	0.70	5.20	0.71	5.35	0.72	5.52	0.74			
					12	3.53	0.68	4.85	0.69	4.95	0.71	5.01	0.72	5.08	0.73	5.23	0.74	5.41	0.75			
					14	3.53	0.69	4.72	0.71	4.83	0.73	4.89	0.73	4.96	0.74	5.12	0.76	5.31	0.77			
					16	3.53	0.71	4.60	0.73	4.71	0.74	4.78	0.75	4.85	0.76	5.02	0.77	5.21	0.79			
					18	3.53	0.73	4.48	0.75	4.60	0.76	4.67	0.77	4.75	0.78	4.92	0.79	5.12	0.81			
					20	3.53	0.75	4.36	0.76	4.49	0.78	4.57	0.79	4.65	0.80	4.83	0.81	5.03	0.82			
					21	3.53	0.76	4.31	0.77	4.44	0.79	4.52	0.80	4.60	0.81	4.78	0.82	4.99	0.83			
					23	3.53	0.78	4.20	0.79	4.34	0.81	4.42	0.82	4.51	0.82	4.70	0.84	4.91	0.85			
					25	3.53	0.80	4.10	0.81	4.25	0.83	4.33	0.84	4.42	0.84	4.62	0.86	4.84	0.87			
					27	3.53	0.82	4.01	0.83	4.16	0.85	4.25	0.86	4.34	0.86	4.55	0.88	4.78	0.89			
					29	3.53	0.84	3.92	0.85	4.08	0.87	4.17	0.88	4.27	0.88	4.48	0.90	4.72	0.91			
					31	3.53	0.86	3.84	0.88	4.01	0.89	4.10	0.90	4.20	0.91	4.42	0.92	4.66	0.93			
					33	3.53	0.88	3.76	0.90	3.94	0.91	4.03	0.92	4.13	0.93	4.36	0.94	4.61	0.96			
					35	3.53	0.90	3.69	0.92	3.87	0.93	4.00	0.94	4.08	0.95	4.31	0.96	4.57	0.98			
					37	3.53	0.93	3.62	0.94	3.81	0.96	3.91	0.96	4.02	0.97	4.26	0.99	4.53	1.00			
					39	3.53	0.95	3.56	0.97	3.76	0.98	3.86	0.99	3.98	1.00	4.22	1.01	4.49	1.02			
					42	3.53	0.99	3.48	1.00	3.69	1.02	3.80	1.02	3.92	1.03	4.17	1.05	4.46	1.06			
					44	3.53	1.01	3.44	1.03	3.65	1.04	3.76	1.05	3.89	1.06	4.15	1.07	4.44	1.08			
					46	3.53	1.04	3.39	1.05	3.61	1.07	3.73	1.07	3.86	1.08	4.13	1.09	4.42	1.11			
2500	3500		6000	150%	10	3.53	0.67	4.99	0.68	5.08	0.70	5.14	0.71	5.20	0.72	5.35	0.73	5.52	0.75			
					12	3.53	0.68	4.85	0.70	4.95	0.72	5.01	0.73	5.08	0.73	5.23	0.75	5.41	0.76			
					14	3.53	0.70	4.72	0.72	4.83	0.73	4.89	0.74	4.96	0.75	5.12	0.77	5.31	0.78			
					16	3.53	0.72	4.60	0.74	4.71	0.75	4.78	0.76	4.85	0.77	5.02	0.78	5.21	0.80			
					18	3.53	0.74	4.48	0.75	4.60	0.77	4.67	0.78	4.75	0.79	4.92	0.80	5.12	0.81			
					20	3.53	0.76	4.36	0.77	4.49	0.79	4.57	0.80	4.65	0.80	4.83	0.82	5.03	0.83			
					21	3.53	0.77	4.31	0.78	4.44	0.80	4.52	0.81	4.60	0.81	4.78	0.83	4.99	0.84			
					23	3.53	0.79	4.20	0.80	4.34	0.82	4.42	0.83	4.51	0.83	4.70	0.85	4.91	0.86			
					25	3.53	0.81	4.10	0.82	4.25	0.84	4.33	0.85	4.42	0.85	4.62	0.87	4.84	0.88			
					27	3.53	0.83	4.01	0.84	4.16	0.86	4.25	0.87	4.34	0.87	4.55	0.89	4.78	0.90			
					29	3.53	0.85	3.92	0.86	4.08	0.88	4.17	0.89	4.27	0.89	4.48	0.91	4.72	0.92			
					31	3.53	0.87	3.84	0.88	4.01	0.90	4.10	0.91	4.20	0.92	4.42	0.93	4.66	0.94			
					33	3.53	0.89	3.76	0.91	3.94	0.92	4.03	0.93	4.13	0.94	4.36	0.95	4.61	0.97			
					35	3.53	0.91	3.69	0.93	3.87	0.94	4.00	0.95	4.08	0.96	4.31	0.97	4.57	0.99			
					37	3.53	0.94	3.62	0.95	3.81	0.97	3.91	0.98	4.02	0.98	4.26	1.00	4.53	1.01			
					39	3.53	0.96	3.56	0.98	3.76	0.99	3.86	1.00	3.98	1.01	4.22	1.02	4.49	1.03			
					42	3.53	1.00	3.48	1.01	3.69	1.03	3.80	1.03	3.92	1.04	4.17	1.06	4.46	1.07			
					44	3.53	1.02	3.44	1.04	3.65	1.05	3.76	1.06	3.89	1.07	4.15	1.08	4.44	1.09			
					46	3.53	1.05	3.39	1.06	3.61	1.08	3.73	1.08	3.86	1.09	4.13	1.11	4.42	1.12			

NOTE

- The performance table shows the average value of each conditions.
- The above is the value for connecting with the following indoor units.
 - 2000, 2500, 3500 class : AR07MXWSAWKNEU, AR09MXWSAWKNEU, AR12MXWSAWKNEU
- The total ability of connected a indoor unit is up to 6.0kW
- It is impossible to connect the indoor unit for one room only.
- This data is reference data for temperature capacity trend.

12. Capacity Table

11-1. AJ040NCJ2EG/EU

Heating

Combination (Capacity Index)				Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, DB)													
							14		16		18		20		21		22		24	
							TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
2000				2000	50%	-15	1.37	0.62	1.33	0.63	1.29	0.64	1.28	0.64	1.26	0.64	1.23	0.65	1.21	0.66
						-10	1.65	0.65	1.60	0.66	1.56	0.67	1.54	0.67	1.52	0.68	1.49	0.69	1.47	0.69
						-5	1.92	0.68	1.87	0.69	1.83	0.70	1.81	0.71	1.79	0.71	1.75	0.72	1.73	0.73
						0	2.19	0.72	2.14	0.73	2.09	0.74	2.07	0.74	2.05	0.75	2.02	0.75	1.99	0.76
						2	2.30	0.73	2.25	0.74	2.20	0.75	2.18	0.75	2.16	0.76	2.12	0.77	2.09	0.77
						7	2.52	0.75	2.46	0.77	2.42	0.78	2.40	0.78	2.37	0.79	2.33	0.79	2.30	0.80
						10	2.74	0.78	2.68	0.79	2.63	0.80	2.61	0.81	2.59	0.81	2.54	0.82	2.51	0.83
						15	3.01	0.81	2.95	0.82	2.90	0.83	2.88	0.84	2.85	0.84	2.81	0.85	2.77	0.86
2500			2500	63%	-15	1.77	0.68	1.72	0.69	1.67	0.69	1.65	0.70	1.63	0.70	1.59	0.71	1.56	0.72	
					-10	2.13	0.71	2.07	0.72	2.01	0.73	1.99	0.74	1.97	0.74	1.93	0.75	1.89	0.75	
					-5	2.48	0.75	2.42	0.76	2.36	0.77	2.33	0.77	2.31	0.78	2.27	0.78	2.23	0.79	
					0	2.83	0.78	2.76	0.79	2.71	0.80	2.68	0.81	2.65	0.81	2.61	0.82	2.57	0.83	
					2	2.97	0.79	2.90	0.81	2.84	0.82	2.82	0.82	2.79	0.83	2.74	0.84	2.70	0.84	
					7	3.25	0.82	3.18	0.83	3.12	0.85	3.10	0.85	3.06	0.86	3.01	0.87	2.97	0.87	
					10	3.54	0.85	3.46	0.86	3.40	0.87	3.37	0.88	3.34	0.88	3.29	0.89	3.24	0.90	
					15	3.89	0.88	3.81	0.90	3.75	0.91	3.71	0.92	3.68	0.92	3.63	0.93	3.58	0.94	
3500			3500	88%	-15	2.18	0.87	2.11	0.89	2.05	0.90	2.02	0.90	1.99	0.91	1.95	0.92	1.91	0.93	
					-10	2.61	0.92	2.53	0.93	2.47	0.95	2.44	0.95	2.41	0.96	2.36	0.97	2.32	0.97	
					-5	3.04	0.97	2.96	0.98	2.89	0.99	2.86	1.00	2.83	1.00	2.78	1.01	2.73	1.02	
					0	3.47	1.01	3.39	1.03	3.32	1.04	3.28	1.05	3.25	1.05	3.19	1.06	3.14	1.07	
					2	3.64	1.03	3.56	1.04	3.49	1.06	3.45	1.06	3.42	1.07	3.36	1.08	3.31	1.09	
					7	3.99	1.06	3.90	1.08	3.83	1.09	3.80	1.10	3.76	1.11	3.69	1.12	3.64	1.13	
					10	4.33	1.10	4.25	1.12	4.17	1.13	4.13	1.14	4.09	1.15	4.03	1.16	3.97	1.17	
					15	4.77	1.14	4.68	1.16	4.59	1.18	4.55	1.18	4.52	1.19	4.45	1.20	4.38	1.22	
2000	2000		4000	100%	-15	2.40	0.72	2.33	0.73	2.26	0.74	2.23	0.74	2.20	0.74	2.15	0.75	2.11	0.76	
					-10	2.88	0.75	2.80	0.76	2.73	0.77	2.70	0.78	2.67	0.78	2.61	0.79	2.57	0.80	
					-5	3.36	0.79	3.27	0.80	3.20	0.81	3.16	0.82	3.13	0.82	3.07	0.83	3.02	0.84	
					0	3.83	0.83	3.75	0.84	3.66	0.85	3.63	0.86	3.59	0.86	3.53	0.87	3.48	0.88	
					2	4.02	0.84	3.93	0.85	3.85	0.87	3.81	0.87	3.78	0.88	3.71	0.89	3.66	0.89	
					7	4.41	0.87	4.31	0.88	4.23	0.90	4.20	0.90	4.15	0.91	4.08	0.92	4.02	0.92	
					10	4.79	0.90	4.69	0.91	4.60	0.93	4.56	0.93	4.52	0.94	4.45	0.95	4.39	0.96	
					15	5.27	0.94	5.17	0.95	5.08	0.96	5.03	0.97	4.99	0.97	4.91	0.99	4.85	0.99	
2000	2500		4500	113%	-15	2.40	0.73	2.33	0.74	2.26	0.75	2.23	0.76	2.20	0.76	2.15	0.77	2.11	0.77	
					-10	2.88	0.77	2.80	0.78	2.73	0.79	2.70	0.80	2.67	0.80	2.61	0.81	2.57	0.82	
					-5	3.36	0.81	3.27	0.82	3.20	0.83	3.16	0.84	3.13	0.84	3.07	0.85	3.02	0.86	
					0	3.83	0.85	3.75	0.86	3.66	0.87	3.63	0.87	3.59	0.88	3.53	0.89	3.48	0.90	
					2	4.02	0.86	3.93	0.87	3.85	0.88	3.81	0.89	3.78	0.90	3.71	0.90	3.66	0.91	
					7	4.41	0.89	4.31	0.90	4.23	0.92	4.20	0.92	4.15	0.93	4.08	0.94	4.02	0.95	
					10	4.79	0.92	4.69	0.93	4.60	0.95	4.56	0.95	4.52	0.96	4.45	0.97	4.39	0.98	
					15	5.27	0.96	5.17	0.97	5.08	0.98	5.03	0.99	4.99	1.00	4.91	1.01	4.85	1.02	

12. Capacity Table

Combination (Capacity Index)				Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, DB)													
							14		16		18		20		21		22		24	
							TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
2000	3500		5500	138%	-15	2.40	0.74	2.33	0.75	2.26	0.76	2.23	0.76	2.20	0.77	2.15	0.78	2.11	0.78	
					-10	2.88	0.78	2.80	0.79	2.73	0.80	2.70	0.80	2.67	0.81	2.61	0.82	2.57	0.82	
					-5	3.36	0.82	3.27	0.83	3.20	0.84	3.16	0.84	3.13	0.85	3.07	0.86	3.02	0.87	
					0	3.83	0.85	3.75	0.87	3.66	0.88	3.63	0.88	3.59	0.89	3.53	0.90	3.48	0.91	
					2	4.02	0.87	3.93	0.88	3.85	0.89	3.81	0.90	3.78	0.91	3.71	0.91	3.66	0.92	
					7	4.41	0.90	4.31	0.91	4.23	0.93	4.20	0.93	4.15	0.94	4.08	0.95	4.02	0.96	
					10	4.79	0.93	4.69	0.94	4.60	0.96	4.56	0.96	4.52	0.97	4.45	0.98	4.39	0.99	
					15	5.27	0.97	5.17	0.98	5.08	1.00	5.03	1.00	4.99	1.01	4.91	1.02	4.85	1.03	
2500	2500		5000	125%	-15	2.40	0.75	2.33	0.76	2.26	0.77	2.23	0.77	2.20	0.78	2.15	0.78	2.11	0.79	
					-10	2.88	0.79	2.80	0.80	2.73	0.81	2.70	0.81	2.67	0.82	2.61	0.83	2.57	0.83	
					-5	3.36	0.83	3.27	0.84	3.20	0.85	3.16	0.85	3.13	0.86	3.07	0.87	3.02	0.87	
					0	3.83	0.86	3.75	0.88	3.66	0.89	3.63	0.89	3.59	0.90	3.53	0.91	3.48	0.92	
					2	4.02	0.88	3.93	0.89	3.85	0.90	3.81	0.91	3.78	0.91	3.71	0.92	3.66	0.93	
					7	4.41	0.91	4.31	0.92	4.23	0.94	4.20	0.94	4.15	0.95	4.08	0.96	4.02	0.97	
					10	4.79	0.94	4.69	0.95	4.60	0.97	4.56	0.97	4.52	0.98	4.45	0.99	4.39	1.00	
					15	5.27	0.98	5.17	0.99	5.08	1.01	5.03	1.01	4.99	1.02	4.91	1.03	4.85	1.04	
2500	3500		6000	150%	-15	2.40	0.76	2.33	0.77	2.26	0.78	2.23	0.78	2.20	0.79	2.15	0.79	2.11	0.80	
					-10	2.88	0.79	2.80	0.81	2.73	0.82	2.70	0.82	2.67	0.83	2.61	0.83	2.57	0.84	
					-5	3.36	0.83	3.27	0.85	3.20	0.86	3.16	0.86	3.13	0.87	3.07	0.88	3.02	0.88	
					0	3.83	0.87	3.75	0.89	3.66	0.90	3.63	0.90	3.59	0.91	3.53	0.92	3.48	0.93	
					2	4.02	0.89	3.93	0.90	3.85	0.91	3.81	0.92	3.78	0.92	3.71	0.93	3.66	0.94	
					7	4.41	0.92	4.31	0.93	4.23	0.95	4.20	0.95	4.15	0.96	4.08	0.97	4.02	0.98	
					10	4.79	0.95	4.69	0.96	4.60	0.98	4.56	0.98	4.52	0.99	4.45	1.00	4.39	1.01	
					15	5.27	0.99	5.17	1.00	5.08	1.02	5.03	1.02	4.99	1.03	4.91	1.04	4.85	1.05	

NOTE

- The performance table shows the average value of each conditions.
- The above is the value for connecting with the following indoor units.
 - 2000, 2500, 3500 class : AR07MXWSAWKNEU, AR09MXWSAWKNEU, AR12MXWSAWKNEU
- The total ability of connected a indoor unit is up to 6.0kW
- It is impossible to connect the indoor unit for one room only.
- This data is reference data for temperature capacity trend.

12. Capacity Table

11-2. AJ050NCJ2EG/EU

Cooling

Combination (Capacity Index)				Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, WB)													
							14		16		18		19		20		22		24	
							TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
2000				2000	40%	10	1.92	0.42	2.78	0.47	2.90	0.51	2.96	0.53	3.02	0.54	3.13	0.57	3.25	0.59
						12	1.92	0.44	2.74	0.49	2.85	0.53	2.91	0.54	2.97	0.56	3.09	0.58	3.21	0.60
						14	1.92	0.46	2.69	0.51	2.81	0.54	2.87	0.56	2.92	0.57	3.04	0.60	3.16	0.61
						16	1.92	0.48	2.65	0.52	2.76	0.56	2.82	0.57	2.88	0.59	3.00	0.61	3.11	0.63
						18	1.92	0.50	2.60	0.54	2.72	0.58	2.78	0.59	2.83	0.60	2.95	0.62	3.07	0.64
						20	1.92	0.52	2.56	0.56	2.67	0.59	2.73	0.61	2.79	0.62	2.90	0.64	3.02	0.65
						21	1.92	0.53	2.54	0.57	2.65	0.60	2.71	0.62	2.77	0.63	2.88	0.65	3.00	0.66
						23	1.92	0.55	2.50	0.59	2.61	0.62	2.66	0.63	2.72	0.64	2.83	0.66	2.95	0.67
						25	1.92	0.57	2.45	0.61	2.56	0.64	2.62	0.65	2.68	0.66	2.79	0.67	2.90	0.68
						27	1.92	0.59	2.41	0.63	2.52	0.66	2.58	0.67	2.63	0.68	2.74	0.69	2.86	0.70
						29	1.92	0.62	2.37	0.65	2.48	0.67	2.53	0.68	2.59	0.69	2.70	0.71	2.81	0.71
						31	1.92	0.64	2.32	0.67	2.43	0.69	2.49	0.70	2.54	0.71	2.65	0.72	2.76	0.72
						33	1.92	0.66	2.28	0.69	2.39	0.71	2.44	0.72	2.50	0.73	2.61	0.74	2.72	0.74
						35	1.92	0.68	2.24	0.71	2.34	0.73	2.40	0.73	2.45	0.75	2.56	0.75	2.67	0.75
						37	1.92	0.71	2.19	0.73	2.30	0.75	2.36	0.76	2.41	0.76	2.52	0.77	2.63	0.77
						39	1.92	0.73	2.15	0.75	2.26	0.77	2.31	0.78	2.37	0.78	2.47	0.79	2.58	0.78
						42	1.90	0.76	2.09	0.79	2.19	0.80	2.25	0.81	2.30	0.81	2.41	0.81	2.51	0.81
						44	1.80	0.79	2.05	0.81	2.15	0.82	2.20	0.83	2.26	0.83	2.36	0.83	2.47	0.82
						46	1.75	0.81	2.00	0.83	2.11	0.84	2.16	0.85	2.21	0.85	2.32	0.85	2.42	0.84
2500				2500	50%	10	2.00	0.46	2.90	0.52	3.02	0.56	3.08	0.58	3.14	0.60	3.26	0.63	3.39	0.65
						12	2.00	0.48	2.85	0.53	2.97	0.58	3.03	0.60	3.09	0.61	3.22	0.64	3.34	0.66
						14	2.00	0.51	2.80	0.55	2.93	0.60	2.99	0.61	3.05	0.63	3.17	0.65	3.29	0.67
						16	2.00	0.53	2.76	0.57	2.88	0.61	2.94	0.63	3.00	0.65	3.12	0.67	3.24	0.69
						18	2.00	0.55	2.71	0.59	2.83	0.63	2.89	0.65	2.95	0.66	3.07	0.68	3.19	0.70
						20	2.00	0.57	2.67	0.61	2.79	0.65	2.85	0.67	2.90	0.68	3.02	0.70	3.14	0.71
						21	2.00	0.58	2.64	0.62	2.76	0.66	2.82	0.67	2.88	0.69	3.00	0.71	3.12	0.72
						23	2.00	0.61	2.60	0.65	2.72	0.68	2.78	0.69	2.83	0.71	2.95	0.72	3.07	0.73
						25	2.00	0.63	2.55	0.67	2.67	0.70	2.73	0.71	2.79	0.72	2.91	0.74	3.02	0.75
						27	2.00	0.65	2.51	0.69	2.62	0.72	2.68	0.73	2.74	0.74	2.86	0.76	2.98	0.76
						29	2.00	0.68	2.46	0.71	2.58	0.74	2.64	0.75	2.69	0.76	2.81	0.77	2.93	0.78
						31	2.00	0.70	2.42	0.73	2.53	0.76	2.59	0.77	2.65	0.78	2.76	0.79	2.88	0.79
						33	2.00	0.72	2.37	0.76	2.49	0.78	2.54	0.79	2.60	0.80	2.72	0.81	2.83	0.81
						35	2.00	0.75	2.33	0.78	2.44	0.80	2.50	0.80	2.56	0.82	2.67	0.83	2.78	0.83
						37	2.00	0.77	2.29	0.80	2.40	0.82	2.45	0.83	2.51	0.84	2.62	0.84	2.74	0.84
						39	2.00	0.80	2.24	0.83	2.35	0.85	2.41	0.85	2.46	0.86	2.58	0.86	2.69	0.86
						42	1.98	0.84	2.18	0.86	2.29	0.88	2.34	0.88	2.40	0.89	2.51	0.89	2.62	0.88
						44	1.88	0.86	2.13	0.89	2.24	0.90	2.30	0.91	2.35	0.91	2.46	0.91	2.57	0.90
						46	1.83	0.89	2.09	0.91	2.20	0.93	2.25	0.93	2.30	0.93	2.41	0.93	2.53	0.92

12. Capacity Table

Combination (Capacity Index)				Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, WB)													
							14		16		18		19		20		22		24	
							TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
3500				3500	70%	10	2.80	0.63	4.06	0.70	4.23	0.76	4.31	0.79	4.40	0.81	4.57	0.85	4.74	0.88
						12	2.80	0.66	3.99	0.73	4.16	0.79	4.25	0.81	4.33	0.83	4.50	0.87	4.68	0.90
						14	2.80	0.69	3.93	0.75	4.10	0.81	4.18	0.83	4.26	0.86	4.44	0.89	4.61	0.92
						16	2.80	0.72	3.86	0.78	4.03	0.84	4.11	0.86	4.20	0.88	4.37	0.91	4.54	0.93
						18	2.80	0.75	3.80	0.81	3.96	0.86	4.05	0.88	4.13	0.90	4.30	0.93	4.47	0.95
						20	2.80	0.78	3.73	0.84	3.90	0.89	3.98	0.91	4.07	0.92	4.23	0.95	4.40	0.97
						21	2.80	0.79	3.70	0.85	3.87	0.90	3.95	0.92	4.03	0.94	4.20	0.96	4.37	0.98
						23	2.80	0.82	3.64	0.88	3.80	0.93	3.89	0.94	3.97	0.96	4.13	0.99	4.30	1.00
						25	2.80	0.86	3.58	0.91	3.74	0.95	3.82	0.97	3.90	0.99	4.07	1.01	4.23	1.02
						27	2.80	0.89	3.51	0.94	3.67	0.98	3.76	1.00	3.84	1.01	4.00	1.03	4.17	1.04
						29	2.80	0.92	3.45	0.97	3.61	1.01	3.69	1.02	3.77	1.04	3.93	1.05	4.10	1.06
						31	2.80	0.95	3.39	1.00	3.55	1.04	3.63	1.05	3.71	1.06	3.87	1.08	4.03	1.08
						33	2.80	0.99	3.32	1.03	3.48	1.06	3.56	1.08	3.64	1.09	3.80	1.10	3.97	1.10
						35	2.80	1.02	3.26	1.06	3.42	1.09	3.50	1.09	3.58	1.11	3.74	1.12	3.90	1.12
						37	2.80	1.05	3.20	1.09	3.36	1.12	3.43	1.13	3.51	1.14	3.67	1.15	3.83	1.15
						39	2.80	1.09	3.14	1.13	3.29	1.15	3.37	1.16	3.45	1.17	3.61	1.17	3.77	1.17
						42	2.77	1.14	3.05	1.17	3.20	1.20	3.28	1.21	3.35	1.21	3.51	1.21	3.67	1.21
						44	2.63	1.18	2.98	1.21	3.14	1.23	3.21	1.24	3.29	1.24	3.45	1.24	3.60	1.23
						46	2.56	1.21	2.92	1.24	3.07	1.26	3.15	1.27	3.23	1.27	3.38	1.27	3.54	1.25
2000	2000			4000	80%	10	3.53	0.69	4.99	0.71	5.08	0.72	5.14	0.73	5.20	0.74	5.35	0.75	5.52	0.77
						12	3.53	0.71	4.85	0.72	4.95	0.74	5.01	0.75	5.08	0.76	5.23	0.77	5.41	0.79
						14	3.53	0.72	4.72	0.74	4.83	0.76	4.89	0.77	4.96	0.77	5.12	0.79	5.31	0.80
						16	3.53	0.74	4.60	0.76	4.71	0.78	4.78	0.78	4.85	0.79	5.02	0.81	5.21	0.82
						18	3.53	0.76	4.48	0.78	4.60	0.79	4.67	0.80	4.75	0.81	4.92	0.83	5.12	0.84
						20	3.53	0.78	4.36	0.80	4.49	0.81	4.57	0.82	4.65	0.83	4.83	0.84	5.03	0.86
						21	3.53	0.79	4.31	0.81	4.44	0.82	4.52	0.83	4.60	0.84	4.78	0.85	4.99	0.87
						23	3.53	0.81	4.20	0.83	4.34	0.84	4.42	0.85	4.51	0.86	4.70	0.87	4.91	0.89
						25	3.53	0.83	4.10	0.85	4.25	0.86	4.33	0.87	4.42	0.88	4.62	0.90	4.84	0.91
						27	3.53	0.85	4.01	0.87	4.16	0.89	4.25	0.89	4.34	0.90	4.55	0.92	4.78	0.93
						29	3.53	0.87	3.92	0.89	4.08	0.91	4.17	0.91	4.27	0.92	4.48	0.94	4.72	0.95
						31	3.53	0.90	3.84	0.91	4.01	0.93	4.10	0.94	4.20	0.94	4.42	0.96	4.66	0.97
						33	3.53	0.92	3.76	0.94	3.94	0.95	4.03	0.96	4.13	0.97	4.36	0.98	4.61	1.00
						35	3.53	0.94	3.69	0.96	3.87	0.97	4.00	0.98	4.08	0.99	4.31	1.00	4.57	1.02
						37	3.53	0.97	3.62	0.98	3.81	1.00	3.91	1.01	4.02	1.01	4.26	1.03	4.53	1.04
						39	3.53	0.99	3.56	1.01	3.76	1.02	3.86	1.03	3.98	1.04	4.22	1.05	4.49	1.07
						42	3.53	1.03	3.48	1.04	3.69	1.06	3.80	1.07	3.92	1.07	4.17	1.09	4.46	1.10
						44	3.53	1.05	3.44	1.07	3.65	1.09	3.76	1.09	3.89	1.10	4.15	1.11	4.44	1.13
						46	3.53	1.08	3.39	1.10	3.61	1.11	3.73	1.12	3.86	1.13	4.13	1.14	4.42	1.15

12. Capacity Table

Combination (Capacity Index)				Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, WB)													
							14		16		18		19		20		22		24	
							TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
2000	2500			4500	90%	10	4.07	0.79	5.73	0.81	5.84	0.83	5.91	0.84	5.98	0.84	6.15	0.86	6.34	0.88
						12	4.07	0.81	5.58	0.83	5.69	0.85	5.76	0.85	5.84	0.86	6.02	0.88	6.22	0.90
						14	4.07	0.83	5.43	0.85	5.55	0.87	5.63	0.88	5.71	0.88	5.89	0.90	6.10	0.92
						16	4.07	0.85	5.29	0.87	5.42	0.89	5.50	0.90	5.58	0.90	5.77	0.92	5.99	0.94
						18	4.07	0.87	5.15	0.89	5.29	0.91	5.37	0.92	5.46	0.93	5.66	0.94	5.89	0.96
						20	4.07	0.89	5.02	0.91	5.17	0.93	5.25	0.94	5.34	0.95	5.55	0.97	5.79	0.98
						21	4.07	0.90	4.96	0.92	5.11	0.94	5.19	0.95	5.29	0.96	5.50	0.98	5.74	0.99
						23	4.07	0.93	4.83	0.95	4.99	0.96	5.09	0.97	5.18	0.98	5.40	1.00	5.65	1.02
						25	4.07	0.95	4.72	0.97	4.89	0.99	4.98	1.00	5.09	1.01	5.31	1.02	5.57	1.04
						27	4.07	0.97	4.61	0.99	4.79	1.01	4.89	1.02	4.99	1.03	5.23	1.05	5.49	1.06
						29	4.07	1.00	4.51	1.02	4.69	1.04	4.80	1.05	4.91	1.05	5.15	1.07	5.42	1.09
						31	4.07	1.02	4.42	1.04	4.61	1.06	4.71	1.07	4.83	1.08	5.08	1.10	5.36	1.11
						33	4.07	1.05	4.33	1.07	4.53	1.09	4.64	1.10	4.76	1.11	5.01	1.12	5.30	1.14
						35	4.07	1.08	4.24	1.10	4.45	1.11	4.60	1.12	4.69	1.13	4.96	1.15	5.25	1.16
						37	4.07	1.10	4.17	1.12	4.38	1.14	4.50	1.15	4.63	1.16	4.90	1.18	5.21	1.19
						39	4.07	1.13	4.10	1.15	4.32	1.17	4.44	1.18	4.57	1.19	4.86	1.20	5.17	1.22
						42	4.07	1.17	4.01	1.19	4.24	1.21	4.37	1.22	4.51	1.23	4.80	1.25	5.12	1.26
						44	4.07	1.20	3.95	1.22	4.20	1.24	4.33	1.25	4.47	1.26	4.77	1.27	5.10	1.29
						46	4.07	1.23	3.90	1.25	4.16	1.27	4.29	1.28	4.44	1.29	4.75	1.30	5.09	1.32
2000	3500			5500	110%	10	4.42	0.86	6.23	0.89	6.35	0.91	6.42	0.92	6.50	0.93	6.68	0.95	6.90	0.97
						12	4.42	0.89	6.06	0.91	6.19	0.93	6.27	0.94	6.35	0.95	6.54	0.97	6.76	0.99
						14	4.42	0.91	5.90	0.93	6.04	0.95	6.12	0.96	6.20	0.97	6.40	0.99	6.63	1.01
						16	4.42	0.93	5.75	0.95	5.89	0.97	5.97	0.98	6.06	0.99	6.27	1.01	6.51	1.03
						18	4.42	0.95	5.60	0.98	5.75	1.00	5.84	1.01	5.93	1.02	6.15	1.04	6.40	1.06
						20	4.42	0.98	5.45	1.00	5.62	1.02	5.71	1.03	5.81	1.04	6.03	1.06	6.29	1.08
						21	4.42	0.99	5.39	1.01	5.55	1.03	5.65	1.04	5.75	1.05	5.98	1.07	6.24	1.09
						23	4.42	1.02	5.25	1.04	5.43	1.06	5.53	1.07	5.63	1.08	5.87	1.10	6.14	1.12
						25	4.42	1.04	5.13	1.06	5.31	1.08	5.42	1.09	5.53	1.10	5.77	1.12	6.05	1.14
						27	4.42	1.07	5.01	1.09	5.20	1.11	5.31	1.12	5.43	1.13	5.68	1.15	5.97	1.17
						29	4.42	1.10	4.90	1.12	5.10	1.14	5.21	1.15	5.33	1.16	5.60	1.18	5.89	1.19
						31	4.42	1.12	4.80	1.15	5.01	1.17	5.12	1.18	5.25	1.19	5.52	1.20	5.82	1.22
						33	4.42	1.15	4.70	1.17	4.92	1.19	5.04	1.20	5.17	1.21	5.45	1.23	5.76	1.25
						35	4.42	1.18	4.61	1.20	4.84	1.22	5.00	1.23	5.10	1.24	5.39	1.26	5.71	1.28
						37	4.42	1.21	4.53	1.23	4.76	1.25	4.89	1.26	5.03	1.27	5.33	1.29	5.66	1.31
						39	4.42	1.24	4.45	1.26	4.70	1.28	4.83	1.29	4.97	1.30	5.28	1.32	5.62	1.34
						42	4.42	1.29	4.35	1.31	4.61	1.33	4.75	1.34	4.90	1.35	5.22	1.37	5.57	1.39
						44	4.42	1.32	4.30	1.34	4.56	1.36	4.70	1.37	4.86	1.38	5.18	1.40	5.55	1.42
						46	4.42	1.35	4.24	1.38	4.52	1.39	4.67	1.40	4.82	1.41	5.16	1.43	5.53	1.45

12. Capacity Table

Combination (Capacity Index)				Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, WB)													
							14		16		18		19		20		22		24	
							TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
2500	2500			5000	100%	10	4.42	0.86	6.23	0.88	6.35	0.90	6.42	0.91	6.50	0.92	6.68	0.94	6.90	0.96
						12	4.42	0.88	6.06	0.90	6.19	0.92	6.27	0.93	6.35	0.94	6.54	0.96	6.76	0.98
						14	4.42	0.90	5.90	0.92	6.04	0.94	6.12	0.95	6.20	0.96	6.40	0.98	6.63	1.00
						16	4.42	0.92	5.75	0.95	5.89	0.97	5.97	0.98	6.06	0.99	6.27	1.00	6.51	1.02
						18	4.42	0.95	5.60	0.97	5.75	0.99	5.84	1.00	5.93	1.01	6.15	1.03	6.40	1.05
						20	4.42	0.97	5.45	0.99	5.62	1.01	5.71	1.02	5.81	1.03	6.03	1.05	6.29	1.07
						21	4.42	0.98	5.39	1.00	5.55	1.03	5.65	1.04	5.75	1.04	5.98	1.06	6.24	1.08
						23	4.42	1.01	5.25	1.03	5.43	1.05	5.53	1.06	5.63	1.07	5.87	1.09	6.14	1.11
						25	4.42	1.03	5.13	1.06	5.31	1.08	5.42	1.09	5.53	1.10	5.77	1.11	6.05	1.13
						27	4.42	1.06	5.01	1.08	5.20	1.10	5.31	1.11	5.43	1.12	5.68	1.14	5.97	1.16
						29	4.42	1.09	4.90	1.11	5.10	1.13	5.21	1.14	5.33	1.15	5.60	1.17	5.89	1.18
						31	4.42	1.12	4.80	1.14	5.01	1.16	5.12	1.17	5.25	1.18	5.52	1.19	5.82	1.21
						33	4.42	1.14	4.70	1.16	4.92	1.18	5.04	1.19	5.17	1.20	5.45	1.22	5.76	1.24
						35	4.42	1.17	4.61	1.19	4.84	1.21	5.00	1.22	5.10	1.23	5.39	1.25	5.71	1.27
						37	4.42	1.20	4.53	1.22	4.76	1.24	4.89	1.25	5.03	1.26	5.33	1.28	5.66	1.30
						39	4.42	1.23	4.45	1.25	4.70	1.27	4.83	1.28	4.97	1.29	5.28	1.31	5.62	1.33
						42	4.42	1.28	4.35	1.30	4.61	1.32	4.75	1.33	4.90	1.34	5.22	1.36	5.57	1.37
						44	4.42	1.31	4.30	1.33	4.56	1.35	4.70	1.36	4.86	1.37	5.18	1.39	5.55	1.41
						46	4.42	1.34	4.24	1.36	4.52	1.38	4.67	1.39	4.82	1.40	5.16	1.42	5.53	1.44
2500	3500			6000	120%	10	4.42	0.86	6.23	0.89	6.35	0.91	6.42	0.92	6.50	0.93	6.68	0.95	6.90	0.97
						12	4.42	0.89	6.06	0.91	6.19	0.93	6.27	0.94	6.35	0.95	6.54	0.97	6.76	0.99
						14	4.42	0.91	5.90	0.93	6.04	0.95	6.12	0.96	6.20	0.97	6.40	0.99	6.63	1.01
						16	4.42	0.93	5.75	0.95	5.89	0.97	5.97	0.98	6.06	0.99	6.27	1.01	6.51	1.03
						18	4.42	0.95	5.60	0.98	5.75	1.00	5.84	1.01	5.93	1.02	6.15	1.04	6.40	1.06
						20	4.42	0.98	5.45	1.00	5.62	1.02	5.71	1.03	5.81	1.04	6.03	1.06	6.29	1.08
						21	4.42	0.99	5.39	1.01	5.55	1.03	5.65	1.04	5.75	1.05	5.98	1.07	6.24	1.09
						23	4.42	1.02	5.25	1.04	5.43	1.06	5.53	1.07	5.63	1.08	5.87	1.10	6.14	1.12
						25	4.42	1.04	5.13	1.06	5.31	1.08	5.42	1.09	5.53	1.10	5.77	1.12	6.05	1.14
						27	4.42	1.07	5.01	1.09	5.20	1.11	5.31	1.12	5.43	1.13	5.68	1.15	5.97	1.17
						29	4.42	1.10	4.90	1.12	5.10	1.14	5.21	1.15	5.33	1.16	5.60	1.18	5.89	1.19
						31	4.42	1.12	4.80	1.15	5.01	1.17	5.12	1.18	5.25	1.19	5.52	1.20	5.82	1.22
						33	4.42	1.15	4.70	1.17	4.92	1.19	5.04	1.20	5.17	1.21	5.45	1.23	5.76	1.25
						35	4.42	1.18	4.61	1.20	4.84	1.22	5.00	1.23	5.10	1.24	5.39	1.26	5.71	1.28
						37	4.42	1.21	4.53	1.23	4.76	1.25	4.89	1.26	5.03	1.27	5.33	1.29	5.66	1.31
						39	4.42	1.24	4.45	1.26	4.70	1.28	4.83	1.29	4.97	1.30	5.28	1.32	5.62	1.34
						42	4.42	1.29	4.35	1.31	4.61	1.33	4.75	1.34	4.90	1.35	5.22	1.37	5.57	1.39
						44	4.42	1.32	4.30	1.34	4.56	1.36	4.70	1.37	4.86	1.38	5.18	1.40	5.55	1.42
						46	4.42	1.35	4.24	1.38	4.52	1.39	4.67	1.40	4.82	1.41	5.16	1.43	5.53	1.45

12. Capacity Table

Combination (Capacity Index)				Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, WB)													
							14		16		18		19		20		22		24	
							TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
3500	3500			7000	140%	10	4.42	0.87	6.23	0.89	6.35	0.91	6.42	0.92	6.50	0.94	6.68	0.95	6.90	0.97
						12	4.42	0.89	6.06	0.91	6.19	0.94	6.27	0.95	6.35	0.96	6.54	0.98	6.76	1.00
						14	4.42	0.92	5.90	0.94	6.04	0.96	6.12	0.97	6.20	0.98	6.40	1.00	6.63	1.02
						16	4.42	0.94	5.75	0.96	5.89	0.98	5.97	0.99	6.06	1.00	6.27	1.02	6.51	1.04
						18	4.42	0.96	5.60	0.98	5.75	1.01	5.84	1.02	5.93	1.03	6.15	1.04	6.40	1.06
						20	4.42	0.99	5.45	1.01	5.62	1.03	5.71	1.04	5.81	1.05	6.03	1.07	6.29	1.09
						21	4.42	1.00	5.39	1.02	5.55	1.04	5.65	1.05	5.75	1.06	5.98	1.08	6.24	1.10
						23	4.42	1.03	5.25	1.05	5.43	1.07	5.53	1.08	5.63	1.09	5.87	1.11	6.14	1.13
						25	4.42	1.05	5.13	1.07	5.31	1.09	5.42	1.10	5.53	1.11	5.77	1.13	6.05	1.15
						27	4.42	1.08	5.01	1.10	5.20	1.12	5.31	1.13	5.43	1.14	5.68	1.16	5.97	1.18
						29	4.42	1.11	4.90	1.13	5.10	1.15	5.21	1.16	5.33	1.17	5.60	1.19	5.89	1.20
						31	4.42	1.13	4.80	1.15	5.01	1.18	5.12	1.19	5.25	1.19	5.52	1.21	5.82	1.23
						33	4.42	1.16	4.70	1.18	4.92	1.20	5.04	1.21	5.17	1.22	5.45	1.24	5.76	1.26
						35	4.42	1.19	4.61	1.21	4.84	1.23	5.00	1.24	5.10	1.25	5.39	1.27	5.71	1.29
						37	4.42	1.22	4.53	1.24	4.76	1.26	4.89	1.27	5.03	1.28	5.33	1.30	5.66	1.32
						39	4.42	1.25	4.45	1.27	4.70	1.29	4.83	1.30	4.97	1.31	5.28	1.33	5.62	1.35
						42	4.42	1.30	4.35	1.32	4.61	1.34	4.75	1.35	4.90	1.36	5.22	1.38	5.57	1.40
						44	4.42	1.33	4.30	1.35	4.56	1.37	4.70	1.38	4.86	1.39	5.18	1.41	5.55	1.43
						46	4.42	1.37	4.24	1.39	4.52	1.41	4.67	1.42	4.82	1.43	5.16	1.44	5.53	1.46

NOTE

- The performance table shows the average value of each conditions.
- The above is the value for connecting with the following indoor units.
 - 2000, 2500, 3500 class : AR07MXWSAWKNEU, AR09MXWSAWKNEU, AR12MXWSAWKNEU
- The total ability of connected a indoor unit is up to 7.0kW
- It is impossible to connect the indoor unit for one room only.
- This data is reference data for temperature capacity trend.

12. Capacity Table

11-2. AJ050NCJ2EG/EU

Heating

Combination (Capacity Index)				Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C,DB)													
							14		16		18		20		21		22		24	
							TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
2000				2000	40%	-15	1.43	0.70	1.39	0.71	1.35	0.72	1.33	0.72	1.31	0.73	1.28	0.73	1.26	0.74
						-10	1.71	0.74	1.67	0.75	1.62	0.76	1.60	0.76	1.59	0.77	1.55	0.77	1.53	0.78
						-5	2.00	0.77	1.95	0.78	1.90	0.79	1.88	0.80	1.86	0.80	1.83	0.81	1.80	0.82
						0	2.28	0.81	2.23	0.82	2.18	0.83	2.16	0.84	2.14	0.84	2.10	0.85	2.07	0.86
						2	2.40	0.82	2.34	0.84	2.29	0.85	2.27	0.85	2.25	0.86	2.21	0.87	2.18	0.87
						7	2.62	0.85	2.57	0.86	2.52	0.88	2.50	0.88	2.47	0.89	2.43	0.90	2.39	0.90
						10	2.85	0.88	2.79	0.89	2.74	0.91	2.72	0.91	2.69	0.92	2.65	0.93	2.61	0.93
						15	3.14	0.92	3.08	0.93	3.02	0.94	3.00	0.95	2.97	0.95	2.93	0.96	2.88	0.97
2500				2500	50%	-15	1.89	0.83	1.83	0.85	1.78	0.86	1.75	0.86	1.73	0.87	1.69	0.88	1.66	0.88
						-10	2.26	0.88	2.20	0.89	2.14	0.90	2.12	0.91	2.09	0.91	2.05	0.92	2.02	0.93
						-5	2.64	0.92	2.57	0.94	2.51	0.95	2.48	0.95	2.46	0.96	2.41	0.97	2.37	0.98
						0	3.01	0.96	2.94	0.98	2.88	0.99	2.85	1.00	2.82	1.00	2.77	1.01	2.73	1.02
						2	3.16	0.98	3.09	1.00	3.03	1.01	3.00	1.02	2.97	1.02	2.92	1.03	2.87	1.04
						7	3.46	1.02	3.39	1.03	3.32	1.05	3.30	1.05	3.26	1.06	3.21	1.07	3.16	1.08
						10	3.76	1.05	3.69	1.07	3.62	1.08	3.59	1.09	3.55	1.09	3.50	1.10	3.45	1.12
						15	4.14	1.09	4.06	1.11	3.99	1.12	3.95	1.13	3.92	1.14	3.86	1.15	3.81	1.16
3500				3500	70%	-15	2.29	1.03	2.22	1.05	2.15	1.06	2.13	1.07	2.10	1.07	2.05	1.08	2.01	1.09
						-10	2.74	1.09	2.67	1.10	2.60	1.12	2.57	1.12	2.54	1.13	2.49	1.14	2.44	1.15
						-5	3.20	1.14	3.12	1.16	3.04	1.17	3.01	1.18	2.98	1.19	2.92	1.20	2.88	1.21
						0	3.65	1.19	3.57	1.21	3.49	1.23	3.46	1.24	3.42	1.24	3.36	1.26	3.31	1.27
						2	3.83	1.22	3.75	1.23	3.67	1.25	3.63	1.26	3.60	1.27	3.54	1.28	3.48	1.29
						7	4.20	1.26	4.11	1.28	4.03	1.29	4.00	1.30	3.95	1.31	3.89	1.32	3.83	1.34
						10	4.56	1.30	4.47	1.32	4.38	1.34	4.35	1.35	4.31	1.35	4.24	1.37	4.18	1.38
						15	5.02	1.35	4.92	1.37	4.83	1.39	4.79	1.40	4.75	1.41	4.68	1.42	4.62	1.44
2000	2000			4000	80%	-15	2.52	0.80	2.44	0.81	2.37	0.83	2.34	0.83	2.31	0.83	2.26	0.84	2.21	0.85
						-10	3.02	0.84	2.93	0.86	2.86	0.87	2.82	0.87	2.79	0.88	2.74	0.89	2.69	0.89
						-5	3.52	0.89	3.43	0.90	3.35	0.91	3.31	0.92	3.28	0.92	3.22	0.93	3.16	0.94
						0	4.02	0.93	3.92	0.94	3.84	0.95	3.80	0.96	3.76	0.97	3.70	0.98	3.64	0.98
						2	4.22	0.94	4.12	0.96	4.04	0.97	4.00	0.98	3.96	0.98	3.89	0.99	3.83	1.00
						7	4.62	0.98	4.52	0.99	4.43	1.01	4.40	1.01	4.35	1.02	4.28	1.03	4.21	1.04
						10	5.02	1.01	4.92	1.03	4.82	1.04	4.78	1.05	4.74	1.05	4.66	1.06	4.60	1.07
						15	5.52	1.05	5.41	1.07	5.32	1.08	5.27	1.09	5.23	1.09	5.15	1.11	5.08	1.12
2000	2500			4500	90%	-15	2.92	1.04	2.83	1.06	2.75	1.07	2.71	1.08	2.68	1.08	2.62	1.09	2.56	1.10
						-10	3.50	1.10	3.40	1.11	3.31	1.13	3.27	1.13	3.24	1.14	3.17	1.15	3.12	1.16
						-5	4.08	1.15	3.97	1.17	3.88	1.18	3.84	1.19	3.80	1.20	3.73	1.21	3.67	1.22
						0	4.66	1.20	4.55	1.22	4.45	1.24	4.41	1.25	4.36	1.25	4.29	1.27	4.22	1.28
						2	4.89	1.23	4.78	1.24	4.68	1.26	4.63	1.27	4.59	1.27	4.51	1.29	4.44	1.30
						7	5.35	1.27	5.24	1.29	5.13	1.30	5.10	1.31	5.04	1.32	4.96	1.33	4.89	1.35
						10	5.82	1.31	5.70	1.33	5.59	1.35	5.54	1.36	5.49	1.36	5.41	1.38	5.33	1.39
						15	6.40	1.36	6.28	1.38	6.16	1.40	6.11	1.41	6.06	1.42	5.97	1.43	5.88	1.45

12. Capacity Table

Combination (Capacity Index)				Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, DB)													
							14		16		18		20		21		22		24	
							TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
2000	3500			5500	110%	-15	3.21	1.03	3.11	1.04	3.02	1.05	2.98	1.06	2.94	1.07	2.87	1.08	2.82	1.09
						-10	3.84	1.08	3.73	1.10	3.64	1.11	3.60	1.12	3.55	1.12	3.48	1.13	3.42	1.14
						-5	4.48	1.13	4.36	1.15	4.26	1.16	4.22	1.17	4.17	1.18	4.09	1.19	4.03	1.20
						0	5.11	1.19	4.99	1.20	4.89	1.22	4.84	1.23	4.79	1.23	4.71	1.25	4.63	1.26
						2	5.37	1.21	5.25	1.22	5.14	1.24	5.09	1.25	5.04	1.26	4.95	1.27	4.88	1.28
						7	5.88	1.25	5.75	1.27	5.64	1.28	5.60	1.29	5.54	1.30	5.44	1.31	5.36	1.33
						10	6.39	1.29	6.26	1.31	6.14	1.33	6.08	1.34	6.03	1.34	5.94	1.36	5.85	1.37
						15	7.03	1.34	6.89	1.36	6.77	1.38	6.71	1.39	6.65	1.40	6.55	1.41	6.46	1.43
2500	2500			5000	100%	-15	3.21	1.02	3.11	1.03	3.02	1.05	2.98	1.05	2.94	1.06	2.87	1.07	2.82	1.08
						-10	3.84	1.07	3.73	1.09	3.64	1.10	3.60	1.11	3.55	1.11	3.48	1.12	3.42	1.13
						-5	4.48	1.12	4.36	1.14	4.26	1.16	4.22	1.16	4.17	1.17	4.09	1.18	4.03	1.19
						0	5.11	1.18	4.99	1.19	4.89	1.21	4.84	1.22	4.79	1.22	4.71	1.24	4.63	1.25
						2	5.37	1.20	5.25	1.21	5.14	1.23	5.09	1.24	5.04	1.25	4.95	1.26	4.88	1.27
						7	5.88	1.24	5.75	1.26	5.64	1.27	5.60	1.28	5.54	1.29	5.44	1.30	5.36	1.32
						10	6.39	1.28	6.26	1.30	6.14	1.32	6.08	1.32	6.03	1.33	5.94	1.35	5.85	1.36
						15	7.03	1.33	6.89	1.35	6.77	1.37	6.71	1.38	6.65	1.39	6.55	1.40	6.46	1.41
2500	3500			6000	120%	-15	3.21	1.03	3.11	1.04	3.02	1.05	2.98	1.06	2.94	1.07	2.87	1.08	2.82	1.09
						-10	3.84	1.08	3.73	1.10	3.64	1.11	3.60	1.12	3.55	1.12	3.48	1.13	3.42	1.14
						-5	4.48	1.13	4.36	1.15	4.26	1.16	4.22	1.17	4.17	1.18	4.09	1.19	4.03	1.20
						0	5.11	1.19	4.99	1.20	4.89	1.22	4.84	1.23	4.79	1.23	4.71	1.25	4.63	1.26
						2	5.37	1.21	5.25	1.22	5.14	1.24	5.09	1.25	5.04	1.26	4.95	1.27	4.88	1.28
						7	5.88	1.25	5.75	1.27	5.64	1.28	5.60	1.29	5.54	1.30	5.44	1.31	5.36	1.33
						10	6.39	1.29	6.26	1.31	6.14	1.33	6.08	1.34	6.03	1.34	5.94	1.36	5.85	1.37
						15	7.03	1.34	6.89	1.36	6.77	1.38	6.71	1.39	6.65	1.40	6.55	1.41	6.46	1.43
3500	3500			7000	140%	-15	3.21	1.03	3.11	1.05	3.02	1.06	2.98	1.07	2.94	1.07	2.87	1.08	2.82	1.09
						-10	3.84	1.09	3.73	1.10	3.64	1.12	3.60	1.12	3.55	1.13	3.48	1.14	3.42	1.15
						-5	4.48	1.14	4.36	1.16	4.26	1.17	4.22	1.18	4.17	1.19	4.09	1.20	4.03	1.21
						0	5.11	1.19	4.99	1.21	4.89	1.23	4.84	1.24	4.79	1.24	4.71	1.26	4.63	1.27
						2	5.37	1.22	5.25	1.23	5.14	1.25	5.09	1.26	5.04	1.27	4.95	1.28	4.88	1.29
						7	5.88	1.26	5.75	1.28	5.64	1.29	5.60	1.30	5.54	1.31	5.44	1.32	5.36	1.34
						10	6.39	1.30	6.26	1.32	6.14	1.34	6.08	1.35	6.03	1.35	5.94	1.37	5.85	1.38
						15	7.03	1.35	6.89	1.37	6.77	1.39	6.71	1.40	6.65	1.41	6.55	1.42	6.46	1.44

NOTE

- The performance table shows the average value of each conditions.
- The above is the value for connecting with the following indoor units.
 - 2000, 2500, 3500 class : AR07MXWSAWKNEU, AR09MXWSAWKNEU, AR12MXWSAWKNEU
- The total ability of connected a indoor unit is up to 7.0kW
- It is impossible to connect the indoor unit for one room only.
- This data is reference data for temperature capacity trend.

12. Capacity Table

11-3. AJ052RCJ3EGEU

Cooling

Combination (Capacity Index)			Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, WB)													
						14		16		18		19		20		22		24	
						TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
2000			2000	38%	10	1.60	0.36	2.32	0.41	2.42	0.44	2.46	0.46	2.51	0.47	2.61	0.49	2.71	0.51
					12	1.60	0.38	2.28	0.42	2.38	0.45	2.43	0.47	2.48	0.48	2.57	0.50	2.67	0.52
					14	1.60	0.40	2.24	0.44	2.34	0.47	2.39	0.48	2.44	0.50	2.53	0.52	2.63	0.53
					16	1.60	0.41	2.21	0.45	2.30	0.48	2.35	0.50	2.40	0.51	2.50	0.53	2.59	0.54
					18	1.60	0.43	2.17	0.47	2.27	0.50	2.31	0.51	2.36	0.52	2.46	0.54	2.55	0.55
					20	1.60	0.45	2.13	0.48	2.23	0.51	2.28	0.52	2.32	0.53	2.42	0.55	2.52	0.56
					21	1.60	0.46	2.12	0.49	2.21	0.52	2.26	0.53	2.30	0.54	2.40	0.56	2.50	0.57
					23	1.60	0.48	2.08	0.51	2.17	0.53	2.22	0.55	2.27	0.56	2.36	0.57	2.46	0.58
					25	1.60	0.49	2.04	0.53	2.14	0.55	2.18	0.56	2.23	0.57	2.32	0.58	2.42	0.59
					27	1.60	0.51	2.01	0.54	2.10	0.57	2.15	0.58	2.19	0.58	2.29	0.60	2.38	0.60
					29	1.60	0.53	1.97	0.56	2.06	0.58	2.11	0.59	2.16	0.60	2.25	0.61	2.34	0.61
					31	1.60	0.55	1.94	0.58	2.03	0.60	2.07	0.61	2.12	0.61	2.21	0.62	2.30	0.62
					33	1.60	0.57	1.90	0.60	1.99	0.61	2.04	0.62	2.08	0.63	2.17	0.64	2.27	0.64
					35	1.60	0.59	1.86	0.61	1.95	0.63	2.00	0.63	2.04	0.64	2.14	0.65	2.23	0.65
					37	1.60	0.61	1.83	0.63	1.92	0.65	1.96	0.65	2.01	0.66	2.10	0.66	2.19	0.66
					39	1.60	0.63	1.79	0.65	1.88	0.67	1.93	0.67	1.97	0.68	2.06	0.68	2.15	0.68
					42	1.58	0.66	1.74	0.68	1.83	0.69	1.87	0.70	1.92	0.70	2.01	0.70	2.10	0.70
					44	1.50	0.68	1.71	0.70	1.79	0.71	1.84	0.71	1.88	0.72	1.97	0.72	2.06	0.71
					46	1.46	0.70	1.67	0.72	1.76	0.73	1.80	0.73	1.84	0.73	1.93	0.73	2.02	0.72
2500			2500	48%	10	2.00	0.46	2.90	0.51	3.02	0.55	3.08	0.57	3.14	0.59	3.26	0.62	3.39	0.64
					12	2.00	0.48	2.85	0.53	2.97	0.57	3.03	0.59	3.09	0.60	3.22	0.63	3.34	0.65
					14	2.00	0.50	2.80	0.55	2.93	0.59	2.99	0.61	3.05	0.62	3.17	0.65	3.29	0.66
					16	2.00	0.52	2.76	0.57	2.88	0.61	2.94	0.62	3.00	0.64	3.12	0.66	3.24	0.68
					18	2.00	0.54	2.71	0.59	2.83	0.62	2.89	0.64	2.95	0.65	3.07	0.68	3.19	0.69
					20	2.00	0.56	2.67	0.61	2.79	0.64	2.85	0.66	2.90	0.67	3.02	0.69	3.14	0.70
					21	2.00	0.58	2.64	0.62	2.76	0.65	2.82	0.67	2.88	0.68	3.00	0.70	3.12	0.71
					23	2.00	0.60	2.60	0.64	2.72	0.67	2.78	0.68	2.83	0.70	2.95	0.71	3.07	0.72
					25	2.00	0.62	2.55	0.66	2.67	0.69	2.73	0.70	2.79	0.71	2.91	0.73	3.02	0.74
					27	2.00	0.64	2.51	0.68	2.62	0.71	2.68	0.72	2.74	0.73	2.86	0.75	2.98	0.75
					29	2.00	0.67	2.46	0.70	2.58	0.73	2.64	0.74	2.69	0.75	2.81	0.76	2.93	0.77
					31	2.00	0.69	2.42	0.72	2.53	0.75	2.59	0.76	2.65	0.77	2.76	0.78	2.88	0.78
					33	2.00	0.71	2.37	0.75	2.49	0.77	2.54	0.78	2.60	0.79	2.72	0.80	2.83	0.80
					35	2.00	0.74	2.33	0.77	2.44	0.79	2.50	0.79	2.56	0.81	2.67	0.81	2.78	0.82
					37	2.00	0.76	2.29	0.79	2.40	0.81	2.45	0.82	2.51	0.83	2.62	0.83	2.74	0.83
					39	2.00	0.79	2.24	0.82	2.35	0.84	2.41	0.84	2.46	0.85	2.58	0.85	2.69	0.85
					42	1.98	0.83	2.18	0.85	2.29	0.87	2.34	0.87	2.40	0.88	2.51	0.88	2.62	0.87
					44	1.88	0.85	2.13	0.88	2.24	0.89	2.30	0.90	2.35	0.90	2.46	0.90	2.57	0.89
					46	1.83	0.88	2.09	0.90	2.20	0.91	2.25	0.92	2.30	0.92	2.41	0.92	2.53	0.91

12. Capacity Table

Combination (Capacity Index)			Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, WB)													
						14		16		18		19		20		22		24	
						TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
3500			3500	67%	10	2.80	0.67	4.06	0.74	4.23	0.80	4.31	0.83	4.40	0.86	4.57	0.90	4.74	0.93
					12	2.80	0.70	3.99	0.77	4.16	0.83	4.25	0.86	4.33	0.88	4.50	0.92	4.68	0.95
					14	2.80	0.73	3.93	0.80	4.10	0.86	4.18	0.88	4.26	0.90	4.44	0.94	4.61	0.97
					16	2.80	0.76	3.86	0.82	4.03	0.88	4.11	0.91	4.20	0.93	4.37	0.96	4.54	0.99
					18	2.80	0.79	3.80	0.85	3.96	0.91	4.05	0.93	4.13	0.95	4.30	0.98	4.47	1.00
					20	2.80	0.82	3.73	0.88	3.90	0.94	3.98	0.96	4.07	0.98	4.23	1.01	4.40	1.02
					21	2.80	0.84	3.70	0.90	3.87	0.95	3.95	0.97	4.03	0.99	4.20	1.02	4.37	1.03
					23	2.80	0.87	3.64	0.93	3.80	0.98	3.89	1.00	3.97	1.01	4.13	1.04	4.30	1.05
					25	2.80	0.90	3.58	0.96	3.74	1.00	3.82	1.02	3.90	1.04	4.07	1.06	4.23	1.08
					27	2.80	0.94	3.51	0.99	3.67	1.03	3.76	1.05	3.84	1.07	4.00	1.09	4.17	1.10
					29	2.80	0.97	3.45	1.02	3.61	1.06	3.69	1.08	3.77	1.09	3.93	1.11	4.10	1.12
					31	2.80	1.01	3.39	1.05	3.55	1.09	3.63	1.11	3.71	1.12	3.87	1.14	4.03	1.14
					33	2.80	1.04	3.32	1.09	3.48	1.12	3.56	1.14	3.64	1.15	3.80	1.16	3.97	1.16
					35	2.80	1.08	3.26	1.12	3.42	1.15	3.50	1.15	3.58	1.18	3.74	1.19	3.90	1.19
					37	2.80	1.11	3.20	1.15	3.36	1.18	3.43	1.20	3.51	1.20	3.67	1.21	3.83	1.21
					39	2.80	1.15	3.14	1.19	3.29	1.22	3.37	1.23	3.45	1.23	3.61	1.24	3.77	1.23
					42	2.77	1.20	3.05	1.24	3.20	1.26	3.28	1.27	3.35	1.28	3.51	1.28	3.67	1.27
5000			5000	96%	44	2.63	1.24	2.98	1.27	3.14	1.30	3.21	1.30	3.29	1.31	3.45	1.31	3.60	1.30
					46	2.56	1.28	2.92	1.31	3.07	1.33	3.15	1.34	3.23	1.34	3.38	1.34	3.54	1.32
					10	4.00	0.94	5.79	1.04	6.04	1.13	6.16	1.17	6.28	1.21	6.53	1.27	6.78	1.31
					12	4.00	0.98	5.70	1.08	5.94	1.17	6.07	1.21	6.19	1.24	6.43	1.30	6.68	1.34
					14	4.00	1.02	5.61	1.12	5.85	1.21	5.97	1.24	6.09	1.27	6.34	1.33	6.58	1.36
					16	4.00	1.07	5.52	1.16	5.76	1.24	5.88	1.28	6.00	1.31	6.24	1.36	6.48	1.39
					18	4.00	1.11	5.43	1.20	5.66	1.28	5.78	1.31	5.90	1.34	6.14	1.39	6.39	1.42
					20	4.00	1.16	5.34	1.24	5.57	1.32	5.69	1.35	5.81	1.37	6.05	1.42	6.29	1.44
					21	4.00	1.18	5.29	1.27	5.53	1.34	5.64	1.37	5.76	1.39	6.00	1.43	6.24	1.46
					23	4.00	1.23	5.20	1.31	5.43	1.38	5.55	1.40	5.67	1.43	5.91	1.46	6.14	1.49
					25	4.00	1.27	5.11	1.35	5.34	1.42	5.46	1.44	5.57	1.46	5.81	1.50	6.05	1.52
					27	4.00	1.32	5.02	1.40	5.25	1.46	5.37	1.48	5.48	1.50	5.72	1.53	5.95	1.55
					29	4.00	1.37	4.93	1.44	5.16	1.50	5.27	1.52	5.39	1.54	5.62	1.56	5.86	1.58
					31	4.00	1.42	4.84	1.49	5.07	1.54	5.18	1.56	5.30	1.58	5.53	1.60	5.76	1.61
					33	4.00	1.47	4.75	1.53	4.98	1.58	5.09	1.60	5.20	1.62	5.43	1.64	5.66	1.64
					35	4.00	1.52	4.66	1.58	4.89	1.62	5.00	1.62	5.11	1.66	5.34	1.67	5.57	1.67
					37	4.00	1.57	4.57	1.63	4.79	1.67	4.91	1.68	5.02	1.70	5.25	1.71	5.47	1.70
					39	4.00	1.62	4.48	1.67	4.70	1.71	4.82	1.73	4.93	1.74	5.15	1.75	5.38	1.74
					42	3.95	1.70	4.35	1.75	4.57	1.78	4.68	1.79	4.79	1.80	5.01	1.80	5.24	1.79
					44	3.75	1.75	4.26	1.80	4.48	1.83	4.59	1.84	4.70	1.84	4.92	1.84	5.14	1.83
					46	3.65	1.80	4.18	1.85	4.39	1.87	4.50	1.88	4.61	1.89	4.83	1.88	5.05	1.86

12. Capacity Table

Combination (Capacity Index)			Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, WB)													
						14		16		18		19		20		22		24	
						TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
2000	2000	4000	77%	10	3.53	0.87	4.99	0.89	5.08	0.91	5.14	0.92	5.20	0.94	5.35	0.95	5.52	0.97	
				12	3.53	0.89	4.85	0.91	4.95	0.94	5.01	0.95	5.08	0.96	5.23	0.98	5.41	1.00	
				14	3.53	0.92	4.72	0.94	4.83	0.96	4.89	0.97	4.96	0.98	5.12	1.00	5.31	1.02	
				16	3.53	0.94	4.60	0.96	4.71	0.98	4.78	0.99	4.85	1.00	5.02	1.02	5.21	1.04	
				18	3.53	0.96	4.48	0.98	4.60	1.01	4.67	1.02	4.75	1.03	4.92	1.04	5.12	1.06	
				20	3.53	0.99	4.36	1.01	4.49	1.03	4.57	1.04	4.65	1.05	4.83	1.07	5.03	1.09	
				21	3.53	1.00	4.31	1.02	4.44	1.04	4.52	1.05	4.60	1.06	4.78	1.08	4.99	1.10	
				23	3.53	1.03	4.20	1.05	4.34	1.07	4.42	1.08	4.51	1.09	4.70	1.11	4.91	1.13	
				25	3.53	1.05	4.10	1.07	4.25	1.09	4.33	1.10	4.42	1.11	4.62	1.13	4.84	1.15	
				27	3.53	1.08	4.01	1.10	4.16	1.12	4.25	1.13	4.34	1.14	4.55	1.16	4.78	1.18	
				29	3.53	1.11	3.92	1.13	4.08	1.15	4.17	1.16	4.27	1.17	4.48	1.19	4.72	1.20	
				31	3.53	1.13	3.84	1.15	4.01	1.18	4.10	1.19	4.20	1.19	4.42	1.21	4.66	1.23	
				33	3.53	1.16	3.76	1.18	3.94	1.20	4.03	1.21	4.13	1.22	4.36	1.24	4.61	1.26	
				35	3.53	1.19	3.69	1.21	3.87	1.23	4.00	1.24	4.08	1.25	4.31	1.27	4.57	1.29	
				37	3.53	1.22	3.62	1.24	3.81	1.26	3.91	1.27	4.02	1.28	4.26	1.30	4.53	1.32	
				39	3.53	1.25	3.56	1.27	3.76	1.29	3.86	1.30	3.98	1.31	4.22	1.33	4.49	1.35	
				42	3.53	1.30	3.48	1.32	3.69	1.34	3.80	1.35	3.92	1.36	4.17	1.38	4.46	1.40	
				44	3.53	1.33	3.44	1.35	3.65	1.37	3.76	1.38	3.89	1.39	4.15	1.41	4.44	1.43	
				46	3.53	1.37	3.39	1.39	3.61	1.41	3.73	1.42	3.86	1.43	4.13	1.44	4.42	1.46	
2000	2500	4500	87%	10	4.07	0.99	5.73	1.02	5.84	1.04	5.91	1.05	5.98	1.06	6.15	1.09	6.34	1.11	
				12	4.07	1.02	5.58	1.04	5.69	1.06	5.76	1.08	5.84	1.09	6.02	1.11	6.22	1.13	
				14	4.07	1.04	5.43	1.07	5.55	1.09	5.63	1.10	5.71	1.11	5.89	1.14	6.10	1.16	
				16	4.07	1.07	5.29	1.09	5.42	1.12	5.50	1.13	5.58	1.14	5.77	1.16	5.99	1.18	
				18	4.07	1.09	5.15	1.12	5.29	1.14	5.37	1.15	5.46	1.17	5.66	1.19	5.89	1.21	
				20	4.07	1.12	5.02	1.15	5.17	1.17	5.25	1.18	5.34	1.19	5.55	1.22	5.79	1.24	
				21	4.07	1.14	4.96	1.16	5.11	1.18	5.19	1.20	5.29	1.21	5.50	1.23	5.74	1.25	
				23	4.07	1.17	4.83	1.19	4.99	1.21	5.09	1.23	5.18	1.24	5.40	1.26	5.65	1.28	
				25	4.07	1.20	4.72	1.22	4.89	1.24	4.98	1.25	5.09	1.27	5.31	1.29	5.57	1.31	
				27	4.07	1.23	4.61	1.25	4.79	1.27	4.89	1.28	4.99	1.30	5.23	1.32	5.49	1.34	
				29	4.07	1.26	4.51	1.28	4.69	1.30	4.80	1.32	4.91	1.33	5.15	1.35	5.42	1.37	
				31	4.07	1.29	4.42	1.31	4.61	1.34	4.71	1.35	4.83	1.36	5.08	1.38	5.36	1.40	
				33	4.07	1.32	4.33	1.35	4.53	1.37	4.64	1.38	4.76	1.39	5.01	1.41	5.30	1.43	
				35	4.07	1.36	4.24	1.38	4.45	1.40	4.60	1.41	4.69	1.42	4.96	1.45	5.25	1.47	
				37	4.07	1.39	4.17	1.41	4.38	1.44	4.50	1.45	4.63	1.46	4.90	1.48	5.21	1.50	
				39	4.07	1.42	4.10	1.45	4.32	1.47	4.44	1.48	4.57	1.49	4.86	1.51	5.17	1.53	
				42	4.07	1.48	4.01	1.50	4.24	1.52	4.37	1.54	4.51	1.55	4.80	1.57	5.12	1.59	
				44	4.07	1.52	3.95	1.54	4.20	1.56	4.33	1.57	4.47	1.58	4.77	1.60	5.10	1.62	
				46	4.07	1.55	3.90	1.58	4.16	1.60	4.29	1.61	4.44	1.62	4.75	1.64	5.09	1.66	

12. Capacity Table

Combination (Capacity Index)			Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, WB)													
						14		16		18		19		20		22		24	
						TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
2000	3500	5500	106%	10	4.42	1.07	6.23	1.09	6.35	1.12	6.42	1.13	6.50	1.15	6.68	1.17	6.90	1.19	
				12	4.42	1.09	6.06	1.12	6.19	1.15	6.27	1.16	6.35	1.17	6.54	1.20	6.76	1.22	
				14	4.42	1.12	5.90	1.15	6.04	1.17	6.12	1.19	6.20	1.20	6.40	1.22	6.63	1.25	
				16	4.42	1.15	5.75	1.18	5.89	1.20	5.97	1.22	6.06	1.23	6.27	1.25	6.51	1.28	
				18	4.42	1.18	5.60	1.21	5.75	1.23	5.84	1.24	5.93	1.26	6.15	1.28	6.40	1.30	
				20	4.42	1.21	5.45	1.24	5.62	1.26	5.71	1.27	5.81	1.29	6.03	1.31	6.29	1.33	
				21	4.42	1.23	5.39	1.25	5.55	1.28	5.65	1.29	5.75	1.30	5.98	1.33	6.24	1.35	
				23	4.42	1.26	5.25	1.28	5.43	1.31	5.53	1.32	5.63	1.33	5.87	1.36	6.14	1.38	
				25	4.42	1.29	5.13	1.31	5.31	1.34	5.42	1.35	5.53	1.36	5.77	1.39	6.05	1.41	
				27	4.42	1.32	5.01	1.35	5.20	1.37	5.31	1.39	5.43	1.40	5.68	1.42	5.97	1.44	
				29	4.42	1.36	4.90	1.38	5.10	1.41	5.21	1.42	5.33	1.43	5.60	1.45	5.89	1.48	
				31	4.42	1.39	4.80	1.42	5.01	1.44	5.12	1.45	5.25	1.46	5.52	1.49	5.82	1.51	
				33	4.42	1.42	4.70	1.45	4.92	1.48	5.04	1.49	5.17	1.50	5.45	1.52	5.76	1.55	
				35	4.42	1.46	4.61	1.49	4.84	1.51	5.00	1.52	5.10	1.54	5.39	1.56	5.71	1.58	
				37	4.42	1.50	4.53	1.52	4.76	1.55	4.89	1.56	5.03	1.57	5.33	1.60	5.66	1.62	
				39	4.42	1.54	4.45	1.56	4.70	1.59	4.83	1.60	4.97	1.61	5.28	1.63	5.62	1.65	
42	4.42	1.59	4.35	1.62	4.61	1.64	4.75	1.66	4.90	1.67	5.22	1.69	5.57	1.71					
44	4.42	1.63	4.30	1.66	4.56	1.68	4.70	1.70	4.86	1.71	5.18	1.73	5.55	1.75					
46	4.42	1.67	4.24	1.70	4.52	1.72	4.67	1.74	4.82	1.75	5.16	1.77	5.53	1.79					
2000	5000	7000	135%	10	4.60	1.08	6.48	1.11	6.61	1.14	6.68	1.15	6.76	1.16	6.95	1.19	7.17	1.21	
				12	4.60	1.11	6.31	1.14	6.44	1.16	6.52	1.18	6.60	1.19	6.80	1.21	7.03	1.24	
				14	4.60	1.14	6.14	1.16	6.28	1.19	6.36	1.20	6.45	1.22	6.66	1.24	6.90	1.26	
				16	4.60	1.17	5.97	1.19	6.12	1.22	6.21	1.23	6.31	1.24	6.52	1.27	6.77	1.29	
				18	4.60	1.20	5.82	1.22	5.98	1.25	6.07	1.26	6.17	1.27	6.40	1.30	6.65	1.32	
				20	4.60	1.23	5.67	1.25	5.84	1.28	5.94	1.29	6.04	1.30	6.28	1.33	6.54	1.35	
				21	4.60	1.24	5.60	1.27	5.77	1.29	5.87	1.31	5.98	1.32	6.22	1.34	6.49	1.37	
				23	4.60	1.27	5.47	1.30	5.65	1.33	5.75	1.34	5.86	1.35	6.11	1.37	6.39	1.40	
				25	4.60	1.31	5.34	1.33	5.53	1.36	5.63	1.37	5.75	1.38	6.01	1.41	6.29	1.43	
				27	4.60	1.34	5.21	1.37	5.41	1.39	5.52	1.40	5.64	1.42	5.91	1.44	6.21	1.46	
				29	4.60	1.37	5.10	1.40	5.31	1.42	5.42	1.44	5.55	1.45	5.82	1.47	6.13	1.50	
				31	4.60	1.41	4.99	1.43	5.21	1.46	5.33	1.47	5.46	1.48	5.74	1.51	6.06	1.53	
				33	4.60	1.44	4.89	1.47	5.12	1.50	5.24	1.51	5.38	1.52	5.67	1.54	5.99	1.57	
				35	4.60	1.48	4.80	1.51	5.03	1.53	5.20	1.54	5.30	1.56	5.60	1.58	5.94	1.60	
				37	4.60	1.52	4.71	1.54	4.95	1.57	5.09	1.58	5.23	1.59	5.54	1.62	5.89	1.64	
				39	4.60	1.56	4.63	1.58	4.89	1.61	5.02	1.62	5.17	1.63	5.49	1.65	5.84	1.68	
42	4.60	1.61	4.53	1.64	4.79	1.67	4.94	1.68	5.09	1.69	5.43	1.71	5.79	1.73					
44	4.60	1.66	4.47	1.68	4.74	1.71	4.89	1.72	5.05	1.73	5.39	1.75	5.77	1.77					
46	4.60	1.70	4.41	1.72	4.70	1.75	4.85	1.76	5.02	1.77	5.37	1.79	5.75	1.81					

12. Capacity Table

Combination (Capacity Index)			Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, WB)													
						14		16		18		19		20		22		24	
						TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
2500	2500	5000	96%	10	4.42	1.09	6.23	1.12	6.35	1.14	6.42	1.16	6.50	1.17	6.68	1.19	6.90	1.22	
				12	4.42	1.12	6.06	1.14	6.19	1.17	6.27	1.18	6.35	1.20	6.54	1.22	6.76	1.24	
				14	4.42	1.14	5.90	1.17	6.04	1.20	6.12	1.21	6.20	1.22	6.40	1.25	6.63	1.27	
				16	4.42	1.17	5.75	1.20	5.89	1.23	5.97	1.24	6.06	1.25	6.27	1.28	6.51	1.30	
				18	4.42	1.20	5.60	1.23	5.75	1.26	5.84	1.27	5.93	1.28	6.15	1.31	6.40	1.33	
				20	4.42	1.23	5.45	1.26	5.62	1.29	5.71	1.30	5.81	1.31	6.03	1.34	6.29	1.36	
				21	4.42	1.25	5.39	1.28	5.55	1.30	5.65	1.32	5.75	1.33	5.98	1.35	6.24	1.38	
				23	4.42	1.28	5.25	1.31	5.43	1.33	5.53	1.35	5.63	1.36	5.87	1.38	6.14	1.41	
				25	4.42	1.31	5.13	1.34	5.31	1.37	5.42	1.38	5.53	1.39	5.77	1.42	6.05	1.44	
				27	4.42	1.35	5.01	1.37	5.20	1.40	5.31	1.41	5.43	1.42	5.68	1.45	5.97	1.47	
				29	4.42	1.38	4.90	1.41	5.10	1.43	5.21	1.45	5.33	1.46	5.60	1.48	5.89	1.51	
				31	4.42	1.42	4.80	1.44	5.01	1.47	5.12	1.48	5.25	1.49	5.52	1.52	5.82	1.54	
				33	4.42	1.45	4.70	1.48	4.92	1.50	5.04	1.52	5.17	1.53	5.45	1.55	5.76	1.58	
				35	4.42	1.49	4.61	1.52	4.84	1.54	5.00	1.55	5.10	1.57	5.39	1.59	5.71	1.61	
				37	4.42	1.53	4.53	1.55	4.76	1.58	4.89	1.59	5.03	1.60	5.33	1.63	5.66	1.65	
				39	4.42	1.57	4.45	1.59	4.70	1.62	4.83	1.63	4.97	1.64	5.28	1.66	5.62	1.69	
42	4.42	1.63	4.35	1.65	4.61	1.68	4.75	1.69	4.90	1.70	5.22	1.72	5.57	1.75					
44	4.42	1.67	4.30	1.69	4.56	1.72	4.70	1.73	4.86	1.74	5.18	1.76	5.55	1.79					
46	4.42	1.71	4.24	1.73	4.52	1.76	4.67	1.77	4.82	1.78	5.16	1.80	5.53	1.83					
2500	3500	6000	115%	10	4.42	1.06	6.23	1.09	6.35	1.11	6.42	1.13	6.50	1.14	6.68	1.16	6.90	1.19	
				12	4.42	1.09	6.06	1.11	6.19	1.14	6.27	1.15	6.35	1.16	6.54	1.19	6.76	1.21	
				14	4.42	1.11	5.90	1.14	6.04	1.17	6.12	1.18	6.20	1.19	6.40	1.22	6.63	1.24	
				16	4.42	1.14	5.75	1.17	5.89	1.20	5.97	1.21	6.06	1.22	6.27	1.24	6.51	1.27	
				18	4.42	1.17	5.60	1.20	5.75	1.22	5.84	1.24	5.93	1.25	6.15	1.27	6.40	1.30	
				20	4.42	1.20	5.45	1.23	5.62	1.25	5.71	1.27	5.81	1.28	6.03	1.30	6.29	1.32	
				21	4.42	1.22	5.39	1.24	5.55	1.27	5.65	1.28	5.75	1.29	5.98	1.32	6.24	1.34	
				23	4.42	1.25	5.25	1.27	5.43	1.30	5.53	1.31	5.63	1.32	5.87	1.35	6.14	1.37	
				25	4.42	1.28	5.13	1.31	5.31	1.33	5.42	1.34	5.53	1.36	5.77	1.38	6.05	1.40	
				27	4.42	1.31	5.01	1.34	5.20	1.36	5.31	1.38	5.43	1.39	5.68	1.41	5.97	1.43	
				29	4.42	1.35	4.90	1.37	5.10	1.40	5.21	1.41	5.33	1.42	5.60	1.44	5.89	1.47	
				31	4.42	1.38	4.80	1.41	5.01	1.43	5.12	1.44	5.25	1.46	5.52	1.48	5.82	1.50	
				33	4.42	1.42	4.70	1.44	4.92	1.47	5.04	1.48	5.17	1.49	5.45	1.51	5.76	1.53	
				35	4.42	1.45	4.61	1.48	4.84	1.50	5.00	1.51	5.10	1.53	5.39	1.55	5.71	1.57	
				37	4.42	1.49	4.53	1.51	4.76	1.54	4.89	1.55	5.03	1.56	5.33	1.58	5.66	1.61	
				39	4.42	1.53	4.45	1.55	4.70	1.58	4.83	1.59	4.97	1.60	5.28	1.62	5.62	1.64	
42	4.42	1.58	4.35	1.61	4.61	1.63	4.75	1.64	4.90	1.66	5.22	1.68	5.57	1.70					
44	4.42	1.62	4.30	1.65	4.56	1.67	4.70	1.68	4.86	1.70	5.18	1.72	5.55	1.74					
46	4.42	1.66	4.24	1.69	4.52	1.71	4.67	1.72	4.82	1.74	5.16	1.76	5.53	1.78					

12. Capacity Table

Combination (Capacity Index)			Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, WB)													
						14		16		18		19		20		22		24	
						TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
2500	5000	7500	144%	10	4.60	1.08	6.48	1.11	6.61	1.14	6.68	1.15	6.76	1.16	6.95	1.19	7.17	1.21	
				12	4.60	1.11	6.31	1.14	6.44	1.16	6.52	1.18	6.60	1.19	6.80	1.21	7.03	1.24	
				14	4.60	1.14	6.14	1.16	6.28	1.19	6.36	1.20	6.45	1.22	6.66	1.24	6.90	1.26	
				16	4.60	1.17	5.97	1.19	6.12	1.22	6.21	1.23	6.31	1.24	6.52	1.27	6.77	1.29	
				18	4.60	1.20	5.82	1.22	5.98	1.25	6.07	1.26	6.17	1.27	6.40	1.30	6.65	1.32	
				20	4.60	1.23	5.67	1.25	5.84	1.28	5.94	1.29	6.04	1.30	6.28	1.33	6.54	1.35	
				21	4.60	1.24	5.60	1.27	5.77	1.29	5.87	1.31	5.98	1.32	6.22	1.34	6.49	1.37	
				23	4.60	1.27	5.47	1.30	5.65	1.33	5.75	1.34	5.86	1.35	6.11	1.37	6.39	1.40	
				25	4.60	1.31	5.34	1.33	5.53	1.36	5.63	1.37	5.75	1.38	6.01	1.41	6.29	1.43	
				27	4.60	1.34	5.21	1.37	5.41	1.39	5.52	1.40	5.64	1.42	5.91	1.44	6.21	1.46	
				29	4.60	1.37	5.10	1.40	5.31	1.42	5.42	1.44	5.55	1.45	5.82	1.47	6.13	1.50	
				31	4.60	1.41	4.99	1.43	5.21	1.46	5.33	1.47	5.46	1.48	5.74	1.51	6.06	1.53	
				33	4.60	1.44	4.89	1.47	5.12	1.50	5.24	1.51	5.38	1.52	5.67	1.54	5.99	1.57	
				35	4.60	1.48	4.80	1.51	5.03	1.53	5.20	1.54	5.30	1.56	5.60	1.58	5.94	1.60	
				37	4.60	1.52	4.71	1.54	4.95	1.57	5.09	1.58	5.23	1.59	5.54	1.62	5.89	1.64	
				39	4.60	1.56	4.63	1.58	4.89	1.61	5.02	1.62	5.17	1.63	5.49	1.65	5.84	1.68	
				42	4.60	1.61	4.53	1.64	4.79	1.67	4.94	1.68	5.09	1.69	5.43	1.71	5.79	1.73	
				44	4.60	1.66	4.47	1.68	4.74	1.71	4.89	1.72	5.05	1.73	5.39	1.75	5.77	1.77	
				46	4.60	1.70	4.41	1.72	4.70	1.75	4.85	1.76	5.02	1.77	5.37	1.79	5.75	1.81	
3500	3500	7000	135%	10	4.60	1.08	6.48	1.11	6.61	1.14	6.68	1.15	6.76	1.16	6.95	1.19	7.17	1.21	
				12	4.60	1.11	6.31	1.14	6.44	1.16	6.52	1.18	6.60	1.19	6.80	1.21	7.03	1.24	
				14	4.60	1.14	6.14	1.16	6.28	1.19	6.36	1.20	6.45	1.22	6.66	1.24	6.90	1.26	
				16	4.60	1.17	5.97	1.19	6.12	1.22	6.21	1.23	6.31	1.24	6.52	1.27	6.77	1.29	
				18	4.60	1.20	5.82	1.22	5.98	1.25	6.07	1.26	6.17	1.27	6.40	1.30	6.65	1.32	
				20	4.60	1.23	5.67	1.25	5.84	1.28	5.94	1.29	6.04	1.30	6.28	1.33	6.54	1.35	
				21	4.60	1.24	5.60	1.27	5.77	1.29	5.87	1.31	5.98	1.32	6.22	1.34	6.49	1.37	
				23	4.60	1.27	5.47	1.30	5.65	1.33	5.75	1.34	5.86	1.35	6.11	1.37	6.39	1.40	
				25	4.60	1.31	5.34	1.33	5.53	1.36	5.63	1.37	5.75	1.38	6.01	1.41	6.29	1.43	
				27	4.60	1.34	5.21	1.37	5.41	1.39	5.52	1.40	5.64	1.42	5.91	1.44	6.21	1.46	
				29	4.60	1.37	5.10	1.40	5.31	1.42	5.42	1.44	5.55	1.45	5.82	1.47	6.13	1.50	
				31	4.60	1.41	4.99	1.43	5.21	1.46	5.33	1.47	5.46	1.48	5.74	1.51	6.06	1.53	
				33	4.60	1.44	4.89	1.47	5.12	1.50	5.24	1.51	5.38	1.52	5.67	1.54	5.99	1.57	
				35	4.60	1.48	4.80	1.51	5.03	1.53	5.20	1.54	5.30	1.56	5.60	1.58	5.94	1.60	
				37	4.60	1.52	4.71	1.54	4.95	1.57	5.09	1.58	5.23	1.59	5.54	1.62	5.89	1.64	
				39	4.60	1.56	4.63	1.58	4.89	1.61	5.02	1.62	5.17	1.63	5.49	1.65	5.84	1.68	
				42	4.60	1.61	4.53	1.64	4.79	1.67	4.94	1.68	5.09	1.69	5.43	1.71	5.79	1.73	
				44	4.60	1.66	4.47	1.68	4.74	1.71	4.89	1.72	5.05	1.73	5.39	1.75	5.77	1.77	
				46	4.60	1.70	4.41	1.72	4.70	1.75	4.85	1.76	5.02	1.77	5.37	1.79	5.75	1.81	

12. Capacity Table

Combination (Capacity Index)			Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, WB)													
						14		16		18		19		20		22		24	
						TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
2000	2000	2000	6000	115%	10	4.60	1.05	6.48	1.08	6.61	1.11	6.68	1.12	6.76	1.13	6.95	1.16	7.17	1.18
					12	4.60	1.08	6.31	1.11	6.44	1.13	6.52	1.14	6.60	1.16	6.80	1.18	7.03	1.20
					14	4.60	1.11	6.14	1.13	6.28	1.16	6.36	1.17	6.45	1.18	6.66	1.21	6.90	1.23
					16	4.60	1.14	5.97	1.16	6.12	1.19	6.21	1.20	6.31	1.21	6.52	1.24	6.77	1.26
					18	4.60	1.16	5.82	1.19	5.98	1.22	6.07	1.23	6.17	1.24	6.40	1.26	6.65	1.29
					20	4.60	1.19	5.67	1.22	5.84	1.25	5.94	1.26	6.04	1.27	6.28	1.29	6.54	1.32
					21	4.60	1.21	5.60	1.24	5.77	1.26	5.87	1.27	5.98	1.28	6.22	1.31	6.49	1.33
					23	4.60	1.24	5.47	1.27	5.65	1.29	5.75	1.30	5.86	1.32	6.11	1.34	6.39	1.36
					25	4.60	1.27	5.34	1.30	5.53	1.32	5.63	1.33	5.75	1.35	6.01	1.37	6.29	1.39
					27	4.60	1.30	5.21	1.33	5.41	1.35	5.52	1.37	5.64	1.38	5.91	1.40	6.21	1.42
					29	4.60	1.34	5.10	1.36	5.31	1.39	5.42	1.40	5.55	1.41	5.82	1.43	6.13	1.46
					31	4.60	1.37	4.99	1.40	5.21	1.42	5.33	1.43	5.46	1.45	5.74	1.47	6.06	1.49
					33	4.60	1.41	4.89	1.43	5.12	1.46	5.24	1.47	5.38	1.48	5.67	1.50	5.99	1.52
					35	4.60	1.44	4.80	1.47	5.03	1.49	5.20	1.50	5.30	1.52	5.60	1.54	5.94	1.56
					37	4.60	1.48	4.71	1.50	4.95	1.53	5.09	1.54	5.23	1.55	5.54	1.57	5.89	1.60
					39	4.60	1.52	4.63	1.54	4.89	1.56	5.02	1.58	5.17	1.59	5.49	1.61	5.84	1.63
42	4.60	1.57	4.53	1.60	4.79	1.62	4.94	1.63	5.09	1.65	5.43	1.67	5.79	1.69					
44	4.60	1.61	4.47	1.64	4.74	1.66	4.89	1.67	5.05	1.68	5.39	1.71	5.77	1.73					
46	4.60	1.65	4.41	1.68	4.70	1.70	4.85	1.71	5.02	1.72	5.37	1.75	5.75	1.77					
2000	2000	2500	6500	125%	10	4.60	1.07	6.48	1.10	6.61	1.13	6.68	1.14	6.76	1.15	6.95	1.18	7.17	1.20
					12	4.60	1.10	6.31	1.13	6.44	1.16	6.52	1.17	6.60	1.18	6.80	1.20	7.03	1.23
					14	4.60	1.13	6.14	1.16	6.28	1.18	6.36	1.20	6.45	1.21	6.66	1.23	6.90	1.26
					16	4.60	1.16	5.97	1.19	6.12	1.21	6.21	1.22	6.31	1.24	6.52	1.26	6.77	1.28
					18	4.60	1.19	5.82	1.21	5.98	1.24	6.07	1.25	6.17	1.27	6.40	1.29	6.65	1.31
					20	4.60	1.22	5.67	1.24	5.84	1.27	5.94	1.28	6.04	1.30	6.28	1.32	6.54	1.34
					21	4.60	1.23	5.60	1.26	5.77	1.29	5.87	1.30	5.98	1.31	6.22	1.33	6.49	1.36
					23	4.60	1.26	5.47	1.29	5.65	1.32	5.75	1.33	5.86	1.34	6.11	1.37	6.39	1.39
					25	4.60	1.30	5.34	1.32	5.53	1.35	5.63	1.36	5.75	1.37	6.01	1.40	6.29	1.42
					27	4.60	1.33	5.21	1.36	5.41	1.38	5.52	1.39	5.64	1.41	5.91	1.43	6.21	1.45
					29	4.60	1.36	5.10	1.39	5.31	1.42	5.42	1.43	5.55	1.44	5.82	1.46	6.13	1.49
					31	4.60	1.40	4.99	1.42	5.21	1.45	5.33	1.46	5.46	1.47	5.74	1.50	6.06	1.52
					33	4.60	1.43	4.89	1.46	5.12	1.49	5.24	1.50	5.38	1.51	5.67	1.53	5.99	1.56
					35	4.60	1.47	4.80	1.50	5.03	1.52	5.20	1.53	5.30	1.55	5.60	1.57	5.94	1.59
					37	4.60	1.51	4.71	1.53	4.95	1.56	5.09	1.57	5.23	1.58	5.54	1.61	5.89	1.63
					39	4.60	1.55	4.63	1.57	4.89	1.60	5.02	1.61	5.17	1.62	5.49	1.64	5.84	1.67
42	4.60	1.60	4.53	1.63	4.79	1.65	4.94	1.67	5.09	1.68	5.43	1.70	5.79	1.72					
44	4.60	1.64	4.47	1.67	4.74	1.69	4.89	1.71	5.05	1.72	5.39	1.74	5.77	1.76					
46	4.60	1.69	4.41	1.71	4.70	1.73	4.85	1.75	5.02	1.76	5.37	1.78	5.75	1.80					

12. Capacity Table

Combination (Capacity Index)			Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, WB)													
						14		16		18		19		20		22		24	
						TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
2000	2000	3500	7500	144%	10	4.60	1.00	6.48	1.02	6.61	1.05	6.68	1.06	6.76	1.07	6.95	1.09	7.17	1.12
					12	4.60	1.02	6.31	1.05	6.44	1.07	6.52	1.08	6.60	1.10	6.80	1.12	7.03	1.14
					14	4.60	1.05	6.14	1.07	6.28	1.10	6.36	1.11	6.45	1.12	6.66	1.14	6.90	1.17
					16	4.60	1.07	5.97	1.10	6.12	1.12	6.21	1.14	6.31	1.15	6.52	1.17	6.77	1.19
					18	4.60	1.10	5.82	1.13	5.98	1.15	6.07	1.16	6.17	1.17	6.40	1.20	6.65	1.22
					20	4.60	1.13	5.67	1.16	5.84	1.18	5.94	1.19	6.04	1.20	6.28	1.22	6.54	1.25
					21	4.60	1.14	5.60	1.17	5.77	1.19	5.87	1.20	5.98	1.22	6.22	1.24	6.49	1.26
					23	4.60	1.17	5.47	1.20	5.65	1.22	5.75	1.23	5.86	1.25	6.11	1.27	6.39	1.29
					25	4.60	1.20	5.34	1.23	5.53	1.25	5.63	1.26	5.75	1.27	6.01	1.30	6.29	1.32
					27	4.60	1.23	5.21	1.26	5.41	1.28	5.52	1.29	5.64	1.31	5.91	1.33	6.21	1.35
					29	4.60	1.27	5.10	1.29	5.31	1.31	5.42	1.33	5.55	1.34	5.82	1.36	6.13	1.38
					31	4.60	1.30	4.99	1.32	5.21	1.35	5.33	1.36	5.46	1.37	5.74	1.39	6.06	1.41
					33	4.60	1.33	4.89	1.36	5.12	1.38	5.24	1.39	5.38	1.40	5.67	1.42	5.99	1.44
					35	4.60	1.36	4.80	1.39	5.03	1.41	5.20	1.42	5.30	1.43	5.60	1.46	5.94	1.48
					37	4.60	1.40	4.71	1.42	4.95	1.45	5.09	1.46	5.23	1.47	5.54	1.49	5.89	1.51
					39	4.60	1.43	4.63	1.46	4.89	1.48	5.02	1.49	5.17	1.50	5.49	1.52	5.84	1.55
					42	4.60	1.49	4.53	1.51	4.79	1.54	4.94	1.55	5.09	1.56	5.43	1.58	5.79	1.60
					44	4.60	1.53	4.47	1.55	4.74	1.57	4.89	1.58	5.05	1.59	5.39	1.62	5.77	1.64
					46	4.60	1.56	4.41	1.59	4.70	1.61	4.85	1.62	5.02	1.63	5.37	1.65	5.75	1.67
2000	2500	2500	7000	135%	10	4.60	0.98	6.48	1.00	6.61	1.03	6.68	1.04	6.76	1.05	6.95	1.07	7.17	1.09
					12	4.60	1.00	6.31	1.03	6.44	1.05	6.52	1.06	6.60	1.07	6.80	1.09	7.03	1.12
					14	4.60	1.03	6.14	1.05	6.28	1.07	6.36	1.09	6.45	1.10	6.66	1.12	6.90	1.14
					16	4.60	1.05	5.97	1.08	6.12	1.10	6.21	1.11	6.31	1.12	6.52	1.15	6.77	1.17
					18	4.60	1.08	5.82	1.10	5.98	1.13	6.07	1.14	6.17	1.15	6.40	1.17	6.65	1.19
					20	4.60	1.11	5.67	1.13	5.84	1.15	5.94	1.17	6.04	1.18	6.28	1.20	6.54	1.22
					21	4.60	1.12	5.60	1.14	5.77	1.17	5.87	1.18	5.98	1.19	6.22	1.21	6.49	1.23
					23	4.60	1.15	5.47	1.17	5.65	1.20	5.75	1.21	5.86	1.22	6.11	1.24	6.39	1.26
					25	4.60	1.18	5.34	1.20	5.53	1.23	5.63	1.24	5.75	1.25	6.01	1.27	6.29	1.29
					27	4.60	1.21	5.21	1.23	5.41	1.26	5.52	1.27	5.64	1.28	5.91	1.30	6.21	1.32
					29	4.60	1.24	5.10	1.26	5.31	1.29	5.42	1.30	5.55	1.31	5.82	1.33	6.13	1.35
					31	4.60	1.27	4.99	1.29	5.21	1.32	5.33	1.33	5.46	1.34	5.74	1.36	6.06	1.38
					33	4.60	1.30	4.89	1.33	5.12	1.35	5.24	1.36	5.38	1.37	5.67	1.39	5.99	1.41
					35	4.60	1.34	4.80	1.36	5.03	1.38	5.20	1.39	5.30	1.40	5.60	1.43	5.94	1.45
					37	4.60	1.37	4.71	1.39	4.95	1.42	5.09	1.43	5.23	1.44	5.54	1.46	5.89	1.48
					39	4.60	1.40	4.63	1.43	4.89	1.45	5.02	1.46	5.17	1.47	5.49	1.49	5.84	1.51
					42	4.60	1.46	4.53	1.48	4.79	1.50	4.94	1.51	5.09	1.52	5.43	1.55	5.79	1.57
					44	4.60	1.49	4.47	1.52	4.74	1.54	4.89	1.55	5.05	1.56	5.39	1.58	5.77	1.60
					46	4.60	1.53	4.41	1.55	4.70	1.58	4.85	1.59	5.02	1.60	5.37	1.62	5.75	1.64

12. Capacity Table

Combination (Capacity Index)			Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, WB)													
						14		16		18		19		20		22		24	
						TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
2000	2500	3500	8000	154%	10	5.85	1.00	6.08	1.02	6.31	1.04	6.43	1.05	6.55	1.06	6.79	1.08	7.03	1.10
					12	5.75	1.02	5.98	1.04	6.21	1.07	6.33	1.08	6.45	1.09	6.69	1.11	6.93	1.13
					14	5.64	1.05	5.87	1.07	6.11	1.09	6.23	1.10	6.35	1.11	6.59	1.14	6.83	1.16
					16	5.54	1.08	5.77	1.10	6.01	1.12	6.13	1.13	6.25	1.14	6.49	1.16	6.73	1.19
					18	5.44	1.11	5.67	1.13	5.91	1.15	6.03	1.16	6.15	1.17	6.39	1.19	6.63	1.22
					20	5.34	1.13	5.57	1.16	5.81	1.18	5.93	1.19	6.05	1.20	6.29	1.22	6.54	1.24
					21	5.29	1.15	5.52	1.17	5.76	1.19	5.88	1.20	6.00	1.22	6.24	1.24	6.49	1.26
					23	5.19	1.18	5.42	1.20	5.66	1.22	5.78	1.23	5.90	1.25	6.14	1.27	6.39	1.29
					25	5.09	1.21	5.32	1.23	5.56	1.25	5.68	1.26	5.80	1.28	6.04	1.30	6.29	1.32
					27	4.99	1.24	5.23	1.26	5.46	1.28	5.58	1.30	5.70	1.31	5.95	1.33	6.19	1.35
					29	4.89	1.27	5.13	1.29	5.36	1.32	5.48	1.33	5.60	1.34	5.85	1.36	6.10	1.38
					31	4.79	1.30	5.03	1.32	5.27	1.35	5.39	1.36	5.51	1.37	5.75	1.39	6.00	1.41
					33	4.69	1.33	4.93	1.36	5.17	1.38	5.29	1.39	5.41	1.40	5.65	1.42	5.90	1.45
					35	4.60	1.37	4.83	1.39	5.07	1.41	5.20	1.42	5.31	1.43	5.56	1.46	5.81	1.48
					37	4.50	1.40	4.73	1.42	4.97	1.44	5.09	1.46	5.22	1.47	5.46	1.49	5.71	1.51
					39	4.40	1.43	4.64	1.46	4.88	1.48	5.00	1.49	5.12	1.50	5.36	1.52	5.61	1.55
42	4.25	1.48	4.49	1.51	4.73	1.53	4.85	1.54	4.97	1.55	5.22	1.58	5.47	1.60					
44	4.16	1.52	4.39	1.54	4.63	1.56	4.76	1.58	4.88	1.59	5.13	1.61	5.38	1.64					
46	4.06	1.55	4.30	1.58	4.54	1.60	4.66	1.61	4.78	1.62	5.03	1.65	5.28	1.67					
2500	2500	2500	7500	144%	10	5.85	1.12	6.08	1.15	6.31	1.17	6.43	1.18	6.55	1.19	6.79	1.22	7.03	1.24
					12	5.75	1.15	5.98	1.18	6.21	1.20	6.33	1.21	6.45	1.22	6.69	1.25	6.93	1.27
					14	5.64	1.18	5.87	1.21	6.11	1.23	6.23	1.24	6.35	1.26	6.59	1.28	6.83	1.30
					16	5.54	1.21	5.77	1.24	6.01	1.26	6.13	1.28	6.25	1.29	6.49	1.31	6.73	1.34
					18	5.44	1.25	5.67	1.27	5.91	1.30	6.03	1.31	6.15	1.32	6.39	1.34	6.63	1.37
					20	5.34	1.28	5.57	1.30	5.81	1.33	5.93	1.34	6.05	1.35	6.29	1.38	6.54	1.40
					21	5.29	1.29	5.52	1.32	5.76	1.34	5.88	1.36	6.00	1.37	6.24	1.39	6.49	1.42
					23	5.19	1.33	5.42	1.35	5.66	1.38	5.78	1.39	5.90	1.40	6.14	1.43	6.39	1.45
					25	5.09	1.36	5.32	1.39	5.56	1.41	5.68	1.42	5.80	1.44	6.04	1.46	6.29	1.49
					27	4.99	1.40	5.23	1.42	5.46	1.45	5.58	1.46	5.70	1.47	5.95	1.50	6.19	1.52
					29	4.89	1.43	5.13	1.46	5.36	1.48	5.48	1.49	5.60	1.51	5.85	1.53	6.10	1.56
					31	4.79	1.47	5.03	1.49	5.27	1.52	5.39	1.53	5.51	1.54	5.75	1.57	6.00	1.59
					33	4.69	1.50	4.93	1.53	5.17	1.55	5.29	1.57	5.41	1.58	5.65	1.61	5.90	1.63
					35	4.60	1.54	4.83	1.56	5.07	1.59	5.20	1.60	5.31	1.62	5.56	1.64	5.81	1.67
					37	4.50	1.58	4.73	1.60	4.97	1.63	5.09	1.64	5.22	1.65	5.46	1.68	5.71	1.71
					39	4.40	1.61	4.64	1.64	4.88	1.67	5.00	1.68	5.12	1.69	5.36	1.72	5.61	1.74
42	4.25	1.67	4.49	1.70	4.73	1.72	4.85	1.74	4.97	1.75	5.22	1.78	5.47	1.80					
44	4.16	1.71	4.39	1.74	4.63	1.76	4.76	1.78	4.88	1.79	5.13	1.82	5.38	1.84					
46	4.06	1.75	4.30	1.78	4.54	1.80	4.66	1.82	4.78	1.83	5.03	1.86	5.28	1.88					

12. Capacity Table

Combination (Capacity Index)			Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, WB)													
						14		16		18		19		20		22		24	
						TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
2500	2500	3500	8500	163%	10	5.85	1.12	6.08	1.15	6.31	1.17	6.43	1.18	6.55	1.19	6.79	1.22	7.03	1.24
					12	5.75	1.15	5.98	1.18	6.21	1.20	6.33	1.21	6.45	1.22	6.69	1.25	6.93	1.27
					14	5.64	1.18	5.87	1.21	6.11	1.23	6.23	1.24	6.35	1.26	6.59	1.28	6.83	1.30
					16	5.54	1.21	5.77	1.24	6.01	1.26	6.13	1.28	6.25	1.29	6.49	1.31	6.73	1.34
					18	5.44	1.25	5.67	1.27	5.91	1.30	6.03	1.31	6.15	1.32	6.39	1.34	6.63	1.37
					20	5.34	1.28	5.57	1.30	5.81	1.33	5.93	1.34	6.05	1.35	6.29	1.38	6.54	1.40
					21	5.29	1.29	5.52	1.32	5.76	1.34	5.88	1.36	6.00	1.37	6.24	1.39	6.49	1.42
					23	5.19	1.33	5.42	1.35	5.66	1.38	5.78	1.39	5.90	1.40	6.14	1.43	6.39	1.45
					25	5.09	1.36	5.32	1.39	5.56	1.41	5.68	1.42	5.80	1.44	6.04	1.46	6.29	1.49
					27	4.99	1.40	5.23	1.42	5.46	1.45	5.58	1.46	5.70	1.47	5.95	1.50	6.19	1.52
					29	4.89	1.43	5.13	1.46	5.36	1.48	5.48	1.49	5.60	1.51	5.85	1.53	6.10	1.56
					31	4.79	1.47	5.03	1.49	5.27	1.52	5.39	1.53	5.51	1.54	5.75	1.57	6.00	1.59
					33	4.69	1.50	4.93	1.53	5.17	1.55	5.29	1.57	5.41	1.58	5.65	1.61	5.90	1.63
					35	4.60	1.54	4.83	1.56	5.07	1.59	5.20	1.60	5.31	1.62	5.56	1.64	5.81	1.67
					37	4.50	1.58	4.73	1.60	4.97	1.63	5.09	1.64	5.22	1.65	5.46	1.68	5.71	1.71
					39	4.40	1.61	4.64	1.64	4.88	1.67	5.00	1.68	5.12	1.69	5.36	1.72	5.61	1.74
					42	4.25	1.67	4.49	1.70	4.73	1.72	4.85	1.74	4.97	1.75	5.22	1.78	5.47	1.80
					44	4.16	1.71	4.39	1.74	4.63	1.76	4.76	1.78	4.88	1.79	5.13	1.82	5.38	1.84
					46	4.06	1.75	4.30	1.78	4.54	1.80	4.66	1.82	4.78	1.83	5.03	1.86	5.28	1.88

NOTE

- Cooling capacity is based on 27°CDB / 19°CWB (indoor temperature), 35°CDB (outdoor temperature).
- Heating capacity is based on 20°CDB (indoor temperature), 7°CDB/6°CWB (outdoor temperature).
- The above is the value for connecting with the following indoor units.
 - 2000, 2500, 3500, 5000W class: Wall Mounted A3050 Series [only for AR**MXWSAWKNEU]
- Capacities are based on the following conditions:
 - Corresponding refrigerant piping length : 5m / - Level difference : 0m
- The total ability of connected a indoor unit is up to 7.5kW
- It is impossible to connect the indoor unit for one room only.
- This data is reference data for temperature capacity trend.

12. Capacity Table

11-3. AJ052RCJ3EGEU

Heating

Combination (Capacity Index)			Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, DB)													
						14		16		18		20		21		22		24	
						TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
2000		2000	38%	-15	1.26	0.72	1.22	0.73	1.18	0.74	1.17	0.75	1.15	0.75	1.13	0.76	1.11	0.77	
				-10	1.51	0.76	1.47	0.77	1.43	0.78	1.41	0.79	1.40	0.79	1.37	0.80	1.34	0.81	
				-5	1.76	0.80	1.71	0.81	1.67	0.82	1.66	0.83	1.64	0.83	1.61	0.84	1.58	0.85	
				0	2.01	0.84	1.96	0.85	1.92	0.86	1.90	0.87	1.88	0.87	1.85	0.88	1.82	0.89	
				2	2.11	0.85	2.06	0.86	2.02	0.88	2.00	0.88	1.98	0.89	1.95	0.89	1.92	0.90	
				7	2.31	0.88	2.26	0.89	2.21	0.91	2.20	0.91	2.17	0.92	2.14	0.93	2.11	0.93	
				10	2.51	0.91	2.46	0.92	2.41	0.94	2.39	0.94	2.37	0.95	2.33	0.96	2.30	0.97	
				15	2.76	0.95	2.71	0.96	2.66	0.97	2.64	0.98	2.61	0.99	2.57	1.00	2.54	1.01	
2500		2500	48%	-15	1.89	0.91	1.83	0.93	1.78	0.94	1.75	0.95	1.73	0.95	1.69	0.96	1.66	0.97	
				-10	2.26	0.96	2.20	0.98	2.14	0.99	2.12	1.00	2.09	1.00	2.05	1.01	2.02	1.02	
				-5	2.64	1.01	2.57	1.02	2.51	1.04	2.48	1.04	2.46	1.05	2.41	1.06	2.37	1.07	
				0	3.01	1.06	2.94	1.07	2.88	1.09	2.85	1.09	2.82	1.10	2.77	1.11	2.73	1.12	
				2	3.16	1.08	3.09	1.09	3.03	1.11	3.00	1.11	2.97	1.12	2.92	1.13	2.87	1.14	
				7	3.46	1.11	3.39	1.13	3.32	1.14	3.30	1.15	3.26	1.16	3.21	1.17	3.16	1.18	
				10	3.76	1.15	3.69	1.17	3.62	1.18	3.59	1.19	3.55	1.20	3.50	1.21	3.45	1.22	
				15	4.14	1.20	4.06	1.21	3.99	1.23	3.95	1.24	3.92	1.25	3.86	1.26	3.81	1.27	
3500		3500	67%	-15	2.29	1.07	2.22	1.09	2.15	1.10	2.13	1.11	2.10	1.12	2.05	1.13	2.01	1.14	
				-10	2.74	1.13	2.67	1.15	2.60	1.16	2.57	1.17	2.54	1.17	2.49	1.19	2.44	1.20	
				-5	3.20	1.19	3.12	1.20	3.04	1.22	3.01	1.23	2.98	1.23	2.92	1.25	2.88	1.26	
				0	3.65	1.24	3.57	1.26	3.49	1.28	3.46	1.28	3.42	1.29	3.36	1.30	3.31	1.32	
				2	3.83	1.26	3.75	1.28	3.67	1.30	3.63	1.31	3.60	1.31	3.54	1.33	3.48	1.34	
				7	4.20	1.31	4.11	1.33	4.03	1.34	4.00	1.35	3.95	1.36	3.89	1.37	3.83	1.39	
				10	4.56	1.35	4.47	1.37	4.38	1.39	4.35	1.40	4.31	1.41	4.24	1.42	4.18	1.43	
				15	5.02	1.40	4.92	1.43	4.83	1.44	4.79	1.45	4.75	1.46	4.68	1.48	4.62	1.49	
5000		5000	96%	-15	3.21	1.45	3.11	1.47	3.02	1.49	2.98	1.50	2.94	1.50	2.87	1.52	2.82	1.53	
				-10	3.84	1.52	3.73	1.55	3.64	1.57	3.60	1.57	3.55	1.58	3.48	1.60	3.42	1.61	
				-5	4.48	1.60	4.36	1.62	4.26	1.64	4.22	1.65	4.17	1.66	4.09	1.68	4.03	1.69	
				0	5.11	1.67	4.99	1.70	4.89	1.72	4.84	1.73	4.79	1.74	4.71	1.76	4.63	1.77	
				2	5.37	1.70	5.25	1.73	5.14	1.75	5.09	1.76	5.04	1.77	4.95	1.79	4.88	1.81	
				7	5.88	1.76	5.75	1.79	5.64	1.81	5.60	1.82	5.54	1.83	5.44	1.85	5.36	1.87	
				10	6.39	1.82	6.26	1.85	6.14	1.87	6.08	1.88	6.03	1.89	5.94	1.92	5.85	1.93	
				15	7.03	1.89	6.89	1.92	6.77	1.95	6.71	1.96	6.65	1.97	6.55	1.99	6.46	2.01	
2000	2000	4000	77%	-15	2.52	0.97	2.44	0.98	2.37	1.00	2.34	1.00	2.31	1.01	2.26	1.02	2.21	1.03	
				-10	3.02	1.02	2.93	1.04	2.86	1.05	2.82	1.06	2.79	1.06	2.74	1.07	2.69	1.08	
				-5	3.52	1.07	3.43	1.09	3.35	1.10	3.31	1.11	3.28	1.11	3.22	1.13	3.16	1.14	
				0	4.02	1.12	3.92	1.14	3.84	1.15	3.80	1.16	3.76	1.17	3.70	1.18	3.64	1.19	
				2	4.22	1.14	4.12	1.16	4.04	1.17	4.00	1.18	3.96	1.19	3.89	1.20	3.83	1.21	
				7	4.62	1.18	4.52	1.20	4.43	1.21	4.40	1.22	4.35	1.23	4.28	1.24	4.21	1.25	
				10	5.02	1.22	4.92	1.24	4.82	1.25	4.78	1.26	4.74	1.27	4.66	1.28	4.60	1.30	
				15	5.52	1.27	5.41	1.29	5.32	1.31	5.27	1.31	5.23	1.32	5.15	1.34	5.08	1.35	

12. Capacity Table

Combination (Capacity Index)			Combination (Total)	Combination (%)	Outdoor Temperature (°C, DB)	Indoor Temperature (°C, DB)													
						14		16		18		20		21		22		24	
						TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
2000	2500		4500	87%	-15	2.92	1.12	2.83	1.14	2.75	1.15	2.71	1.16	2.68	1.17	2.62	1.18	2.56	1.19
					-10	3.50	1.18	3.40	1.20	3.31	1.21	3.27	1.22	3.24	1.23	3.17	1.24	3.12	1.25
					-5	4.08	1.24	3.97	1.26	3.88	1.27	3.84	1.28	3.80	1.29	3.73	1.30	3.67	1.31
					0	4.66	1.30	4.55	1.31	4.45	1.33	4.41	1.34	4.36	1.35	4.29	1.36	4.22	1.37
					2	4.89	1.32	4.78	1.34	4.68	1.36	4.63	1.36	4.59	1.37	4.51	1.39	4.44	1.40
					7	5.35	1.36	5.24	1.38	5.13	1.40	5.10	1.41	5.04	1.42	4.96	1.44	4.89	1.45
					10	5.82	1.41	5.70	1.43	5.59	1.45	5.54	1.46	5.49	1.47	5.41	1.48	5.33	1.50
					15	6.40	1.47	6.28	1.49	6.16	1.51	6.11	1.52	6.06	1.53	5.97	1.54	5.88	1.56
2000	3500		5500	106%	-15	3.21	1.22	3.11	1.24	3.02	1.26	2.98	1.27	2.94	1.27	2.87	1.29	2.82	1.30
					-10	3.84	1.29	3.73	1.31	3.64	1.32	3.60	1.33	3.55	1.34	3.48	1.35	3.42	1.36
					-5	4.48	1.35	4.36	1.37	4.26	1.39	4.22	1.40	4.17	1.41	4.09	1.42	4.03	1.43
					0	5.11	1.42	4.99	1.44	4.89	1.46	4.84	1.46	4.79	1.47	4.71	1.49	4.63	1.50
					2	5.37	1.44	5.25	1.46	5.14	1.48	5.09	1.49	5.04	1.50	4.95	1.51	4.88	1.53
					7	5.88	1.49	5.75	1.51	5.64	1.53	5.60	1.54	5.54	1.55	5.44	1.57	5.36	1.58
					10	6.39	1.54	6.26	1.56	6.14	1.58	6.08	1.59	6.03	1.60	5.94	1.62	5.85	1.64
					15	7.03	1.60	6.89	1.63	6.77	1.65	6.71	1.66	6.65	1.67	6.55	1.69	6.46	1.70
2000	5000		7000	135%	-15	3.43	1.32	3.33	1.34	3.23	1.36	3.19	1.36	3.15	1.37	3.08	1.39	3.02	1.40
					-10	4.11	1.39	4.00	1.41	3.90	1.43	3.85	1.44	3.81	1.44	3.73	1.46	3.67	1.47
					-5	4.80	1.46	4.67	1.48	4.57	1.50	4.52	1.51	4.47	1.52	4.39	1.53	4.31	1.54
					0	5.48	1.53	5.35	1.55	5.24	1.57	5.18	1.58	5.13	1.59	5.04	1.60	4.97	1.62
					2	5.75	1.55	5.62	1.58	5.50	1.60	5.45	1.61	5.40	1.62	5.31	1.63	5.23	1.65
					7	6.30	1.61	6.16	1.63	6.04	1.65	6.00	1.66	5.93	1.67	5.83	1.69	5.75	1.71
					10	6.84	1.66	6.70	1.68	6.58	1.71	6.52	1.72	6.46	1.73	6.36	1.75	6.27	1.76
					15	7.53	1.73	7.38	1.75	7.25	1.78	7.19	1.79	7.13	1.80	7.02	1.82	6.92	1.84
2500	2500		5000	96%	-15	3.32	1.27	3.22	1.29	3.12	1.31	3.08	1.32	3.04	1.32	2.97	1.34	2.92	1.35
					-10	3.98	1.34	3.87	1.36	3.77	1.38	3.72	1.38	3.68	1.39	3.61	1.41	3.54	1.42
					-5	4.64	1.40	4.52	1.43	4.41	1.44	4.37	1.45	4.32	1.46	4.24	1.48	4.17	1.49
					0	5.29	1.47	5.17	1.49	5.06	1.51	5.01	1.52	4.96	1.53	4.88	1.55	4.80	1.56
					2	5.56	1.50	5.43	1.52	5.32	1.54	5.27	1.55	5.22	1.56	5.13	1.57	5.05	1.59
					7	6.09	1.55	5.96	1.57	5.84	1.59	5.80	1.60	5.73	1.61	5.64	1.63	5.56	1.64
					10	6.62	1.60	6.48	1.62	6.36	1.65	6.30	1.66	6.25	1.67	6.15	1.68	6.06	1.70
					15	7.28	1.66	7.14	1.69	7.01	1.71	6.95	1.72	6.89	1.73	6.79	1.75	6.69	1.77
2500	3500		6000	115%	-15	3.32	1.27	3.22	1.29	3.12	1.31	3.08	1.32	3.04	1.32	2.97	1.34	2.92	1.35
					-10	3.98	1.34	3.87	1.36	3.77	1.38	3.72	1.38	3.68	1.39	3.61	1.41	3.54	1.42
					-5	4.64	1.40	4.52	1.43	4.41	1.44	4.37	1.45	4.32	1.46	4.24	1.48	4.17	1.49
					0	5.29	1.47	5.17	1.49	5.06	1.51	5.01	1.52	4.96	1.53	4.88	1.55	4.80	1.56
					2	5.56	1.50	5.43	1.52	5.32	1.54	5.27	1.55	5.22	1.56	5.13	1.57	5.05	1.59
					7	6.09	1.55	5.96	1.57	5.84	1.59	5.80	1.60	5.73	1.61	5.64	1.63	5.56	1.64
					10	6.62	1.60	6.48	1.62	6.36	1.65	6.30	1.66	6.25	1.67	6.15	1.68	6.06	1.70
					15	7.28	1.66	7.14	1.69	7.01	1.71	6.95	1.72	6.89	1.73	6.79	1.75	6.69	1.77
2500	5000		7500	144%	-15	3.61	1.38	3.49	1.40	3.39	1.42	3.35	1.43	3.31	1.44	3.23	1.45	3.17	1.46
					-10	4.32	1.46	4.20	1.48	4.09	1.50	4.04	1.51	4.00	1.51	3.92	1.53	3.85	1.54
					-5	5.03	1.53	4.91	1.55	4.79	1.57	4.74	1.58	4.69	1.59	4.61	1.61	4.53	1.62
					0	5.75	1.60	5.62	1.62	5.50	1.64	5.44	1.65	5.39	1.66	5.30	1.68	5.21	1.70
					2	6.04	1.63	5.90	1.65	5.78	1.67	5.72	1.68	5.67	1.69	5.57	1.71	5.49	1.73
					7	6.61	1.68	6.47	1.71	6.34	1.73	6.30	1.74	6.23	1.75	6.12	1.77	6.03	1.79
					10	7.19	1.74	7.04	1.77	6.91	1.79	6.84	1.80	6.79	1.81	6.68	1.83	6.58	1.85
					15	7.91	1.81	7.75	1.84	7.61	1.86	7.55	1.87	7.49	1.88	7.37	1.91	7.27	1.92

12. Capacity Table

Combination (Capacity Index)			Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, DB)													
						14		16		18		20		21		22		24	
						TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
3500	3500	7000	135%	-15		3.38	1.30	3.27	1.32	3.18	1.33	3.14	1.34	3.10	1.35	3.03	1.36	2.97	1.37
				-10		4.05	1.36	3.93	1.38	3.83	1.40	3.79	1.41	3.75	1.42	3.67	1.43	3.60	1.44
				-5		4.72	1.43	4.60	1.45	4.49	1.47	4.44	1.48	4.40	1.49	4.31	1.50	4.24	1.52
				0		5.39	1.50	5.26	1.52	5.15	1.54	5.10	1.55	5.05	1.56	4.96	1.57	4.88	1.59
				2		5.65	1.52	5.53	1.55	5.41	1.57	5.36	1.58	5.31	1.59	5.22	1.60	5.14	1.62
				7		6.19	1.58	6.06	1.60	5.94	1.62	5.90	1.63	5.83	1.64	5.74	1.66	5.65	1.67
				10		6.73	1.63	6.59	1.65	6.47	1.68	6.41	1.69	6.35	1.70	6.25	1.72	6.16	1.73
				15		7.40	1.70	7.26	1.72	7.13	1.74	7.07	1.75	7.01	1.77	6.90	1.78	6.81	1.80
2000	2000	2000	6000	115%	-15	3.32	1.26	3.22	1.28	3.12	1.30	3.08	1.31	3.04	1.31	2.97	1.33	2.92	1.34
					-10	3.98	1.33	3.87	1.35	3.77	1.37	3.72	1.38	3.68	1.38	3.61	1.40	3.54	1.41
					-5	4.64	1.40	4.52	1.42	4.41	1.44	4.37	1.44	4.32	1.45	4.24	1.47	4.17	1.48
					0	5.29	1.46	5.17	1.48	5.06	1.50	5.01	1.51	4.96	1.52	4.88	1.54	4.80	1.55
					2	5.56	1.49	5.43	1.51	5.32	1.53	5.27	1.54	5.22	1.55	5.13	1.56	5.05	1.58
					7	6.09	1.54	5.96	1.56	5.84	1.58	5.80	1.59	5.73	1.60	5.64	1.62	5.56	1.63
					10	6.62	1.59	6.48	1.61	6.36	1.64	6.30	1.65	6.25	1.66	6.15	1.67	6.06	1.69
					15	7.28	1.65	7.14	1.68	7.01	1.70	6.95	1.71	6.89	1.72	6.79	1.74	6.69	1.76
2000	2000	2500	6500	125%	-15	3.38	1.31	3.27	1.33	3.18	1.35	3.14	1.36	3.10	1.36	3.03	1.38	2.97	1.39
					-10	4.05	1.38	3.93	1.40	3.83	1.42	3.79	1.43	3.75	1.44	3.67	1.45	3.60	1.46
					-5	4.72	1.45	4.60	1.47	4.49	1.49	4.44	1.50	4.40	1.51	4.31	1.52	4.24	1.54
					0	5.39	1.52	5.26	1.54	5.15	1.56	5.10	1.57	5.05	1.58	4.96	1.59	4.88	1.61
					2	5.65	1.54	5.53	1.57	5.41	1.59	5.36	1.60	5.31	1.61	5.22	1.62	5.14	1.64
					7	6.19	1.60	6.06	1.62	5.94	1.64	5.90	1.65	5.83	1.66	5.74	1.68	5.65	1.70
					10	6.73	1.65	6.59	1.67	6.47	1.70	6.41	1.71	6.35	1.72	6.25	1.74	6.16	1.75
					15	7.40	1.72	7.26	1.74	7.13	1.77	7.07	1.78	7.01	1.79	6.90	1.81	6.81	1.82
2000	2000	3500	7500	144%	-15	3.61	1.32	3.49	1.34	3.39	1.36	3.35	1.36	3.31	1.37	3.23	1.39	3.17	1.40
					-10	4.32	1.39	4.20	1.41	4.09	1.43	4.04	1.44	4.00	1.44	3.92	1.46	3.85	1.47
					-5	5.03	1.46	4.91	1.48	4.79	1.50	4.74	1.51	4.69	1.52	4.61	1.53	4.53	1.54
					0	5.75	1.53	5.62	1.55	5.50	1.57	5.44	1.58	5.39	1.59	5.30	1.60	5.21	1.62
					2	6.04	1.55	5.90	1.58	5.78	1.60	5.72	1.61	5.67	1.62	5.57	1.63	5.49	1.65
					7	6.61	1.61	6.47	1.63	6.34	1.65	6.30	1.66	6.23	1.67	6.12	1.69	6.03	1.71
					10	7.19	1.66	7.04	1.68	6.91	1.71	6.84	1.72	6.79	1.73	6.68	1.75	6.58	1.76
					15	7.91	1.73	7.75	1.75	7.61	1.78	7.55	1.79	7.49	1.80	7.37	1.82	7.27	1.84
2000	2500	2500	7000	135%	-15	3.43	1.26	3.33	1.28	3.23	1.30	3.19	1.31	3.15	1.31	3.08	1.33	3.02	1.34
					-10	4.11	1.33	4.00	1.35	3.90	1.37	3.85	1.38	3.81	1.38	3.73	1.40	3.67	1.41
					-5	4.80	1.40	4.67	1.42	4.57	1.44	4.52	1.44	4.47	1.45	4.39	1.47	4.31	1.48
					0	5.48	1.46	5.35	1.48	5.24	1.50	5.18	1.51	5.13	1.52	5.04	1.54	4.97	1.55
					2	5.75	1.49	5.62	1.51	5.50	1.53	5.45	1.54	5.40	1.55	5.31	1.56	5.23	1.58
					7	6.30	1.54	6.16	1.56	6.04	1.58	6.00	1.59	5.93	1.60	5.83	1.62	5.75	1.63
					10	6.84	1.59	6.70	1.61	6.58	1.64	6.52	1.65	6.46	1.66	6.36	1.67	6.27	1.69
					15	7.53	1.65	7.38	1.68	7.25	1.70	7.19	1.71	7.13	1.72	7.02	1.74	6.92	1.76
2000	2500	3500	8000	154%	-15	3.61	1.30	3.49	1.32	3.39	1.33	3.35	1.34	3.31	1.35	3.23	1.36	3.17	1.37
					-10	4.32	1.36	4.20	1.38	4.09	1.40	4.04	1.41	4.00	1.42	3.92	1.43	3.85	1.44
					-5	5.03	1.43	4.91	1.45	4.79	1.47	4.74	1.48	4.69	1.49	4.61	1.50	4.53	1.52
					0	5.75	1.50	5.62	1.52	5.50	1.54	5.44	1.55	5.39	1.56	5.30	1.57	5.21	1.59
					2	6.04	1.52	5.90	1.55	5.78	1.57	5.72	1.58	5.67	1.59	5.57	1.60	5.49	1.62
					7	6.61	1.58	6.47	1.60	6.34	1.62	6.30	1.63	6.23	1.64	6.12	1.66	6.03	1.67
					10	7.19	1.63	7.04	1.65	6.91	1.68	6.84	1.69	6.79	1.70	6.68	1.72	6.58	1.73
					15	7.91	1.70	7.75	1.72	7.61	1.74	7.55	1.75	7.49	1.77	7.37	1.78	7.27	1.80

12. Capacity Table

Combination (Capacity Index)			Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, DB)													
						14		16		18		20		21		22		24	
						TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
2500	2500	2500	7500	144%	-15	3.61	1.11	3.49	1.13	3.39	1.14	3.35	1.15	3.31	1.16	3.23	1.17	3.17	1.18
					-10	4.32	1.17	4.20	1.19	4.09	1.20	4.04	1.21	4.00	1.22	3.92	1.23	3.85	1.24
					-5	5.03	1.23	4.91	1.25	4.79	1.26	4.74	1.27	4.69	1.28	4.61	1.29	4.53	1.30
					0	5.75	1.29	5.62	1.31	5.50	1.32	5.44	1.33	5.39	1.34	5.30	1.35	5.21	1.36
					2	6.04	1.31	5.90	1.33	5.78	1.35	5.72	1.35	5.67	1.36	5.57	1.38	5.49	1.39
					7	6.61	1.35	6.47	1.37	6.34	1.39	6.30	1.40	6.23	1.41	6.12	1.43	6.03	1.44
					10	7.19	1.40	7.04	1.42	6.91	1.44	6.84	1.45	6.79	1.46	6.68	1.47	6.58	1.49
					15	7.91	1.46	7.75	1.48	7.61	1.50	7.55	1.51	7.49	1.52	7.37	1.53	7.27	1.55
2500	2500	3500	8500	163%	-15	3.61	1.11	3.49	1.13	3.39	1.14	3.35	1.15	3.31	1.16	3.23	1.17	3.17	1.18
					-10	4.32	1.17	4.20	1.19	4.09	1.20	4.04	1.21	4.00	1.22	3.92	1.23	3.85	1.24
					-5	5.03	1.23	4.91	1.25	4.79	1.26	4.74	1.27	4.69	1.28	4.61	1.29	4.53	1.30
					0	5.75	1.29	5.62	1.31	5.50	1.32	5.44	1.33	5.39	1.34	5.30	1.35	5.21	1.36
					2	6.04	1.31	5.90	1.33	5.78	1.35	5.72	1.35	5.67	1.36	5.57	1.38	5.49	1.39
					7	6.61	1.35	6.47	1.37	6.34	1.39	6.30	1.40	6.23	1.41	6.12	1.43	6.03	1.44
					10	7.19	1.40	7.04	1.42	6.91	1.44	6.84	1.45	6.79	1.46	6.68	1.47	6.58	1.49
					15	7.91	1.46	7.75	1.48	7.61	1.50	7.55	1.51	7.49	1.52	7.37	1.53	7.27	1.55

NOTE

- Cooling capacity is based on 27°CDB / 19°CWB (indoor temperature), 35°CDB (outdoor temperature).
- Heating capacity is based on 20°CDB (indoor temperature), 7°CDB/6°CWB (outdoor temperature).
- The above is the value for connecting with the following indoor units.
 - 2000, 2500, 3500, 5000W class: Wall Mounted A3050 Series [only for AR**MXWSAWKNEU]
- Capacities are based on the following conditions:
 - Corresponding refrigerant piping length : 5m / - Level difference : 0m
- The total ability of connected a indoor unit is up to 7.5kW
- It is impossible to connect the indoor unit for one room only.
- This data is reference data for temperature capacity trend.

12. Capacity Table

11-4. AJ068RCJ3EGEU

Cooling

Combination (Capacity Index)			Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, WB)													
						14		16		18		19		20		22		24	
						TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
2000			2000	29%	10	1.60	0.36	2.32	0.41	2.42	0.44	2.46	0.46	2.51	0.47	2.61	0.49	2.71	0.51
					12	1.60	0.38	2.28	0.42	2.38	0.45	2.43	0.47	2.48	0.48	2.57	0.50	2.67	0.52
					14	1.60	0.40	2.24	0.44	2.34	0.47	2.39	0.48	2.44	0.50	2.53	0.52	2.63	0.53
					16	1.60	0.41	2.21	0.45	2.30	0.48	2.35	0.50	2.40	0.51	2.50	0.53	2.59	0.54
					18	1.60	0.43	2.17	0.47	2.27	0.50	2.31	0.51	2.36	0.52	2.46	0.54	2.55	0.55
					20	1.60	0.45	2.13	0.48	2.23	0.51	2.28	0.52	2.32	0.53	2.42	0.55	2.52	0.56
					21	1.60	0.46	2.12	0.49	2.21	0.52	2.26	0.53	2.30	0.54	2.40	0.56	2.50	0.57
					23	1.60	0.48	2.08	0.51	2.17	0.53	2.22	0.55	2.27	0.56	2.36	0.57	2.46	0.58
					25	1.60	0.49	2.04	0.53	2.14	0.55	2.18	0.56	2.23	0.57	2.32	0.58	2.42	0.59
					27	1.60	0.51	2.01	0.54	2.10	0.57	2.15	0.58	2.19	0.58	2.29	0.60	2.38	0.60
					29	1.60	0.53	1.97	0.56	2.06	0.58	2.11	0.59	2.16	0.60	2.25	0.61	2.34	0.61
					31	1.60	0.55	1.94	0.58	2.03	0.60	2.07	0.61	2.12	0.61	2.21	0.62	2.30	0.62
					33	1.60	0.57	1.90	0.60	1.99	0.61	2.04	0.62	2.08	0.63	2.17	0.64	2.27	0.64
					35	1.60	0.59	1.86	0.61	1.95	0.63	2.00	0.63	2.04	0.64	2.14	0.65	2.23	0.65
					37	1.60	0.61	1.83	0.63	1.92	0.65	1.96	0.65	2.01	0.66	2.10	0.66	2.19	0.66
					39	1.60	0.63	1.79	0.65	1.88	0.67	1.93	0.67	1.97	0.68	2.06	0.68	2.15	0.68
					42	1.58	0.66	1.74	0.68	1.83	0.69	1.87	0.70	1.92	0.70	2.01	0.70	2.10	0.70
					44	1.50	0.68	1.71	0.70	1.79	0.71	1.84	0.71	1.88	0.72	1.97	0.72	2.06	0.71
					46	1.46	0.70	1.67	0.72	1.76	0.73	1.80	0.73	1.84	0.73	1.93	0.73	2.02	0.72
2500			2500	37%	10	2.00	0.46	2.90	0.51	3.02	0.55	3.08	0.57	3.14	0.59	3.26	0.62	3.39	0.64
					12	2.00	0.48	2.85	0.53	2.97	0.57	3.03	0.59	3.09	0.60	3.22	0.63	3.34	0.65
					14	2.00	0.50	2.80	0.55	2.93	0.59	2.99	0.61	3.05	0.62	3.17	0.65	3.29	0.66
					16	2.00	0.52	2.76	0.57	2.88	0.61	2.94	0.62	3.00	0.64	3.12	0.66	3.24	0.68
					18	2.00	0.54	2.71	0.59	2.83	0.62	2.89	0.64	2.95	0.65	3.07	0.68	3.19	0.69
					20	2.00	0.56	2.67	0.61	2.79	0.64	2.85	0.66	2.90	0.67	3.02	0.69	3.14	0.70
					21	2.00	0.58	2.64	0.62	2.76	0.65	2.82	0.67	2.88	0.68	3.00	0.70	3.12	0.71
					23	2.00	0.60	2.60	0.64	2.72	0.67	2.78	0.68	2.83	0.70	2.95	0.71	3.07	0.72
					25	2.00	0.62	2.55	0.66	2.67	0.69	2.73	0.70	2.79	0.71	2.91	0.73	3.02	0.74
					27	2.00	0.64	2.51	0.68	2.62	0.71	2.68	0.72	2.74	0.73	2.86	0.75	2.98	0.75
					29	2.00	0.67	2.46	0.70	2.58	0.73	2.64	0.74	2.69	0.75	2.81	0.76	2.93	0.77
					31	2.00	0.69	2.42	0.72	2.53	0.75	2.59	0.76	2.65	0.77	2.76	0.78	2.88	0.78
					33	2.00	0.71	2.37	0.75	2.49	0.77	2.54	0.78	2.60	0.79	2.72	0.80	2.83	0.80
					35	2.00	0.74	2.33	0.77	2.44	0.79	2.50	0.79	2.56	0.81	2.67	0.81	2.78	0.82
					37	2.00	0.76	2.29	0.79	2.40	0.81	2.45	0.82	2.51	0.83	2.62	0.83	2.74	0.83
					39	2.00	0.79	2.24	0.82	2.35	0.84	2.41	0.84	2.46	0.85	2.58	0.85	2.69	0.85
					42	1.98	0.83	2.18	0.85	2.29	0.87	2.34	0.87	2.40	0.88	2.51	0.88	2.62	0.87
					44	1.88	0.85	2.13	0.88	2.24	0.89	2.30	0.90	2.35	0.90	2.46	0.90	2.57	0.89
					46	1.83	0.88	2.09	0.90	2.20	0.91	2.25	0.92	2.30	0.92	2.41	0.92	2.53	0.91

12. Capacity Table

Combination (Capacity Index)			Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, WB)													
						14		16		18		19		20		22		24	
						TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
3500			3500	51%	10	2.80	0.62	4.06	0.69	4.23	0.75	4.31	0.77	4.40	0.80	4.57	0.84	4.74	0.87
					12	2.80	0.65	3.99	0.71	4.16	0.77	4.25	0.80	4.33	0.82	4.50	0.86	4.68	0.88
					14	2.80	0.68	3.93	0.74	4.10	0.80	4.18	0.82	4.26	0.84	4.44	0.88	4.61	0.90
					16	2.80	0.70	3.86	0.77	4.03	0.82	4.11	0.84	4.20	0.86	4.37	0.90	4.54	0.92
					18	2.80	0.73	3.80	0.79	3.96	0.84	4.05	0.87	4.13	0.89	4.30	0.92	4.47	0.94
					20	2.80	0.76	3.73	0.82	3.90	0.87	3.98	0.89	4.07	0.91	4.23	0.94	4.40	0.95
					21	2.80	0.78	3.70	0.84	3.87	0.88	3.95	0.90	4.03	0.92	4.20	0.95	4.37	0.96
					23	2.80	0.81	3.64	0.86	3.80	0.91	3.89	0.93	3.97	0.94	4.13	0.97	4.30	0.98
					25	2.80	0.84	3.58	0.89	3.74	0.93	3.82	0.95	3.90	0.97	4.07	0.99	4.23	1.00
					27	2.80	0.87	3.51	0.92	3.67	0.96	3.76	0.98	3.84	0.99	4.00	1.01	4.17	1.02
					29	2.80	0.90	3.45	0.95	3.61	0.99	3.69	1.00	3.77	1.02	3.93	1.03	4.10	1.04
					31	2.80	0.94	3.39	0.98	3.55	1.02	3.63	1.03	3.71	1.04	3.87	1.06	4.03	1.06
					33	2.80	0.97	3.32	1.01	3.48	1.04	3.56	1.06	3.64	1.07	3.80	1.08	3.97	1.08
					35	2.80	1.00	3.26	1.04	3.42	1.07	3.50	1.07	3.58	1.09	3.74	1.10	3.90	1.10
					37	2.80	1.03	3.20	1.07	3.36	1.10	3.43	1.11	3.51	1.12	3.67	1.13	3.83	1.13
					39	2.80	1.07	3.14	1.11	3.29	1.13	3.37	1.14	3.45	1.15	3.61	1.15	3.77	1.15
					42	2.77	1.12	3.05	1.15	3.20	1.18	3.28	1.18	3.35	1.19	3.51	1.19	3.67	1.18
					44	2.63	1.16	2.98	1.19	3.14	1.21	3.21	1.21	3.29	1.22	3.45	1.22	3.60	1.21
					46	2.56	1.19	2.92	1.22	3.07	1.24	3.15	1.24	3.23	1.25	3.38	1.24	3.54	1.23
5000			5000	74%	10	4.00	0.94	5.79	1.04	6.04	1.13	6.16	1.17	6.28	1.21	6.53	1.27	6.78	1.31
					12	4.00	0.98	5.70	1.08	5.94	1.17	6.07	1.21	6.19	1.24	6.43	1.30	6.68	1.34
					14	4.00	1.02	5.61	1.12	5.85	1.21	5.97	1.24	6.09	1.27	6.34	1.33	6.58	1.36
					16	4.00	1.07	5.52	1.16	5.76	1.24	5.88	1.28	6.00	1.31	6.24	1.36	6.48	1.39
					18	4.00	1.11	5.43	1.20	5.66	1.28	5.78	1.31	5.90	1.34	6.14	1.39	6.39	1.42
					20	4.00	1.16	5.34	1.24	5.57	1.32	5.69	1.35	5.81	1.37	6.05	1.42	6.29	1.44
					21	4.00	1.18	5.29	1.27	5.53	1.34	5.64	1.37	5.76	1.39	6.00	1.43	6.24	1.46
					23	4.00	1.23	5.20	1.31	5.43	1.38	5.55	1.40	5.67	1.43	5.91	1.46	6.14	1.49
					25	4.00	1.27	5.11	1.35	5.34	1.42	5.46	1.44	5.57	1.46	5.81	1.50	6.05	1.52
					27	4.00	1.32	5.02	1.40	5.25	1.46	5.37	1.48	5.48	1.50	5.72	1.53	5.95	1.55
					29	4.00	1.37	4.93	1.44	5.16	1.50	5.27	1.52	5.39	1.54	5.62	1.56	5.86	1.58
					31	4.00	1.42	4.84	1.49	5.07	1.54	5.18	1.56	5.30	1.58	5.53	1.60	5.76	1.61
					33	4.00	1.47	4.75	1.53	4.98	1.58	5.09	1.60	5.20	1.62	5.43	1.64	5.66	1.64
					35	4.00	1.52	4.66	1.58	4.89	1.62	5.00	1.62	5.11	1.66	5.34	1.67	5.57	1.67
					37	4.00	1.57	4.57	1.63	4.79	1.67	4.91	1.68	5.02	1.70	5.25	1.71	5.47	1.70
					39	4.00	1.62	4.48	1.67	4.70	1.71	4.82	1.73	4.93	1.74	5.15	1.75	5.38	1.74
					42	3.95	1.70	4.35	1.75	4.57	1.78	4.68	1.79	4.79	1.80	5.01	1.80	5.24	1.79
					44	3.75	1.75	4.26	1.80	4.48	1.83	4.59	1.84	4.70	1.84	4.92	1.84	5.14	1.83
					46	3.65	1.80	4.18	1.85	4.39	1.87	4.50	1.88	4.61	1.89	4.83	1.88	5.05	1.86

12. Capacity Table

Combination (Capacity Index)			Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, WB)													
						14		16		18		19		20		22		24	
						TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
2000	2000	4000	59%	10	3.53	0.87	4.99	0.89	5.08	0.91	5.14	0.92	5.20	0.94	5.35	0.95	5.52	0.97	
				12	3.53	0.89	4.85	0.91	4.95	0.94	5.01	0.95	5.08	0.96	5.23	0.98	5.41	1.00	
				14	3.53	0.92	4.72	0.94	4.83	0.96	4.89	0.97	4.96	0.98	5.12	1.00	5.31	1.02	
				16	3.53	0.94	4.60	0.96	4.71	0.98	4.78	0.99	4.85	1.00	5.02	1.02	5.21	1.04	
				18	3.53	0.96	4.48	0.98	4.60	1.01	4.67	1.02	4.75	1.03	4.92	1.04	5.12	1.06	
				20	3.53	0.99	4.36	1.01	4.49	1.03	4.57	1.04	4.65	1.05	4.83	1.07	5.03	1.09	
				21	3.53	1.00	4.31	1.02	4.44	1.04	4.52	1.05	4.60	1.06	4.78	1.08	4.99	1.10	
				23	3.53	1.03	4.20	1.05	4.34	1.07	4.42	1.08	4.51	1.09	4.70	1.11	4.91	1.13	
				25	3.53	1.05	4.10	1.07	4.25	1.09	4.33	1.10	4.42	1.11	4.62	1.13	4.84	1.15	
				27	3.53	1.08	4.01	1.10	4.16	1.12	4.25	1.13	4.34	1.14	4.55	1.16	4.78	1.18	
				29	3.53	1.11	3.92	1.13	4.08	1.15	4.17	1.16	4.27	1.17	4.48	1.19	4.72	1.20	
				31	3.53	1.13	3.84	1.15	4.01	1.18	4.10	1.19	4.20	1.19	4.42	1.21	4.66	1.23	
				33	3.53	1.16	3.76	1.18	3.94	1.20	4.03	1.21	4.13	1.22	4.36	1.24	4.61	1.26	
				35	3.53	1.19	3.69	1.21	3.87	1.23	4.00	1.24	4.08	1.25	4.31	1.27	4.57	1.29	
				37	3.53	1.22	3.62	1.24	3.81	1.26	3.91	1.27	4.02	1.28	4.26	1.30	4.53	1.32	
				39	3.53	1.25	3.56	1.27	3.76	1.29	3.86	1.30	3.98	1.31	4.22	1.33	4.49	1.35	
42	3.53	1.30	3.48	1.32	3.69	1.34	3.80	1.35	3.92	1.36	4.17	1.38	4.46	1.40					
44	3.53	1.33	3.44	1.35	3.65	1.37	3.76	1.38	3.89	1.39	4.15	1.41	4.44	1.43					
46	3.53	1.37	3.39	1.39	3.61	1.41	3.73	1.42	3.86	1.43	4.13	1.44	4.42	1.46					
2000	2500	4500	66%	10	3.98	0.99	5.61	1.02	5.72	1.04	5.78	1.05	5.85	1.06	6.01	1.09	6.21	1.11	
				12	3.98	1.02	5.46	1.04	5.57	1.06	5.64	1.08	5.71	1.09	5.89	1.11	6.09	1.13	
				14	3.98	1.04	5.31	1.07	5.43	1.09	5.50	1.10	5.58	1.11	5.76	1.14	5.97	1.16	
				16	3.98	1.07	5.17	1.09	5.30	1.12	5.38	1.13	5.46	1.14	5.65	1.16	5.86	1.18	
				18	3.98	1.09	5.04	1.12	5.17	1.14	5.25	1.15	5.34	1.17	5.53	1.19	5.76	1.21	
				20	3.98	1.12	4.91	1.15	5.05	1.17	5.14	1.18	5.23	1.19	5.43	1.22	5.66	1.24	
				21	3.98	1.14	4.85	1.16	5.00	1.18	5.08	1.20	5.17	1.21	5.38	1.23	5.62	1.25	
				23	3.98	1.17	4.73	1.19	4.89	1.21	4.98	1.23	5.07	1.24	5.29	1.26	5.53	1.28	
				25	3.98	1.20	4.62	1.22	4.78	1.24	4.87	1.25	4.98	1.27	5.20	1.29	5.45	1.31	
				27	3.98	1.23	4.51	1.25	4.68	1.27	4.78	1.28	4.88	1.30	5.11	1.32	5.37	1.34	
				29	3.98	1.26	4.41	1.28	4.59	1.30	4.69	1.32	4.80	1.33	5.04	1.35	5.30	1.37	
				31	3.98	1.29	4.32	1.31	4.51	1.34	4.61	1.35	4.72	1.36	4.97	1.38	5.24	1.40	
				33	3.98	1.32	4.23	1.35	4.43	1.37	4.54	1.38	4.65	1.39	4.90	1.41	5.19	1.43	
				35	3.98	1.36	4.15	1.38	4.35	1.40	4.50	1.41	4.59	1.42	4.85	1.45	5.14	1.47	
				37	3.98	1.39	4.08	1.41	4.29	1.44	4.40	1.45	4.53	1.46	4.80	1.48	5.09	1.50	
				39	3.98	1.42	4.01	1.45	4.23	1.47	4.35	1.48	4.48	1.49	4.75	1.51	5.06	1.53	
42	3.98	1.48	3.92	1.50	4.15	1.52	4.27	1.54	4.41	1.55	4.70	1.57	5.01	1.59					
44	3.98	1.52	3.87	1.54	4.10	1.56	4.23	1.57	4.37	1.58	4.67	1.60	4.99	1.62					
46	3.98	1.55	3.82	1.58	4.07	1.60	4.20	1.61	4.34	1.62	4.64	1.64	4.98	1.66					

12. Capacity Table

Combination (Capacity Index)			Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, WB)													
						14		16		18		19		20		22		24	
						TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
2000	3500	5500	81%	10	4.86	1.29	6.86	1.32	6.99	1.35	7.06	1.36	7.15	1.38	7.35	1.41	7.59	1.44	
				12	4.86	1.32	6.67	1.35	6.81	1.38	6.89	1.40	6.98	1.41	7.19	1.44	7.44	1.47	
				14	4.86	1.35	6.49	1.38	6.64	1.41	6.73	1.43	6.82	1.44	7.04	1.47	7.30	1.50	
				16	4.86	1.39	6.32	1.42	6.48	1.45	6.57	1.46	6.67	1.48	6.90	1.51	7.16	1.54	
				18	4.86	1.42	6.16	1.45	6.32	1.48	6.42	1.50	6.53	1.51	6.76	1.54	7.04	1.57	
				20	4.86	1.46	6.00	1.49	6.18	1.52	6.28	1.53	6.39	1.55	6.64	1.58	6.92	1.61	
				21	4.86	1.48	5.92	1.51	6.11	1.54	6.21	1.55	6.32	1.57	6.58	1.60	6.86	1.62	
				23	4.86	1.51	5.78	1.54	5.97	1.58	6.08	1.59	6.20	1.60	6.46	1.63	6.76	1.66	
				25	4.86	1.55	5.64	1.58	5.84	1.61	5.96	1.63	6.08	1.64	6.35	1.67	6.66	1.70	
				27	4.86	1.59	5.51	1.62	5.72	1.65	5.84	1.67	5.97	1.68	6.25	1.71	6.57	1.74	
				29	4.86	1.63	5.39	1.66	5.61	1.69	5.74	1.71	5.87	1.72	6.16	1.75	6.48	1.78	
				31	4.86	1.67	5.28	1.70	5.51	1.73	5.64	1.75	5.77	1.76	6.07	1.79	6.41	1.82	
				33	4.86	1.72	5.17	1.75	5.41	1.78	5.54	1.79	5.69	1.81	5.99	1.83	6.34	1.86	
				35	4.86	1.76	5.07	1.79	5.32	1.82	5.50	1.83	5.61	1.85	5.92	1.88	6.28	1.90	
				37	4.86	1.80	4.98	1.83	5.24	1.86	5.38	1.88	5.53	1.89	5.86	1.92	6.23	1.95	
				39	4.86	1.85	4.90	1.88	5.17	1.91	5.31	1.92	5.47	1.94	5.81	1.97	6.18	1.99	
				42	4.86	1.92	4.79	1.95	5.07	1.98	5.22	1.99	5.39	2.01	5.74	2.03	6.13	2.06	
				44	4.86	1.97	4.72	2.00	5.02	2.03	5.17	2.04	5.34	2.05	5.70	2.08	6.10	2.11	
				46	4.86	2.02	4.67	2.05	4.97	2.08	5.13	2.09	5.30	2.10	5.68	2.13	6.08	2.16	
2000	5000	7000	103%	10	5.74	1.41	8.10	1.44	8.26	1.47	8.35	1.49	8.45	1.51	8.69	1.54	8.97	1.57	
				12	5.74	1.44	7.88	1.48	8.05	1.51	8.15	1.53	8.25	1.54	8.50	1.57	8.79	1.61	
				14	5.74	1.48	7.67	1.51	7.85	1.55	7.95	1.56	8.06	1.58	8.32	1.61	8.62	1.64	
				16	5.74	1.51	7.47	1.55	7.66	1.58	7.76	1.60	7.88	1.62	8.15	1.65	8.47	1.68	
				18	5.74	1.55	7.28	1.59	7.47	1.62	7.59	1.64	7.71	1.65	7.99	1.69	8.32	1.72	
				20	5.74	1.59	7.09	1.63	7.30	1.66	7.42	1.68	7.55	1.69	7.84	1.72	8.18	1.75	
				21	5.74	1.61	7.00	1.65	7.22	1.68	7.34	1.70	7.47	1.71	7.77	1.74	8.11	1.77	
				23	5.74	1.65	6.83	1.69	7.06	1.72	7.19	1.74	7.33	1.75	7.63	1.78	7.99	1.81	
				25	5.74	1.70	6.67	1.73	6.91	1.76	7.04	1.78	7.19	1.80	7.51	1.83	7.87	1.86	
				27	5.74	1.74	6.52	1.77	6.77	1.81	6.91	1.82	7.06	1.84	7.39	1.87	7.76	1.90	
				29	5.74	1.78	6.37	1.82	6.63	1.85	6.78	1.87	6.93	1.88	7.28	1.91	7.66	1.94	
				31	5.74	1.83	6.24	1.86	6.51	1.90	6.66	1.91	6.82	1.93	7.18	1.96	7.57	1.99	
				33	5.74	1.87	6.11	1.91	6.40	1.94	6.55	1.96	6.72	1.97	7.08	2.00	7.49	2.03	
				35	5.74	1.92	6.00	1.96	6.29	1.99	6.50	2.00	6.63	2.02	7.00	2.05	7.42	2.08	
				37	5.74	1.97	5.89	2.00	6.19	2.04	6.36	2.05	6.54	2.07	6.93	2.10	7.36	2.13	
				39	5.74	2.02	5.79	2.05	6.11	2.09	6.28	2.10	6.46	2.12	6.86	2.15	7.30	2.18	
				42	5.74	2.10	5.66	2.13	5.99	2.16	6.17	2.18	6.37	2.19	6.78	2.22	7.24	2.25	
				44	5.74	2.15	5.58	2.18	5.93	2.21	6.12	2.23	6.31	2.25	6.74	2.28	7.21	2.30	
				46	5.74	2.20	5.52	2.24	5.87	2.27	6.07	2.28	6.27	2.30	6.71	2.33	7.19	2.36	

12. Capacity Table

Combination (Capacity Index)			Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, WB)													
						14		16		18		19		20		22		24	
						TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
2500	2500	5000	74%	10	4.42	1.17	6.23	1.20	6.35	1.22	6.42	1.24	6.50	1.25	6.68	1.28	6.90	1.30	
				12	4.42	1.20	6.06	1.22	6.19	1.25	6.27	1.27	6.35	1.28	6.54	1.31	6.76	1.33	
				14	4.42	1.23	5.90	1.25	6.04	1.28	6.12	1.30	6.20	1.31	6.40	1.34	6.63	1.36	
				16	4.42	1.26	5.75	1.29	5.89	1.31	5.97	1.33	6.06	1.34	6.27	1.37	6.51	1.39	
				18	4.42	1.29	5.60	1.32	5.75	1.35	5.84	1.36	5.93	1.37	6.15	1.40	6.40	1.42	
				20	4.42	1.32	5.45	1.35	5.62	1.38	5.71	1.39	5.81	1.41	6.03	1.43	6.29	1.46	
				21	4.42	1.34	5.39	1.37	5.55	1.39	5.65	1.41	5.75	1.42	5.98	1.45	6.24	1.47	
				23	4.42	1.37	5.25	1.40	5.43	1.43	5.53	1.44	5.63	1.46	5.87	1.48	6.14	1.51	
				25	4.42	1.41	5.13	1.44	5.31	1.46	5.42	1.48	5.53	1.49	5.77	1.52	6.05	1.54	
				27	4.42	1.44	5.01	1.47	5.20	1.50	5.31	1.51	5.43	1.53	5.68	1.55	5.97	1.58	
				29	4.42	1.48	4.90	1.51	5.10	1.54	5.21	1.55	5.33	1.56	5.60	1.59	5.89	1.61	
				31	4.42	1.52	4.80	1.55	5.01	1.57	5.12	1.59	5.25	1.60	5.52	1.63	5.82	1.65	
				33	4.42	1.56	4.70	1.58	4.92	1.61	5.04	1.62	5.17	1.64	5.45	1.66	5.76	1.69	
				35	4.42	1.60	4.61	1.62	4.84	1.65	5.00	1.66	5.10	1.68	5.39	1.70	5.71	1.73	
				37	4.42	1.64	4.53	1.66	4.76	1.69	4.89	1.70	5.03	1.72	5.33	1.74	5.66	1.77	
				39	4.42	1.68	4.45	1.71	4.70	1.73	4.83	1.74	4.97	1.76	5.28	1.78	5.62	1.81	
				42	4.42	1.74	4.35	1.77	4.61	1.80	4.75	1.81	4.90	1.82	5.22	1.85	5.57	1.87	
				44	4.42	1.78	4.30	1.81	4.56	1.84	4.70	1.85	4.86	1.86	5.18	1.89	5.55	1.91	
				46	4.42	1.83	4.24	1.86	4.52	1.88	4.67	1.90	4.82	1.91	5.16	1.93	5.53	1.96	
2500	3000	6000	88%	10	5.30	1.39	7.48	1.43	7.62	1.46	7.71	1.48	7.80	1.49	8.02	1.52	8.28	1.56	
				12	5.30	1.43	7.28	1.46	7.43	1.49	7.52	1.51	7.62	1.53	7.85	1.56	8.11	1.59	
				14	5.30	1.46	7.08	1.50	7.24	1.53	7.34	1.55	7.44	1.56	7.68	1.59	7.96	1.62	
				16	5.30	1.50	6.89	1.53	7.07	1.57	7.17	1.58	7.28	1.60	7.53	1.63	7.81	1.66	
				18	5.30	1.54	6.72	1.57	6.90	1.61	7.00	1.62	7.12	1.64	7.38	1.67	7.68	1.70	
				20	5.30	1.58	6.55	1.61	6.74	1.64	6.85	1.66	6.97	1.68	7.24	1.71	7.55	1.74	
				21	5.30	1.60	6.46	1.63	6.66	1.66	6.78	1.68	6.90	1.70	7.17	1.73	7.49	1.76	
				23	5.30	1.64	6.31	1.67	6.51	1.70	6.63	1.72	6.76	1.74	7.05	1.77	7.37	1.80	
				25	5.30	1.68	6.16	1.71	6.38	1.75	6.50	1.76	6.63	1.78	6.93	1.81	7.26	1.84	
				27	5.30	1.72	6.02	1.76	6.25	1.79	6.37	1.80	6.51	1.82	6.82	1.85	7.16	1.88	
				29	5.30	1.77	5.88	1.80	6.12	1.83	6.26	1.85	6.40	1.86	6.72	1.89	7.07	1.92	
				31	5.30	1.81	5.76	1.84	6.01	1.88	6.15	1.89	6.30	1.91	6.62	1.94	6.99	1.97	
				33	5.30	1.86	5.64	1.89	5.90	1.92	6.05	1.94	6.20	1.95	6.54	1.98	6.92	2.01	
				35	5.30	1.90	5.54	1.94	5.81	1.97	6.00	1.98	6.12	2.00	6.46	2.03	6.85	2.06	
				37	5.30	1.95	5.44	1.98	5.72	2.02	5.87	2.03	6.04	2.05	6.39	2.08	6.79	2.11	
				39	5.30	2.00	5.34	2.03	5.64	2.07	5.80	2.08	5.97	2.10	6.34	2.13	6.74	2.15	
				42	5.30	2.08	5.22	2.11	5.53	2.14	5.70	2.16	5.88	2.17	6.26	2.20	6.68	2.23	
				44	5.30	2.13	5.15	2.16	5.47	2.19	5.64	2.21	5.83	2.22	6.22	2.25	6.65	2.28	
				46	5.30	2.18	5.09	2.21	5.42	2.25	5.60	2.26	5.79	2.28	6.19	2.30	6.63	2.33	

12. Capacity Table

Combination (Capacity Index)			Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, WB)													
						14		16		18		19		20		22		24	
						TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
2500	5000		7500	110%	10	6.01	1.47	8.48	1.51	8.64	1.54	8.73	1.56	8.84	1.58	9.09	1.61	9.38	1.64
					12	6.01	1.51	8.25	1.54	8.42	1.58	8.52	1.60	8.63	1.61	8.89	1.65	9.20	1.68
					14	6.01	1.54	8.03	1.58	8.21	1.62	8.32	1.63	8.44	1.65	8.71	1.68	9.02	1.72
					16	6.01	1.58	7.81	1.62	8.01	1.65	8.12	1.67	8.25	1.69	8.53	1.72	8.86	1.75
					18	6.01	1.62	7.61	1.66	7.82	1.69	7.94	1.71	8.07	1.73	8.36	1.76	8.70	1.79
					20	6.01	1.66	7.42	1.70	7.64	1.74	7.76	1.75	7.90	1.77	8.21	1.80	8.56	1.83
					21	6.01	1.68	7.33	1.72	7.55	1.76	7.68	1.77	7.82	1.79	8.13	1.82	8.49	1.85
					23	6.01	1.73	7.15	1.76	7.38	1.80	7.52	1.82	7.66	1.83	7.99	1.87	8.35	1.90
					25	6.01	1.77	6.98	1.81	7.23	1.84	7.37	1.86	7.52	1.88	7.85	1.91	8.23	1.94
					27	6.01	1.82	6.82	1.85	7.08	1.89	7.22	1.90	7.38	1.92	7.73	1.95	8.12	1.98
					29	6.01	1.86	6.67	1.90	6.94	1.93	7.09	1.95	7.25	1.97	7.61	2.00	8.02	2.03
					31	6.01	1.91	6.53	1.95	6.81	1.98	6.97	2.00	7.14	2.01	7.51	2.05	7.92	2.08
					33	6.01	1.96	6.40	1.99	6.69	2.03	6.85	2.05	7.03	2.06	7.41	2.09	7.84	2.12
					35	6.01	2.01	6.27	2.04	6.58	2.08	6.80	2.09	6.93	2.11	7.32	2.14	7.76	2.17
					37	6.01	2.06	6.16	2.09	6.48	2.13	6.66	2.15	6.84	2.16	7.25	2.19	7.70	2.22
					39	6.01	2.11	6.06	2.15	6.39	2.18	6.57	2.20	6.76	2.21	7.18	2.24	7.64	2.27
					42	6.01	2.19	5.92	2.23	6.27	2.26	6.46	2.28	6.66	2.29	7.10	2.32	7.57	2.35
					44	6.01	2.25	5.84	2.28	6.20	2.31	6.40	2.33	6.60	2.35	7.05	2.38	7.54	2.41
					46	6.01	2.30	5.77	2.34	6.14	2.37	6.35	2.39	6.56	2.40	7.02	2.43	7.52	2.46
3500	3500		7000	103%	10	5.74	1.41	8.10	1.45	8.26	1.48	8.35	1.50	8.45	1.52	8.69	1.55	8.97	1.58
					12	5.74	1.45	7.88	1.48	8.05	1.52	8.15	1.53	8.25	1.55	8.50	1.58	8.79	1.61
					14	5.74	1.48	7.67	1.52	7.85	1.55	7.95	1.57	8.06	1.59	8.32	1.62	8.62	1.65
					16	5.74	1.52	7.47	1.56	7.66	1.59	7.76	1.61	7.88	1.62	8.15	1.66	8.47	1.69
					18	5.74	1.56	7.28	1.60	7.47	1.63	7.59	1.65	7.71	1.66	7.99	1.69	8.32	1.72
					20	5.74	1.60	7.09	1.64	7.30	1.67	7.42	1.69	7.55	1.70	7.84	1.73	8.18	1.76
					21	5.74	1.62	7.00	1.66	7.22	1.69	7.34	1.71	7.47	1.72	7.77	1.75	8.11	1.78
					23	5.74	1.66	6.83	1.70	7.06	1.73	7.19	1.75	7.33	1.76	7.63	1.79	7.99	1.82
					25	5.74	1.70	6.67	1.74	6.91	1.77	7.04	1.79	7.19	1.80	7.51	1.84	7.87	1.87
					27	5.74	1.75	6.52	1.78	6.77	1.82	6.91	1.83	7.06	1.85	7.39	1.88	7.76	1.91
					29	5.74	1.79	6.37	1.83	6.63	1.86	6.78	1.88	6.93	1.89	7.28	1.92	7.66	1.95
					31	5.74	1.84	6.24	1.87	6.51	1.91	6.66	1.92	6.82	1.94	7.18	1.97	7.57	2.00
					33	5.74	1.88	6.11	1.92	6.40	1.95	6.55	1.97	6.72	1.98	7.08	2.01	7.49	2.04
					35	5.74	1.93	6.00	1.97	6.29	2.00	6.50	2.01	6.63	2.03	7.00	2.06	7.42	2.09
					37	5.74	1.98	5.89	2.01	6.19	2.05	6.36	2.06	6.54	2.08	6.93	2.11	7.36	2.14
					39	5.74	2.03	5.79	2.06	6.11	2.10	6.28	2.11	6.46	2.13	6.86	2.16	7.30	2.19
					42	5.74	2.11	5.66	2.14	5.99	2.17	6.17	2.19	6.37	2.20	6.78	2.23	7.24	2.26
					44	5.74	2.16	5.58	2.19	5.93	2.23	6.12	2.24	6.31	2.26	6.74	2.29	7.21	2.32
					46	5.74	2.21	5.52	2.25	5.87	2.28	6.07	2.29	6.27	2.31	6.71	2.34	7.19	2.37

12. Capacity Table

Combination (Capacity Index)			Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, WB)													
						14		16		18		19		20		22		24	
						TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
3500	5000	8500	125%	10	6.01	1.48	8.48	1.51	8.64	1.55	8.73	1.57	8.84	1.58	9.09	1.62	9.38	1.65	
				12	6.01	1.51	8.25	1.55	8.42	1.59	8.52	1.60	8.63	1.62	8.89	1.65	9.20	1.69	
				14	6.01	1.55	8.03	1.59	8.21	1.62	8.32	1.64	8.44	1.66	8.71	1.69	9.02	1.72	
				16	6.01	1.59	7.81	1.63	8.01	1.66	8.12	1.68	8.25	1.70	8.53	1.73	8.86	1.76	
				18	6.01	1.63	7.61	1.67	7.82	1.70	7.94	1.72	8.07	1.74	8.36	1.77	8.70	1.80	
				20	6.01	1.67	7.42	1.71	7.64	1.74	7.76	1.76	7.90	1.78	8.21	1.81	8.56	1.84	
				21	6.01	1.69	7.33	1.73	7.55	1.76	7.68	1.78	7.82	1.80	8.13	1.83	8.49	1.86	
				23	6.01	1.74	7.15	1.77	7.38	1.81	7.52	1.82	7.66	1.84	7.99	1.87	8.35	1.91	
				25	6.01	1.78	6.98	1.82	7.23	1.85	7.37	1.87	7.52	1.89	7.85	1.92	8.23	1.95	
				27	6.01	1.83	6.82	1.86	7.08	1.90	7.22	1.91	7.38	1.93	7.73	1.96	8.12	1.99	
				29	6.01	1.87	6.67	1.91	6.94	1.94	7.09	1.96	7.25	1.98	7.61	2.01	8.02	2.04	
				31	6.01	1.92	6.53	1.96	6.81	1.99	6.97	2.01	7.14	2.02	7.51	2.06	7.92	2.09	
				33	6.01	1.97	6.40	2.00	6.69	2.04	6.85	2.06	7.03	2.07	7.41	2.10	7.84	2.13	
				35	6.01	2.02	6.27	2.05	6.58	2.09	6.80	2.10	6.93	2.12	7.32	2.15	7.76	2.18	
				37	6.01	2.07	6.16	2.10	6.48	2.14	6.66	2.16	6.84	2.17	7.25	2.20	7.70	2.23	
				39	6.01	2.12	6.06	2.16	6.39	2.19	6.57	2.21	6.76	2.22	7.18	2.26	7.64	2.29	
5000	5000	10000	147%	42	6.01	2.20	5.92	2.24	6.27	2.27	6.46	2.29	6.66	2.30	7.10	2.33	7.57	2.36	
				44	6.01	2.26	5.84	2.29	6.20	2.33	6.40	2.34	6.60	2.36	7.05	2.39	7.54	2.42	
				46	6.01	2.31	5.77	2.35	6.14	2.38	6.35	2.40	6.56	2.41	7.02	2.44	7.52	2.47	
				10	7.65	1.45	7.95	1.48	8.25	1.51	8.41	1.52	8.56	1.54	8.87	1.57	9.19	1.60	
				12	7.51	1.48	7.81	1.52	8.12	1.55	8.27	1.56	8.43	1.58	8.74	1.61	9.06	1.64	
				14	7.38	1.52	7.68	1.55	7.99	1.59	8.14	1.60	8.30	1.62	8.61	1.65	8.93	1.68	
				16	7.25	1.56	7.55	1.60	7.86	1.63	8.01	1.64	8.17	1.66	8.48	1.69	8.80	1.72	
				18	7.12	1.60	7.42	1.64	7.73	1.67	7.88	1.68	8.04	1.70	8.35	1.73	8.68	1.76	
				20	6.99	1.65	7.29	1.68	7.60	1.71	7.75	1.73	7.91	1.74	8.23	1.77	8.55	1.81	
				21	6.92	1.67	7.22	1.70	7.53	1.73	7.69	1.75	7.84	1.76	8.16	1.79	8.48	1.83	
				23	6.79	1.71	7.09	1.74	7.40	1.77	7.56	1.79	7.71	1.81	8.03	1.84	8.35	1.87	
				25	6.66	1.75	6.96	1.79	7.27	1.82	7.43	1.83	7.59	1.85	7.90	1.88	8.23	1.92	
				27	6.53	1.80	6.83	1.83	7.14	1.86	7.30	1.88	7.46	1.90	7.78	1.93	8.10	1.96	
				29	6.40	1.84	6.70	1.87	7.01	1.91	7.17	1.92	7.33	1.94	7.65	1.97	7.97	2.01	
				31	6.27	1.89	6.57	1.92	6.89	1.95	7.04	1.97	7.20	1.99	7.52	2.02	7.85	2.05	
				33	6.14	1.93	6.45	1.97	6.76	2.00	6.92	2.02	7.07	2.03	7.39	2.07	7.72	2.10	
35	6.01	1.98	6.32	2.01	6.63	2.05	6.80	2.06	6.95	2.08	7.27	2.11	7.59	2.15					
37	5.88	2.03	6.19	2.06	6.50	2.10	6.66	2.11	6.82	2.13	7.14	2.16	7.47	2.20					
39	5.75	2.08	6.06	2.11	6.38	2.14	6.53	2.16	6.69	2.18	7.02	2.21	7.34	2.25					
42	5.56	2.15	5.87	2.19	6.19	2.22	6.34	2.24	6.50	2.25	6.83	2.29	7.15	2.32					
44	5.43	2.20	5.74	2.24	6.06	2.27	6.22	2.29	6.38	2.30	6.70	2.34	7.03	2.37					
46	5.31	2.25	5.62	2.29	5.93	2.32	6.09	2.34	6.25	2.36	6.58	2.39	6.91	2.42					

12. Capacity Table

Combination (Capacity Index)			Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, WB)													
						14		16		18		19		20		22		24	
						TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
2000	2000	2000	6000	88%	10	5.30	1.38	7.48	1.42	7.62	1.45	7.71	1.47	7.80	1.49	8.02	1.52	8.28	1.55
					12	5.30	1.42	7.28	1.45	7.43	1.49	7.52	1.50	7.62	1.52	7.85	1.55	8.11	1.58
					14	5.30	1.45	7.08	1.49	7.24	1.52	7.34	1.54	7.44	1.56	7.68	1.59	7.96	1.62
					16	5.30	1.49	6.89	1.53	7.07	1.56	7.17	1.58	7.28	1.59	7.53	1.62	7.81	1.65
					18	5.30	1.53	6.72	1.56	6.90	1.60	7.00	1.61	7.12	1.63	7.38	1.66	7.68	1.69
					20	5.30	1.57	6.55	1.60	6.74	1.64	6.85	1.65	6.97	1.67	7.24	1.70	7.55	1.73
					21	5.30	1.59	6.46	1.62	6.66	1.66	6.78	1.67	6.90	1.69	7.17	1.72	7.49	1.75
					23	5.30	1.63	6.31	1.66	6.51	1.70	6.63	1.71	6.76	1.73	7.05	1.76	7.37	1.79
					25	5.30	1.67	6.16	1.70	6.38	1.74	6.50	1.75	6.63	1.77	6.93	1.80	7.26	1.83
					27	5.30	1.71	6.02	1.75	6.25	1.78	6.37	1.80	6.51	1.81	6.82	1.84	7.16	1.87
					29	5.30	1.76	5.88	1.79	6.12	1.82	6.26	1.84	6.40	1.85	6.72	1.88	7.07	1.91
					31	5.30	1.80	5.76	1.83	6.01	1.87	6.15	1.88	6.30	1.90	6.62	1.93	6.99	1.96
					33	5.30	1.85	5.64	1.88	5.90	1.91	6.05	1.93	6.20	1.94	6.54	1.97	6.92	2.00
					35	5.30	1.89	5.54	1.93	5.81	1.96	6.00	1.97	6.12	1.99	6.46	2.02	6.85	2.05
					37	5.30	1.94	5.44	1.97	5.72	2.01	5.87	2.02	6.04	2.04	6.39	2.07	6.79	2.10
					39	5.30	1.99	5.34	2.02	5.64	2.06	5.80	2.07	5.97	2.09	6.34	2.12	6.74	2.14
2000	2000	2500	6500	96%	42	5.30	2.07	5.22	2.10	5.53	2.13	5.70	2.15	5.88	2.16	6.26	2.19	6.68	2.22
					44	5.30	2.12	5.15	2.15	5.47	2.18	5.64	2.20	5.83	2.21	6.22	2.24	6.65	2.27
					46	5.30	2.17	5.09	2.20	5.42	2.23	5.60	2.25	5.79	2.26	6.19	2.29	6.63	2.32
					10	5.74	1.41	8.10	1.44	8.26	1.47	8.35	1.49	8.45	1.51	8.69	1.54	8.97	1.57
					12	5.74	1.44	7.88	1.48	8.05	1.51	8.15	1.53	8.25	1.54	8.50	1.57	8.79	1.61
					14	5.74	1.48	7.67	1.51	7.85	1.55	7.95	1.56	8.06	1.58	8.32	1.61	8.62	1.64
					16	5.74	1.51	7.47	1.55	7.66	1.58	7.76	1.60	7.88	1.62	8.15	1.65	8.47	1.68
					18	5.74	1.55	7.28	1.59	7.47	1.62	7.59	1.64	7.71	1.65	7.99	1.69	8.32	1.72
					20	5.74	1.59	7.09	1.63	7.30	1.66	7.42	1.68	7.55	1.69	7.84	1.72	8.18	1.75
					21	5.74	1.61	7.00	1.65	7.22	1.68	7.34	1.70	7.47	1.71	7.77	1.74	8.11	1.77
					23	5.74	1.65	6.83	1.69	7.06	1.72	7.19	1.74	7.33	1.75	7.63	1.78	7.99	1.81
					25	5.74	1.70	6.67	1.73	6.91	1.76	7.04	1.78	7.19	1.80	7.51	1.83	7.87	1.86
					27	5.74	1.74	6.52	1.77	6.77	1.81	6.91	1.82	7.06	1.84	7.39	1.87	7.76	1.90
					29	5.74	1.78	6.37	1.82	6.63	1.85	6.78	1.87	6.93	1.88	7.28	1.91	7.66	1.94
					31	5.74	1.83	6.24	1.86	6.51	1.90	6.66	1.91	6.82	1.93	7.18	1.96	7.57	1.99
					33	5.74	1.87	6.11	1.91	6.40	1.94	6.55	1.96	6.72	1.97	7.08	2.00	7.49	2.03
					35	5.74	1.92	6.00	1.96	6.29	1.99	6.50	2.00	6.63	2.02	7.00	2.05	7.42	2.08
					37	5.74	1.97	5.89	2.00	6.19	2.04	6.36	2.05	6.54	2.07	6.93	2.10	7.36	2.13
					39	5.74	2.02	5.79	2.05	6.11	2.09	6.28	2.10	6.46	2.12	6.86	2.15	7.30	2.18
					42	5.74	2.10	5.66	2.13	5.99	2.16	6.17	2.18	6.37	2.19	6.78	2.22	7.24	2.25
					44	5.74	2.15	5.58	2.18	5.93	2.21	6.12	2.23	6.31	2.25	6.74	2.28	7.21	2.30
					46	5.74	2.20	5.52	2.24	5.87	2.27	6.07	2.28	6.27	2.30	6.71	2.33	7.19	2.36

12. Capacity Table

Combination (Capacity Index)			Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, WB)													
						14		16		18		19		20		22		24	
						TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
2000	2000	3500	7500	110%	10	6.01	1.45	8.48	1.49	8.64	1.53	8.73	1.54	8.84	1.56	9.09	1.59	9.38	1.63
					12	6.01	1.49	8.25	1.53	8.42	1.56	8.52	1.58	8.63	1.60	8.89	1.63	9.20	1.66
					14	6.01	1.53	8.03	1.56	8.21	1.60	8.32	1.62	8.44	1.63	8.71	1.67	9.02	1.70
					16	6.01	1.57	7.81	1.60	8.01	1.64	8.12	1.66	8.25	1.67	8.53	1.71	8.86	1.74
					18	6.01	1.61	7.61	1.64	7.82	1.68	7.94	1.70	8.07	1.71	8.36	1.74	8.70	1.78
					20	6.01	1.65	7.42	1.68	7.64	1.72	7.76	1.74	7.90	1.75	8.21	1.78	8.56	1.82
					21	6.01	1.67	7.33	1.70	7.55	1.74	7.68	1.76	7.82	1.77	8.13	1.81	8.49	1.84
					23	6.01	1.71	7.15	1.75	7.38	1.78	7.52	1.80	7.66	1.82	7.99	1.85	8.35	1.88
					25	6.01	1.75	6.98	1.79	7.23	1.83	7.37	1.84	7.52	1.86	7.85	1.89	8.23	1.92
					27	6.01	1.80	6.82	1.84	7.08	1.87	7.22	1.89	7.38	1.90	7.73	1.93	8.12	1.97
					29	6.01	1.85	6.67	1.88	6.94	1.92	7.09	1.93	7.25	1.95	7.61	1.98	8.02	2.01
					31	6.01	1.89	6.53	1.93	6.81	1.96	6.97	1.98	7.14	1.99	7.51	2.03	7.92	2.06
					33	6.01	1.94	6.40	1.98	6.69	2.01	6.85	2.03	7.03	2.04	7.41	2.07	7.84	2.10
					35	6.01	1.99	6.27	2.02	6.58	2.06	6.80	2.07	6.93	2.09	7.32	2.12	7.76	2.15
					37	6.01	2.04	6.16	2.07	6.48	2.11	6.66	2.12	6.84	2.14	7.25	2.17	7.70	2.20
					39	6.01	2.09	6.06	2.13	6.39	2.16	6.57	2.18	6.76	2.19	7.18	2.22	7.64	2.25
					42	6.01	2.17	5.92	2.21	6.27	2.24	6.46	2.25	6.66	2.27	7.10	2.30	7.57	2.33
					44	6.01	2.22	5.84	2.26	6.20	2.29	6.40	2.31	6.60	2.32	7.05	2.35	7.54	2.38
					46	6.01	2.28	5.77	2.31	6.14	2.35	6.35	2.36	6.56	2.38	7.02	2.41	7.52	2.44
2000	2000	5000	9000	132%	10	7.65	1.40	7.95	1.43	8.25	1.46	8.41	1.48	8.56	1.49	8.87	1.52	9.19	1.55
					12	7.51	1.44	7.81	1.47	8.12	1.50	8.27	1.52	8.43	1.53	8.74	1.56	9.06	1.59
					14	7.38	1.48	7.68	1.51	7.99	1.54	8.14	1.55	8.30	1.57	8.61	1.60	8.93	1.63
					16	7.25	1.52	7.55	1.55	7.86	1.58	8.01	1.59	8.17	1.61	8.48	1.64	8.80	1.67
					18	7.12	1.56	7.42	1.59	7.73	1.62	7.88	1.63	8.04	1.65	8.35	1.68	8.68	1.71
					20	6.99	1.60	7.29	1.63	7.60	1.66	7.75	1.68	7.91	1.69	8.23	1.72	8.55	1.75
					21	6.92	1.62	7.22	1.65	7.53	1.68	7.69	1.70	7.84	1.71	8.16	1.74	8.48	1.77
					23	6.79	1.66	7.09	1.69	7.40	1.72	7.56	1.74	7.71	1.75	8.03	1.78	8.35	1.82
					25	6.66	1.70	6.96	1.73	7.27	1.76	7.43	1.78	7.59	1.80	7.90	1.83	8.23	1.86
					27	6.53	1.74	6.83	1.78	7.14	1.81	7.30	1.82	7.46	1.84	7.78	1.87	8.10	1.90
					29	6.40	1.79	6.70	1.82	7.01	1.85	7.17	1.87	7.33	1.88	7.65	1.92	7.97	1.95
					31	6.27	1.83	6.57	1.86	6.89	1.90	7.04	1.91	7.20	1.93	7.52	1.96	7.85	1.99
					33	6.14	1.88	6.45	1.91	6.76	1.94	6.92	1.96	7.07	1.97	7.39	2.01	7.72	2.04
					35	6.01	1.92	6.32	1.96	6.63	1.99	6.80	2.00	6.95	2.02	7.27	2.05	7.59	2.09
					37	5.88	1.97	6.19	2.00	6.50	2.03	6.66	2.05	6.82	2.07	7.14	2.10	7.47	2.13
					39	5.75	2.02	6.06	2.05	6.38	2.08	6.53	2.10	6.69	2.12	7.02	2.15	7.34	2.18
					42	5.56	2.09	5.87	2.12	6.19	2.15	6.34	2.17	6.50	2.19	6.83	2.22	7.15	2.25
					44	5.43	2.14	5.74	2.17	6.06	2.20	6.22	2.22	6.38	2.24	6.70	2.27	7.03	2.30
					46	5.31	2.19	5.62	2.22	5.93	2.25	6.09	2.27	6.25	2.29	6.58	2.32	6.91	2.35

12. Capacity Table

Combination (Capacity Index)			Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, WB)													
						14		16		18		19		20		22		24	
						TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
2000	2500	2500	7000	103%	10	5.74	1.43	8.10	1.46	8.26	1.50	8.35	1.51	8.45	1.53	8.69	1.56	8.97	1.59
					12	5.74	1.46	7.88	1.50	8.05	1.53	8.15	1.55	8.25	1.57	8.50	1.60	8.79	1.63
					14	5.74	1.50	7.67	1.53	7.85	1.57	7.95	1.59	8.06	1.60	8.32	1.63	8.62	1.67
					16	5.74	1.54	7.47	1.57	7.66	1.61	7.76	1.62	7.88	1.64	8.15	1.67	8.47	1.70
					18	5.74	1.58	7.28	1.61	7.47	1.65	7.59	1.66	7.71	1.68	7.99	1.71	8.32	1.74
					20	5.74	1.62	7.09	1.65	7.30	1.69	7.42	1.70	7.55	1.72	7.84	1.75	8.18	1.78
					21	5.74	1.64	7.00	1.67	7.22	1.71	7.34	1.72	7.47	1.74	7.77	1.77	8.11	1.80
					23	5.74	1.68	6.83	1.71	7.06	1.75	7.19	1.76	7.33	1.78	7.63	1.81	7.99	1.84
					25	5.74	1.72	6.67	1.76	6.91	1.79	7.04	1.81	7.19	1.82	7.51	1.85	7.87	1.88
					27	5.74	1.76	6.52	1.80	6.77	1.83	6.91	1.85	7.06	1.87	7.39	1.90	7.76	1.93
					29	5.74	1.81	6.37	1.84	6.63	1.88	6.78	1.89	6.93	1.91	7.28	1.94	7.66	1.97
					31	5.74	1.86	6.24	1.89	6.51	1.92	6.66	1.94	6.82	1.96	7.18	1.99	7.57	2.02
					33	5.74	1.90	6.11	1.94	6.40	1.97	6.55	1.99	6.72	2.00	7.08	2.03	7.49	2.06
					35	5.74	1.95	6.00	1.99	6.29	2.02	6.50	2.03	6.63	2.05	7.00	2.08	7.42	2.11
					37	5.74	2.00	5.89	2.03	6.19	2.07	6.36	2.08	6.54	2.10	6.93	2.13	7.36	2.16
					39	5.74	2.05	5.79	2.09	6.11	2.12	6.28	2.13	6.46	2.15	6.86	2.18	7.30	2.21
					42	5.74	2.13	5.66	2.16	5.99	2.20	6.17	2.21	6.37	2.23	6.78	2.26	7.24	2.29
					44	5.74	2.18	5.58	2.22	5.93	2.25	6.12	2.26	6.31	2.28	6.74	2.31	7.21	2.34
					46	5.74	2.24	5.52	2.27	5.87	2.30	6.07	2.32	6.27	2.33	6.71	2.36	7.19	2.39
2000	2500	3500	8000	118%	10	7.65	1.47	7.95	1.50	8.25	1.53	8.41	1.54	8.56	1.56	8.87	1.59	9.19	1.62
					12	7.51	1.51	7.81	1.54	8.12	1.57	8.27	1.58	8.43	1.60	8.74	1.63	9.06	1.66
					14	7.38	1.55	7.68	1.58	7.99	1.61	8.14	1.62	8.30	1.64	8.61	1.67	8.93	1.70
					16	7.25	1.59	7.55	1.62	7.86	1.65	8.01	1.67	8.17	1.68	8.48	1.71	8.80	1.75
					18	7.12	1.63	7.42	1.66	7.73	1.69	7.88	1.71	8.04	1.72	8.35	1.76	8.68	1.79
					20	6.99	1.67	7.29	1.70	7.60	1.73	7.75	1.75	7.91	1.77	8.23	1.80	8.55	1.83
					21	6.92	1.69	7.22	1.72	7.53	1.76	7.69	1.77	7.84	1.79	8.16	1.82	8.48	1.85
					23	6.79	1.73	7.09	1.77	7.40	1.80	7.56	1.82	7.71	1.83	8.03	1.87	8.35	1.90
					25	6.66	1.78	6.96	1.81	7.27	1.84	7.43	1.86	7.59	1.88	7.90	1.91	8.23	1.94
					27	6.53	1.82	6.83	1.86	7.14	1.89	7.30	1.91	7.46	1.92	7.78	1.96	8.10	1.99
					29	6.40	1.87	6.70	1.90	7.01	1.94	7.17	1.95	7.33	1.97	7.65	2.00	7.97	2.04
					31	6.27	1.92	6.57	1.95	6.89	1.98	7.04	2.00	7.20	2.02	7.52	2.05	7.85	2.08
					33	6.14	1.96	6.45	2.00	6.76	2.03	6.92	2.05	7.07	2.06	7.39	2.10	7.72	2.13
					35	6.01	2.01	6.32	2.04	6.63	2.08	6.80	2.09	6.95	2.11	7.27	2.15	7.59	2.18
					37	5.88	2.06	6.19	2.09	6.50	2.13	6.66	2.14	6.82	2.16	7.14	2.19	7.47	2.23
					39	5.75	2.11	6.06	2.14	6.38	2.18	6.53	2.19	6.69	2.21	7.02	2.24	7.34	2.28
					42	5.56	2.18	5.87	2.22	6.19	2.25	6.34	2.27	6.50	2.29	6.83	2.32	7.15	2.36
					44	5.43	2.23	5.74	2.27	6.06	2.30	6.22	2.32	6.38	2.34	6.70	2.37	7.03	2.41
					46	5.31	2.29	5.62	2.32	5.93	2.36	6.09	2.37	6.25	2.39	6.58	2.43	6.91	2.46

12. Capacity Table

Combination (Capacity Index)			Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, WB)													
						14		16		18		19		20		22		24	
						TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
2000	2500	5000	9500	140%	10	7.65	1.41	7.95	1.44	8.25	1.47	8.41	1.49	8.56	1.50	8.87	1.53	9.19	1.56
					12	7.51	1.45	7.81	1.48	8.12	1.51	8.27	1.52	8.43	1.54	8.74	1.57	9.06	1.60
					14	7.38	1.49	7.68	1.52	7.99	1.55	8.14	1.56	8.30	1.58	8.61	1.61	8.93	1.64
					16	7.25	1.53	7.55	1.56	7.86	1.59	8.01	1.60	8.17	1.62	8.48	1.65	8.80	1.68
					18	7.12	1.57	7.42	1.60	7.73	1.63	7.88	1.64	8.04	1.66	8.35	1.69	8.68	1.72
					20	6.99	1.61	7.29	1.64	7.60	1.67	7.75	1.68	7.91	1.70	8.23	1.73	8.55	1.76
					21	6.92	1.63	7.22	1.66	7.53	1.69	7.69	1.70	7.84	1.72	8.16	1.75	8.48	1.78
					23	6.79	1.67	7.09	1.70	7.40	1.73	7.56	1.75	7.71	1.76	8.03	1.79	8.35	1.83
					25	6.66	1.71	6.96	1.74	7.27	1.77	7.43	1.79	7.59	1.81	7.90	1.84	8.23	1.87
					27	6.53	1.75	6.83	1.79	7.14	1.82	7.30	1.83	7.46	1.85	7.78	1.88	8.10	1.91
					29	6.40	1.80	6.70	1.83	7.01	1.86	7.17	1.88	7.33	1.89	7.65	1.93	7.97	1.96
					31	6.27	1.84	6.57	1.87	6.89	1.91	7.04	1.92	7.20	1.94	7.52	1.97	7.85	2.00
					33	6.14	1.89	6.45	1.92	6.76	1.95	6.92	1.97	7.07	1.98	7.39	2.02	7.72	2.05
					35	6.01	1.93	6.32	1.97	6.63	2.00	6.80	2.01	6.95	2.03	7.27	2.06	7.59	2.10
					37	5.88	1.98	6.19	2.01	6.50	2.04	6.66	2.06	6.82	2.08	7.14	2.11	7.47	2.14
					39	5.75	2.03	6.06	2.06	6.38	2.09	6.53	2.11	6.69	2.13	7.02	2.16	7.34	2.19
2000	2500	2500	7000	103%	42	5.56	2.10	5.87	2.13	6.19	2.17	6.34	2.18	6.50	2.20	6.83	2.23	7.15	2.27
					44	5.43	2.15	5.74	2.18	6.06	2.21	6.22	2.23	6.38	2.25	6.70	2.28	7.03	2.32
					46	5.31	2.20	5.62	2.23	5.93	2.26	6.09	2.28	6.25	2.30	6.58	2.33	6.91	2.37
					10	7.65	1.41	7.95	1.44	8.25	1.47	8.41	1.49	8.56	1.50	8.87	1.53	9.19	1.56
					12	7.51	1.45	7.81	1.48	8.12	1.51	8.27	1.52	8.43	1.54	8.74	1.57	9.06	1.60
					14	7.38	1.49	7.68	1.52	7.99	1.55	8.14	1.56	8.30	1.58	8.61	1.61	8.93	1.64
					16	7.25	1.53	7.55	1.56	7.86	1.59	8.01	1.60	8.17	1.62	8.48	1.65	8.80	1.68
					18	7.12	1.57	7.42	1.60	7.73	1.63	7.88	1.64	8.04	1.66	8.35	1.69	8.68	1.72
					20	6.99	1.61	7.29	1.64	7.60	1.67	7.75	1.68	7.91	1.70	8.23	1.73	8.55	1.76
					21	6.92	1.63	7.22	1.66	7.53	1.69	7.69	1.70	7.84	1.72	8.16	1.75	8.48	1.78
					23	6.79	1.67	7.09	1.70	7.40	1.73	7.56	1.75	7.71	1.76	8.03	1.79	8.35	1.83
					25	6.66	1.71	6.96	1.74	7.27	1.77	7.43	1.79	7.59	1.81	7.90	1.84	8.23	1.87
					27	6.53	1.75	6.83	1.79	7.14	1.82	7.30	1.83	7.46	1.85	7.78	1.88	8.10	1.91
					29	6.40	1.80	6.70	1.83	7.01	1.86	7.17	1.88	7.33	1.89	7.65	1.93	7.97	1.96
					31	6.27	1.84	6.57	1.87	6.89	1.91	7.04	1.92	7.20	1.94	7.52	1.97	7.85	2.00
					33	6.14	1.89	6.45	1.92	6.76	1.95	6.92	1.97	7.07	1.98	7.39	2.02	7.72	2.05
35	6.01	1.93	6.32	1.97	6.63	2.00	6.80	2.01	6.95	2.03	7.27	2.06	7.59	2.10					
37	5.88	1.98	6.19	2.01	6.50	2.04	6.66	2.06	6.82	2.08	7.14	2.11	7.47	2.14					
39	5.75	2.03	6.06	2.06	6.38	2.09	6.53	2.11	6.69	2.13	7.02	2.16	7.34	2.19					
42	5.56	2.10	5.87	2.13	6.19	2.17	6.34	2.18	6.50	2.20	6.83	2.23	7.15	2.27					
44	5.43	2.15	5.74	2.18	6.06	2.21	6.22	2.23	6.38	2.25	6.70	2.28	7.03	2.32					
46	5.31	2.20	5.62	2.23	5.93	2.26	6.09	2.28	6.25	2.30	6.58	2.33	6.91	2.37					

12. Capacity Table

Combination (Capacity Index)			Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, WB)													
						14		16		18		19		20		22		24	
						TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
2000	2500	3500	8000	118%	10	7.65	1.44	7.95	1.47	8.25	1.50	8.41	1.52	8.56	1.53	8.87	1.56	9.19	1.59
					12	7.51	1.48	7.81	1.51	8.12	1.54	8.27	1.55	8.43	1.57	8.74	1.60	9.06	1.63
					14	7.38	1.52	7.68	1.55	7.99	1.58	8.14	1.59	8.30	1.61	8.61	1.64	8.93	1.67
					16	7.25	1.56	7.55	1.59	7.86	1.62	8.01	1.63	8.17	1.65	8.48	1.68	8.80	1.71
					18	7.12	1.60	7.42	1.63	7.73	1.66	7.88	1.68	8.04	1.69	8.35	1.72	8.68	1.75
					20	6.99	1.64	7.29	1.67	7.60	1.70	7.75	1.72	7.91	1.73	8.23	1.76	8.55	1.80
					21	6.92	1.66	7.22	1.69	7.53	1.72	7.69	1.74	7.84	1.75	8.16	1.79	8.48	1.82
					23	6.79	1.70	7.09	1.73	7.40	1.77	7.56	1.78	7.71	1.80	8.03	1.83	8.35	1.86
					25	6.66	1.74	6.96	1.78	7.27	1.81	7.43	1.83	7.59	1.84	7.90	1.87	8.23	1.91
					27	6.53	1.79	6.83	1.82	7.14	1.85	7.30	1.87	7.46	1.89	7.78	1.92	8.10	1.95
					29	6.40	1.83	6.70	1.87	7.01	1.90	7.17	1.91	7.33	1.93	7.65	1.96	7.97	2.00
					31	6.27	1.88	6.57	1.91	6.89	1.94	7.04	1.96	7.20	1.98	7.52	2.01	7.85	2.04
					33	6.14	1.92	6.45	1.96	6.76	1.99	6.92	2.01	7.07	2.02	7.39	2.06	7.72	2.09
					35	6.01	1.97	6.32	2.00	6.63	2.04	6.80	2.05	6.95	2.07	7.27	2.10	7.59	2.14
					37	5.88	2.02	6.19	2.05	6.50	2.09	6.66	2.10	6.82	2.12	7.14	2.15	7.47	2.19
					39	5.75	2.07	6.06	2.10	6.38	2.13	6.53	2.15	6.69	2.17	7.02	2.20	7.34	2.24
2000	2500	5000	9500	140%	42	5.56	2.14	5.87	2.17	6.19	2.21	6.34	2.23	6.50	2.24	6.83	2.28	7.15	2.31
					44	5.43	2.19	5.74	2.22	6.06	2.26	6.22	2.28	6.38	2.29	6.70	2.33	7.03	2.36
					46	5.31	2.24	5.62	2.28	5.93	2.31	6.09	2.33	6.25	2.34	6.58	2.38	6.91	2.41
					10	7.65	1.45	7.95	1.48	8.25	1.51	8.41	1.52	8.56	1.54	8.87	1.57	9.19	1.60
					12	7.51	1.48	7.81	1.52	8.12	1.55	8.27	1.56	8.43	1.58	8.74	1.61	9.06	1.64
					14	7.38	1.52	7.68	1.55	7.99	1.59	8.14	1.60	8.30	1.62	8.61	1.65	8.93	1.68
					16	7.25	1.56	7.55	1.60	7.86	1.63	8.01	1.64	8.17	1.66	8.48	1.69	8.80	1.72
					18	7.12	1.60	7.42	1.64	7.73	1.67	7.88	1.68	8.04	1.70	8.35	1.73	8.68	1.76
					20	6.99	1.65	7.29	1.68	7.60	1.71	7.75	1.73	7.91	1.74	8.23	1.77	8.55	1.81
					21	6.92	1.67	7.22	1.70	7.53	1.73	7.69	1.75	7.84	1.76	8.16	1.79	8.48	1.83
					23	6.79	1.71	7.09	1.74	7.40	1.77	7.56	1.79	7.71	1.81	8.03	1.84	8.35	1.87
					25	6.66	1.75	6.96	1.79	7.27	1.82	7.43	1.83	7.59	1.85	7.90	1.88	8.23	1.92
					27	6.53	1.80	6.83	1.83	7.14	1.86	7.30	1.88	7.46	1.90	7.78	1.93	8.10	1.96
					29	6.40	1.84	6.70	1.87	7.01	1.91	7.17	1.92	7.33	1.94	7.65	1.97	7.97	2.01
					31	6.27	1.89	6.57	1.92	6.89	1.95	7.04	1.97	7.20	1.99	7.52	2.02	7.85	2.05
					33	6.14	1.93	6.45	1.97	6.76	2.00	6.92	2.02	7.07	2.03	7.39	2.07	7.72	2.10
35	6.01	1.98	6.32	2.01	6.63	2.05	6.80	2.06	6.95	2.08	7.27	2.11	7.59	2.15					
37	5.88	2.03	6.19	2.06	6.50	2.10	6.66	2.11	6.82	2.13	7.14	2.16	7.47	2.20					
39	5.75	2.08	6.06	2.11	6.38	2.14	6.53	2.16	6.69	2.18	7.02	2.21	7.34	2.25					
42	5.56	2.15	5.87	2.19	6.19	2.22	6.34	2.24	6.50	2.25	6.83	2.29	7.15	2.32					
44	5.43	2.20	5.74	2.24	6.06	2.27	6.22	2.29	6.38	2.30	6.70	2.34	7.03	2.37					
46	5.31	2.25	5.62	2.29	5.93	2.32	6.09	2.34	6.25	2.36	6.58	2.39	6.91	2.42					

12. Capacity Table

Combination (Capacity Index)			Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, WB)													
						14		16		18		19		20		22		24	
						TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
2000	3500	3500	9000	132%	10	7.65	1.49	7.95	1.53	8.25	1.56	8.41	1.57	8.56	1.59	8.87	1.62	9.19	1.65
					12	7.51	1.53	7.81	1.57	8.12	1.60	8.27	1.61	8.43	1.63	8.74	1.66	9.06	1.69
					14	7.38	1.58	7.68	1.61	7.99	1.64	8.14	1.66	8.30	1.67	8.61	1.70	8.93	1.74
					16	7.25	1.62	7.55	1.65	7.86	1.68	8.01	1.70	8.17	1.71	8.48	1.75	8.80	1.78
					18	7.12	1.66	7.42	1.69	7.73	1.72	7.88	1.74	8.04	1.76	8.35	1.79	8.68	1.82
					20	6.99	1.70	7.29	1.73	7.60	1.77	7.75	1.78	7.91	1.80	8.23	1.83	8.55	1.87
					21	6.92	1.72	7.22	1.76	7.53	1.79	7.69	1.81	7.84	1.82	8.16	1.86	8.48	1.89
					23	6.79	1.77	7.09	1.80	7.40	1.83	7.56	1.85	7.71	1.87	8.03	1.90	8.35	1.93
					25	6.66	1.81	6.96	1.85	7.27	1.88	7.43	1.90	7.59	1.91	7.90	1.95	8.23	1.98
					27	6.53	1.86	6.83	1.89	7.14	1.93	7.30	1.94	7.46	1.96	7.78	1.99	8.10	2.03
					29	6.40	1.90	6.70	1.94	7.01	1.97	7.17	1.99	7.33	2.01	7.65	2.04	7.97	2.07
					31	6.27	1.95	6.57	1.99	6.89	2.02	7.04	2.04	7.20	2.05	7.52	2.09	7.85	2.12
					33	6.14	2.00	6.45	2.03	6.76	2.07	6.92	2.09	7.07	2.10	7.39	2.14	7.72	2.17
					35	6.01	2.05	6.32	2.08	6.63	2.12	6.80	2.13	6.95	2.15	7.27	2.19	7.59	2.22
					37	5.88	2.10	6.19	2.13	6.50	2.17	6.66	2.18	6.82	2.20	7.14	2.24	7.47	2.27
					39	5.75	2.15	6.06	2.18	6.38	2.22	6.53	2.24	6.69	2.25	7.02	2.29	7.34	2.32
2000	3500	5000	10500	154%	42	5.56	2.22	5.87	2.26	6.19	2.29	6.34	2.31	6.50	2.33	6.83	2.37	7.15	2.40
					44	5.43	2.28	5.74	2.31	6.06	2.35	6.22	2.36	6.38	2.38	6.70	2.42	7.03	2.45
					46	5.31	2.33	5.62	2.36	5.93	2.40	6.09	2.42	6.25	2.44	6.58	2.47	6.91	2.51
					10	7.65	1.42	7.95	1.45	8.25	1.49	8.41	1.50	8.56	1.52	8.87	1.55	9.19	1.58
					12	7.51	1.46	7.81	1.49	8.12	1.52	8.27	1.54	8.43	1.55	8.74	1.58	9.06	1.62
					14	7.38	1.50	7.68	1.53	7.99	1.56	8.14	1.58	8.30	1.59	8.61	1.62	8.93	1.66
					16	7.25	1.54	7.55	1.57	7.86	1.60	8.01	1.62	8.17	1.63	8.48	1.66	8.80	1.70
					18	7.12	1.58	7.42	1.61	7.73	1.64	7.88	1.66	8.04	1.67	8.35	1.71	8.68	1.74
					20	6.99	1.62	7.29	1.65	7.60	1.68	7.75	1.70	7.91	1.72	8.23	1.75	8.55	1.78
					21	6.92	1.64	7.22	1.67	7.53	1.71	7.69	1.72	7.84	1.74	8.16	1.77	8.48	1.80
					23	6.79	1.68	7.09	1.72	7.40	1.75	7.56	1.76	7.71	1.78	8.03	1.81	8.35	1.84
					25	6.66	1.73	6.96	1.76	7.27	1.79	7.43	1.81	7.59	1.82	7.90	1.86	8.23	1.89
					27	6.53	1.77	6.83	1.80	7.14	1.84	7.30	1.85	7.46	1.87	7.78	1.90	8.10	1.93
					29	6.40	1.82	6.70	1.85	7.01	1.88	7.17	1.90	7.33	1.91	7.65	1.94	7.97	1.98
					31	6.27	1.86	6.57	1.89	6.89	1.93	7.04	1.94	7.20	1.96	7.52	1.99	7.85	2.02
					33	6.14	1.91	6.45	1.94	6.76	1.97	6.92	1.99	7.07	2.00	7.39	2.04	7.72	2.07
35	6.01	1.95	6.32	1.98	6.63	2.02	6.80	2.03	6.95	2.05	7.27	2.08	7.59	2.12					
37	5.88	2.00	6.19	2.03	6.50	2.07	6.66	2.08	6.82	2.10	7.14	2.13	7.47	2.16					
39	5.75	2.05	6.06	2.08	6.38	2.11	6.53	2.13	6.69	2.15	7.02	2.18	7.34	2.21					
42	5.56	2.12	5.87	2.15	6.19	2.19	6.34	2.20	6.50	2.22	6.83	2.25	7.15	2.29					
44	5.43	2.17	5.74	2.20	6.06	2.24	6.22	2.25	6.38	2.27	6.70	2.30	7.03	2.34					
46	5.31	2.22	5.62	2.25	5.93	2.29	6.09	2.30	6.25	2.32	6.58	2.36	6.91	2.39					

12. Capacity Table

Combination (Capacity Index)			Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, WB)													
						14		16		18		19		20		22		24	
						TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
2500	2500	2500	7500	110%	10	7.65	1.42	7.95	1.45	8.25	1.48	8.41	1.49	8.56	1.51	8.87	1.54	9.19	1.57
					12	7.51	1.46	7.81	1.49	8.12	1.52	8.27	1.53	8.43	1.55	8.74	1.58	9.06	1.61
					14	7.38	1.49	7.68	1.52	7.99	1.56	8.14	1.57	8.30	1.59	8.61	1.62	8.93	1.65
					16	7.25	1.53	7.55	1.56	7.86	1.59	8.01	1.61	8.17	1.63	8.48	1.66	8.80	1.69
					18	7.12	1.57	7.42	1.60	7.73	1.64	7.88	1.65	8.04	1.67	8.35	1.70	8.68	1.73
					20	6.99	1.61	7.29	1.65	7.60	1.68	7.75	1.69	7.91	1.71	8.23	1.74	8.55	1.77
					21	6.92	1.63	7.22	1.67	7.53	1.70	7.69	1.71	7.84	1.73	8.16	1.76	8.48	1.79
					23	6.79	1.68	7.09	1.71	7.40	1.74	7.56	1.76	7.71	1.77	8.03	1.80	8.35	1.83
					25	6.66	1.72	6.96	1.75	7.27	1.78	7.43	1.80	7.59	1.81	7.90	1.85	8.23	1.88
					27	6.53	1.76	6.83	1.79	7.14	1.83	7.30	1.84	7.46	1.86	7.78	1.89	8.10	1.92
					29	6.40	1.81	6.70	1.84	7.01	1.87	7.17	1.89	7.33	1.90	7.65	1.93	7.97	1.97
					31	6.27	1.85	6.57	1.88	6.89	1.92	7.04	1.93	7.20	1.95	7.52	1.98	7.85	2.01
					33	6.14	1.90	6.45	1.93	6.76	1.96	6.92	1.98	7.07	1.99	7.39	2.03	7.72	2.06
					35	6.01	1.94	6.32	1.98	6.63	2.01	6.80	2.02	6.95	2.04	7.27	2.07	7.59	2.11
					37	5.88	1.99	6.19	2.02	6.50	2.06	6.66	2.07	6.82	2.09	7.14	2.12	7.47	2.15
					39	5.75	2.04	6.06	2.07	6.38	2.10	6.53	2.12	6.69	2.14	7.02	2.17	7.34	2.20
					42	5.56	2.11	5.87	2.14	6.19	2.18	6.34	2.19	6.50	2.21	6.83	2.24	7.15	2.28
					44	5.43	2.16	5.74	2.19	6.06	2.23	6.22	2.24	6.38	2.26	6.70	2.29	7.03	2.33
					46	5.31	2.21	5.62	2.24	5.93	2.28	6.09	2.29	6.25	2.31	6.58	2.34	6.91	2.38
2500	2500	3500	8500	125%	10	7.65	1.45	7.95	1.48	8.25	1.51	8.41	1.53	8.56	1.55	8.87	1.58	9.19	1.61
					12	7.51	1.49	7.81	1.52	8.12	1.55	8.27	1.57	8.43	1.58	8.74	1.62	9.06	1.65
					14	7.38	1.53	7.68	1.56	7.99	1.59	8.14	1.61	8.30	1.63	8.61	1.66	8.93	1.69
					16	7.25	1.57	7.55	1.60	7.86	1.63	8.01	1.65	8.17	1.67	8.48	1.70	8.80	1.73
					18	7.12	1.61	7.42	1.64	7.73	1.68	7.88	1.69	8.04	1.71	8.35	1.74	8.68	1.77
					20	6.99	1.65	7.29	1.69	7.60	1.72	7.75	1.73	7.91	1.75	8.23	1.78	8.55	1.81
					21	6.92	1.68	7.22	1.71	7.53	1.74	7.69	1.76	7.84	1.77	8.16	1.80	8.48	1.84
					23	6.79	1.72	7.09	1.75	7.40	1.78	7.56	1.80	7.71	1.82	8.03	1.85	8.35	1.88
					25	6.66	1.76	6.96	1.79	7.27	1.83	7.43	1.84	7.59	1.86	7.90	1.89	8.23	1.92
					27	6.53	1.81	6.83	1.84	7.14	1.87	7.30	1.89	7.46	1.90	7.78	1.94	8.10	1.97
					29	6.40	1.85	6.70	1.88	7.01	1.92	7.17	1.93	7.33	1.95	7.65	1.98	7.97	2.02
					31	6.27	1.90	6.57	1.93	6.89	1.96	7.04	1.98	7.20	2.00	7.52	2.03	7.85	2.06
					33	6.14	1.94	6.45	1.98	6.76	2.01	6.92	2.03	7.07	2.04	7.39	2.08	7.72	2.11
					35	6.01	1.99	6.32	2.02	6.63	2.06	6.80	2.07	6.95	2.09	7.27	2.12	7.59	2.16
					37	5.88	2.04	6.19	2.07	6.50	2.11	6.66	2.12	6.82	2.14	7.14	2.17	7.47	2.21
					39	5.75	2.09	6.06	2.12	6.38	2.16	6.53	2.17	6.69	2.19	7.02	2.22	7.34	2.26
					42	5.56	2.16	5.87	2.20	6.19	2.23	6.34	2.25	6.50	2.26	6.83	2.30	7.15	2.33
					44	5.43	2.21	5.74	2.25	6.06	2.28	6.22	2.30	6.38	2.32	6.70	2.35	7.03	2.38
					46	5.31	2.26	5.62	2.30	5.93	2.33	6.09	2.35	6.25	2.37	6.58	2.40	6.91	2.44

12. Capacity Table

Combination (Capacity Index)			Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, WB)													
						14		16		18		19		20		22		24	
						TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
2500	2500	5000	10000	147%	10	7.65	1.40	7.95	1.43	8.25	1.46	8.41	1.48	8.56	1.49	8.87	1.52	9.19	1.55
					12	7.51	1.44	7.81	1.47	8.12	1.50	8.27	1.52	8.43	1.53	8.74	1.56	9.06	1.59
					14	7.38	1.48	7.68	1.51	7.99	1.54	8.14	1.55	8.30	1.57	8.61	1.60	8.93	1.63
					16	7.25	1.52	7.55	1.55	7.86	1.58	8.01	1.59	8.17	1.61	8.48	1.64	8.80	1.67
					18	7.12	1.56	7.42	1.59	7.73	1.62	7.88	1.63	8.04	1.65	8.35	1.68	8.68	1.71
					20	6.99	1.60	7.29	1.63	7.60	1.66	7.75	1.68	7.91	1.69	8.23	1.72	8.55	1.75
					21	6.92	1.62	7.22	1.65	7.53	1.68	7.69	1.70	7.84	1.71	8.16	1.74	8.48	1.77
					23	6.79	1.66	7.09	1.69	7.40	1.72	7.56	1.74	7.71	1.75	8.03	1.78	8.35	1.82
					25	6.66	1.70	6.96	1.73	7.27	1.76	7.43	1.78	7.59	1.80	7.90	1.83	8.23	1.86
					27	6.53	1.74	6.83	1.78	7.14	1.81	7.30	1.82	7.46	1.84	7.78	1.87	8.10	1.90
					29	6.40	1.79	6.70	1.82	7.01	1.85	7.17	1.87	7.33	1.88	7.65	1.92	7.97	1.95
					31	6.27	1.83	6.57	1.86	6.89	1.90	7.04	1.91	7.20	1.93	7.52	1.96	7.85	1.99
					33	6.14	1.88	6.45	1.91	6.76	1.94	6.92	1.96	7.07	1.97	7.39	2.01	7.72	2.04
					35	6.01	1.92	6.32	1.96	6.63	1.99	6.80	2.00	6.95	2.02	7.27	2.05	7.59	2.09
					37	5.88	1.97	6.19	2.00	6.50	2.03	6.66	2.05	6.82	2.07	7.14	2.10	7.47	2.13
					39	5.75	2.02	6.06	2.05	6.38	2.08	6.53	2.10	6.69	2.12	7.02	2.15	7.34	2.18
2500	3500	3500	9500	140%	42	5.56	2.09	5.87	2.12	6.19	2.15	6.34	2.17	6.50	2.19	6.83	2.22	7.15	2.25
					44	5.43	2.14	5.74	2.17	6.06	2.20	6.22	2.22	6.38	2.24	6.70	2.27	7.03	2.30
					46	5.31	2.19	5.62	2.22	5.93	2.25	6.09	2.27	6.25	2.29	6.58	2.32	6.91	2.35
					10	7.65	1.45	7.95	1.48	8.25	1.51	8.41	1.52	8.56	1.54	8.87	1.57	9.19	1.60
					12	7.51	1.48	7.81	1.52	8.12	1.55	8.27	1.56	8.43	1.58	8.74	1.61	9.06	1.64
					14	7.38	1.52	7.68	1.55	7.99	1.59	8.14	1.60	8.30	1.62	8.61	1.65	8.93	1.68
					16	7.25	1.56	7.55	1.60	7.86	1.63	8.01	1.64	8.17	1.66	8.48	1.69	8.80	1.72
					18	7.12	1.60	7.42	1.64	7.73	1.67	7.88	1.68	8.04	1.70	8.35	1.73	8.68	1.76
					20	6.99	1.65	7.29	1.68	7.60	1.71	7.75	1.73	7.91	1.74	8.23	1.77	8.55	1.81
					21	6.92	1.67	7.22	1.70	7.53	1.73	7.69	1.75	7.84	1.76	8.16	1.79	8.48	1.83
					23	6.79	1.71	7.09	1.74	7.40	1.77	7.56	1.79	7.71	1.81	8.03	1.84	8.35	1.87
					25	6.66	1.75	6.96	1.79	7.27	1.82	7.43	1.83	7.59	1.85	7.90	1.88	8.23	1.92
					27	6.53	1.80	6.83	1.83	7.14	1.86	7.30	1.88	7.46	1.90	7.78	1.93	8.10	1.96
					29	6.40	1.84	6.70	1.87	7.01	1.91	7.17	1.92	7.33	1.94	7.65	1.97	7.97	2.01
					31	6.27	1.89	6.57	1.92	6.89	1.95	7.04	1.97	7.20	1.99	7.52	2.02	7.85	2.05
					33	6.14	1.93	6.45	1.97	6.76	2.00	6.92	2.02	7.07	2.03	7.39	2.07	7.72	2.10
35	6.01	1.98	6.32	2.01	6.63	2.05	6.80	2.06	6.95	2.08	7.27	2.11	7.59	2.15					
37	5.88	2.03	6.19	2.06	6.50	2.10	6.66	2.11	6.82	2.13	7.14	2.16	7.47	2.20					
39	5.75	2.08	6.06	2.11	6.38	2.14	6.53	2.16	6.69	2.18	7.02	2.21	7.34	2.25					
42	5.56	2.15	5.87	2.19	6.19	2.22	6.34	2.24	6.50	2.25	6.83	2.29	7.15	2.32					
44	5.43	2.20	5.74	2.24	6.06	2.27	6.22	2.29	6.38	2.30	6.70	2.34	7.03	2.37					
46	5.31	2.25	5.62	2.29	5.93	2.32	6.09	2.34	6.25	2.36	6.58	2.39	6.91	2.42					

12. Capacity Table

Combination (Capacity Index)			Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, WB)													
						14		16		18		19		20		22		24	
						TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
2500	3500	5000	11000	162%	10	7.65	1.45	7.95	1.48	8.25	1.51	8.41	1.52	8.56	1.54	8.87	1.57	9.19	1.60
					12	7.51	1.48	7.81	1.52	8.12	1.55	8.27	1.56	8.43	1.58	8.74	1.61	9.06	1.64
					14	7.38	1.52	7.68	1.55	7.99	1.59	8.14	1.60	8.30	1.62	8.61	1.65	8.93	1.68
					16	7.25	1.56	7.55	1.60	7.86	1.63	8.01	1.64	8.17	1.66	8.48	1.69	8.80	1.72
					18	7.12	1.60	7.42	1.64	7.73	1.67	7.88	1.68	8.04	1.70	8.35	1.73	8.68	1.76
					20	6.99	1.65	7.29	1.68	7.60	1.71	7.75	1.73	7.91	1.74	8.23	1.77	8.55	1.81
					21	6.92	1.67	7.22	1.70	7.53	1.73	7.69	1.75	7.84	1.76	8.16	1.79	8.48	1.83
					23	6.79	1.71	7.09	1.74	7.40	1.77	7.56	1.79	7.71	1.81	8.03	1.84	8.35	1.87
					25	6.66	1.75	6.96	1.79	7.27	1.82	7.43	1.83	7.59	1.85	7.90	1.88	8.23	1.92
					27	6.53	1.80	6.83	1.83	7.14	1.86	7.30	1.88	7.46	1.90	7.78	1.93	8.10	1.96
					29	6.40	1.84	6.70	1.87	7.01	1.91	7.17	1.92	7.33	1.94	7.65	1.97	7.97	2.01
					31	6.27	1.89	6.57	1.92	6.89	1.95	7.04	1.97	7.20	1.99	7.52	2.02	7.85	2.05
					33	6.14	1.93	6.45	1.97	6.76	2.00	6.92	2.02	7.07	2.03	7.39	2.07	7.72	2.10
					35	6.01	1.98	6.32	2.01	6.63	2.05	6.80	2.06	6.95	2.08	7.27	2.11	7.59	2.15
					37	5.88	2.03	6.19	2.06	6.50	2.10	6.66	2.11	6.82	2.13	7.14	2.16	7.47	2.20
					39	5.75	2.08	6.06	2.11	6.38	2.14	6.53	2.16	6.69	2.18	7.02	2.21	7.34	2.25
3500	3500	3500	10500	154%	42	5.56	2.15	5.87	2.19	6.19	2.22	6.34	2.24	6.50	2.25	6.83	2.29	7.15	2.32
					44	5.43	2.20	5.74	2.24	6.06	2.27	6.22	2.29	6.38	2.30	6.70	2.34	7.03	2.37
					46	5.31	2.25	5.62	2.29	5.93	2.32	6.09	2.34	6.25	2.36	6.58	2.39	6.91	2.42
					10	7.65	1.45	7.95	1.48	8.25	1.51	8.41	1.52	8.56	1.54	8.87	1.57	9.19	1.60
					12	7.51	1.48	7.81	1.52	8.12	1.55	8.27	1.56	8.43	1.58	8.74	1.61	9.06	1.64
					14	7.38	1.52	7.68	1.55	7.99	1.59	8.14	1.60	8.30	1.62	8.61	1.65	8.93	1.68
					16	7.25	1.56	7.55	1.60	7.86	1.63	8.01	1.64	8.17	1.66	8.48	1.69	8.80	1.72
					18	7.12	1.60	7.42	1.64	7.73	1.67	7.88	1.68	8.04	1.70	8.35	1.73	8.68	1.76
					20	6.99	1.65	7.29	1.68	7.60	1.71	7.75	1.73	7.91	1.74	8.23	1.77	8.55	1.81
					21	6.92	1.67	7.22	1.70	7.53	1.73	7.69	1.75	7.84	1.76	8.16	1.79	8.48	1.83
					23	6.79	1.71	7.09	1.74	7.40	1.77	7.56	1.79	7.71	1.81	8.03	1.84	8.35	1.87
					25	6.66	1.75	6.96	1.79	7.27	1.82	7.43	1.83	7.59	1.85	7.90	1.88	8.23	1.92
					27	6.53	1.80	6.83	1.83	7.14	1.86	7.30	1.88	7.46	1.90	7.78	1.93	8.10	1.96
					29	6.40	1.84	6.70	1.87	7.01	1.91	7.17	1.92	7.33	1.94	7.65	1.97	7.97	2.01
					31	6.27	1.89	6.57	1.92	6.89	1.95	7.04	1.97	7.20	1.99	7.52	2.02	7.85	2.05
					33	6.14	1.93	6.45	1.97	6.76	2.00	6.92	2.02	7.07	2.03	7.39	2.07	7.72	2.10
35	6.01	1.98	6.32	2.01	6.63	2.05	6.80	2.06	6.95	2.08	7.27	2.11	7.59	2.15					
37	5.88	2.03	6.19	2.06	6.50	2.10	6.66	2.11	6.82	2.13	7.14	2.16	7.47	2.20					
39	5.75	2.08	6.06	2.11	6.38	2.14	6.53	2.16	6.69	2.18	7.02	2.21	7.34	2.25					
42	5.56	2.15	5.87	2.19	6.19	2.22	6.34	2.24	6.50	2.25	6.83	2.29	7.15	2.32					
44	5.43	2.20	5.74	2.24	6.06	2.27	6.22	2.29	6.38	2.30	6.70	2.34	7.03	2.37					
46	5.31	2.25	5.62	2.29	5.93	2.32	6.09	2.34	6.25	2.36	6.58	2.39	6.91	2.42					

NOTE

- Cooling capacity is based on 27°CDB / 19°CWB (indoor temperature), 35°CDB (outdoor temperature).
- Heating capacity is based on 20°CDB (indoor temperature), 7°CDB/6°CWB (outdoor temperature).
- The above is the value for connecting with the following indoor units.
 - 2000, 2500, 3500, 5000W class: Wall Mounted A3050 Series [only for AR**MXWSAWKNEU]
- Capacities are based on the following conditions:
 - Corresponding refrigerant piping length : 5m / - Level difference : 0m
- The total ability of connected a indoor unit is up to 7.5kW
- It is impossible to connect the indoor unit for one room only.
- This data is reference data for temperature capacity trend.

12. Capacity Table

11-4. AJ068RCJ3EGEU

Heating

Combination (Capacity Index)			Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, DB)													
						14		16		18		20		21		22		24	
						TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
2000			2000	29%	-15	1.26	0.76	1.22	0.77	1.18	0.78	1.17	0.78	1.15	0.79	1.13	0.79	1.11	0.80
					-10	1.51	0.79	1.47	0.81	1.43	0.82	1.41	0.82	1.40	0.83	1.37	0.83	1.34	0.84
					-5	1.76	0.83	1.71	0.85	1.67	0.86	1.66	0.86	1.64	0.87	1.61	0.88	1.58	0.88
					0	2.01	0.87	1.96	0.89	1.92	0.90	1.90	0.90	1.88	0.91	1.85	0.92	1.82	0.93
					2	2.11	0.89	2.06	0.90	2.02	0.91	2.00	0.92	1.98	0.92	1.95	0.93	1.92	0.94
					7	2.31	0.92	2.26	0.93	2.21	0.95	2.20	0.95	2.17	0.96	2.14	0.97	2.11	0.98
					10	2.51	0.95	2.46	0.96	2.41	0.98	2.39	0.98	2.37	0.99	2.33	1.00	2.30	1.01
					15	2.76	0.99	2.71	1.00	2.66	1.02	2.64	1.02	2.61	1.03	2.57	1.04	2.54	1.05
2500			2500	37%	-15	1.89	0.91	1.83	0.93	1.78	0.94	1.75	0.95	1.73	0.95	1.69	0.96	1.66	0.97
					-10	2.26	0.96	2.20	0.98	2.14	0.99	2.12	1.00	2.09	1.00	2.05	1.01	2.02	1.02
					-5	2.64	1.01	2.57	1.02	2.51	1.04	2.48	1.04	2.46	1.05	2.41	1.06	2.37	1.07
					0	3.01	1.06	2.94	1.07	2.88	1.09	2.85	1.09	2.82	1.10	2.77	1.11	2.73	1.12
					2	3.16	1.08	3.09	1.09	3.03	1.11	3.00	1.11	2.97	1.12	2.92	1.13	2.87	1.14
					7	3.46	1.11	3.39	1.13	3.32	1.14	3.30	1.15	3.26	1.16	3.21	1.17	3.16	1.18
					10	3.76	1.15	3.69	1.17	3.62	1.18	3.59	1.19	3.55	1.20	3.50	1.21	3.45	1.22
					15	4.14	1.20	4.06	1.21	3.99	1.23	3.95	1.24	3.92	1.25	3.86	1.26	3.81	1.27
3500			3500	51%	-15	2.29	1.07	2.22	1.09	2.15	1.10	2.13	1.11	2.10	1.12	2.05	1.13	2.01	1.14
					-10	2.74	1.13	2.67	1.15	2.60	1.16	2.57	1.17	2.54	1.17	2.49	1.19	2.44	1.20
					-5	3.20	1.19	3.12	1.20	3.04	1.22	3.01	1.23	2.98	1.23	2.92	1.25	2.88	1.26
					0	3.65	1.24	3.57	1.26	3.49	1.28	3.46	1.28	3.42	1.29	3.36	1.30	3.31	1.32
					2	3.83	1.26	3.75	1.28	3.67	1.30	3.63	1.31	3.60	1.31	3.54	1.33	3.48	1.34
					7	4.20	1.31	4.11	1.33	4.03	1.34	4.00	1.35	3.95	1.36	3.89	1.37	3.83	1.39
					10	4.56	1.35	4.47	1.37	4.38	1.39	4.35	1.40	4.31	1.41	4.24	1.42	4.18	1.43
					15	5.02	1.40	4.92	1.43	4.83	1.44	4.79	1.45	4.75	1.46	4.68	1.48	4.62	1.49
5000			5000	74%	-15	3.21	1.45	3.11	1.47	3.02	1.49	2.98	1.50	2.94	1.50	2.87	1.52	2.82	1.53
					-10	3.84	1.52	3.73	1.55	3.64	1.57	3.60	1.57	3.55	1.58	3.48	1.60	3.42	1.61
					-5	4.48	1.60	4.36	1.62	4.26	1.64	4.22	1.65	4.17	1.66	4.09	1.68	4.03	1.69
					0	5.11	1.67	4.99	1.70	4.89	1.72	4.84	1.73	4.79	1.74	4.71	1.76	4.63	1.77
					2	5.37	1.70	5.25	1.73	5.14	1.75	5.09	1.76	5.04	1.77	4.95	1.79	4.88	1.81
					7	5.88	1.76	5.75	1.79	5.64	1.81	5.60	1.82	5.54	1.83	5.44	1.85	5.36	1.87
					10	6.39	1.82	6.26	1.85	6.14	1.87	6.08	1.88	6.03	1.89	5.94	1.92	5.85	1.93
					15	7.03	1.89	6.89	1.92	6.77	1.95	6.71	1.96	6.65	1.97	6.55	1.99	6.46	2.01
2000	2000		4000	59%	-15	2.52	0.97	2.44	0.98	2.37	1.00	2.34	1.00	2.31	1.01	2.26	1.02	2.21	1.03
					-10	3.02	1.02	2.93	1.04	2.86	1.05	2.82	1.06	2.79	1.06	2.74	1.07	2.69	1.08
					-5	3.52	1.07	3.43	1.09	3.35	1.10	3.31	1.11	3.28	1.11	3.22	1.13	3.16	1.14
					0	4.02	1.12	3.92	1.14	3.84	1.15	3.80	1.16	3.76	1.17	3.70	1.18	3.64	1.19
					2	4.22	1.14	4.12	1.16	4.04	1.17	4.00	1.18	3.96	1.19	3.89	1.20	3.83	1.21
					7	4.62	1.18	4.52	1.20	4.43	1.21	4.40	1.22	4.35	1.23	4.28	1.24	4.21	1.25
					10	5.02	1.22	4.92	1.24	4.82	1.25	4.78	1.26	4.74	1.27	4.66	1.28	4.60	1.30
					15	5.52	1.27	5.41	1.29	5.32	1.31	5.27	1.31	5.23	1.32	5.15	1.34	5.08	1.35

12. Capacity Table

Combination (Capacity Index)			Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, DB)													
						14		16		18		20		21		22		24	
						TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
2000	2500		4500	66%	-15	3.15	1.18	3.05	1.20	2.96	1.22	2.92	1.22	2.89	1.23	2.82	1.24	2.77	1.25
					-10	3.77	1.25	3.67	1.27	3.57	1.28	3.53	1.29	3.49	1.30	3.42	1.31	3.36	1.32
					-5	4.40	1.31	4.29	1.33	4.19	1.35	4.14	1.35	4.10	1.36	4.02	1.37	3.96	1.39
					0	5.02	1.37	4.90	1.39	4.80	1.41	4.75	1.42	4.71	1.42	4.62	1.44	4.55	1.45
					2	5.27	1.39	5.15	1.41	5.05	1.43	5.00	1.44	4.95	1.45	4.86	1.47	4.79	1.48
					7	5.77	1.44	5.65	1.46	5.54	1.48	5.50	1.49	5.44	1.50	5.35	1.52	5.27	1.53
					10	6.27	1.49	6.15	1.51	6.03	1.53	5.98	1.54	5.92	1.55	5.83	1.57	5.75	1.58
					15	6.90	1.55	6.77	1.57	6.65	1.59	6.59	1.60	6.53	1.61	6.44	1.63	6.35	1.65
2000	3500		5500	81%	-15	3.55	1.33	3.44	1.35	3.34	1.36	3.29	1.37	3.25	1.38	3.18	1.39	3.12	1.40
					-10	4.25	1.40	4.13	1.42	4.03	1.44	3.98	1.45	3.94	1.45	3.86	1.47	3.79	1.48
					-5	4.95	1.47	4.83	1.49	4.72	1.51	4.67	1.52	4.62	1.53	4.53	1.54	4.46	1.55
					0	5.66	1.53	5.53	1.56	5.41	1.58	5.36	1.59	5.30	1.60	5.21	1.61	5.13	1.63
					2	5.94	1.56	5.81	1.59	5.69	1.61	5.63	1.62	5.58	1.63	5.48	1.64	5.40	1.66
					7	6.51	1.62	6.37	1.64	6.24	1.66	6.20	1.67	6.13	1.68	6.03	1.70	5.94	1.72
					10	7.07	1.67	6.93	1.69	6.80	1.72	6.74	1.73	6.68	1.74	6.57	1.76	6.48	1.77
					15	7.78	1.74	7.63	1.76	7.49	1.79	7.43	1.80	7.37	1.81	7.25	1.83	7.15	1.85
2000	5000		7000	103%	-15	4.47	1.58	4.33	1.61	4.20	1.63	4.14	1.64	4.09	1.64	4.00	1.66	3.92	1.67
					-10	5.35	1.66	5.20	1.69	5.07	1.71	5.01	1.72	4.95	1.73	4.85	1.75	4.77	1.76
					-5	6.23	1.75	6.08	1.77	5.94	1.80	5.87	1.81	5.81	1.82	5.70	1.84	5.61	1.85
					0	7.12	1.83	6.96	1.86	6.81	1.88	6.74	1.89	6.67	1.90	6.56	1.92	6.45	1.94
					2	7.47	1.86	7.31	1.89	7.15	1.91	7.08	1.93	7.02	1.94	6.90	1.96	6.79	1.97
					7	8.19	1.93	8.01	1.95	7.85	1.98	7.80	1.99	7.71	2.00	7.58	2.03	7.47	2.04
					10	8.90	1.99	8.72	2.02	8.55	2.05	8.47	2.06	8.40	2.07	8.27	2.09	8.15	2.11
					15	9.79	2.07	9.60	2.10	9.43	2.13	9.34	2.14	9.27	2.16	9.13	2.18	9.00	2.20
2500	2500		5000	74%	-15	3.78	1.50	3.66	1.52	3.55	1.54	3.51	1.55	3.46	1.56	3.38	1.58	3.32	1.59
					-10	4.53	1.58	4.40	1.60	4.29	1.63	4.24	1.64	4.19	1.64	4.10	1.66	4.03	1.67
					-5	5.27	1.66	5.14	1.68	5.02	1.71	4.97	1.72	4.92	1.73	4.83	1.74	4.75	1.76
					0	6.02	1.74	5.89	1.76	5.76	1.79	5.70	1.80	5.65	1.81	5.55	1.83	5.46	1.84
					2	6.32	1.77	6.18	1.79	6.05	1.82	5.99	1.83	5.94	1.84	5.84	1.86	5.75	1.88
					7	6.93	1.83	6.78	1.86	6.64	1.88	6.60	1.89	6.52	1.90	6.42	1.92	6.32	1.94
					10	7.53	1.89	7.37	1.92	7.24	1.94	7.17	1.96	7.11	1.97	7.00	1.99	6.90	2.01
					15	8.28	1.97	8.12	2.00	7.98	2.02	7.91	2.03	7.84	2.05	7.72	2.07	7.62	2.09
2500	3500		6000	88%	-15	4.18	1.55	4.05	1.57	3.93	1.59	3.88	1.60	3.83	1.61	3.74	1.63	3.67	1.64
					-10	5.01	1.63	4.87	1.66	4.74	1.68	4.69	1.69	4.63	1.70	4.54	1.71	4.46	1.73
					-5	5.83	1.71	5.69	1.74	5.56	1.76	5.50	1.77	5.44	1.78	5.34	1.80	5.25	1.81
					0	6.66	1.79	6.51	1.82	6.37	1.84	6.31	1.85	6.25	1.86	6.14	1.88	6.04	1.90
					2	7.00	1.82	6.84	1.85	6.70	1.88	6.63	1.89	6.57	1.90	6.46	1.92	6.36	1.94
					7	7.66	1.89	7.50	1.92	7.35	1.94	7.30	1.95	7.22	1.96	7.10	1.99	6.99	2.00
					10	8.33	1.95	8.16	1.98	8.00	2.01	7.93	2.02	7.86	2.03	7.74	2.05	7.63	2.07
					15	9.16	2.03	8.98	2.06	8.82	2.09	8.75	2.10	8.67	2.11	8.54	2.14	8.42	2.16
2500	5000		7500	110%	-15	4.47	1.62	4.33	1.65	4.20	1.67	4.14	1.68	4.09	1.69	4.00	1.70	3.92	1.72
					-10	5.35	1.71	5.20	1.73	5.07	1.75	5.01	1.77	4.95	1.77	4.85	1.79	4.77	1.81
					-5	6.23	1.79	6.08	1.82	5.94	1.84	5.87	1.85	5.81	1.86	5.70	1.88	5.61	1.90
					0	7.12	1.87	6.96	1.90	6.81	1.93	6.74	1.94	6.67	1.95	6.56	1.97	6.45	1.99
					2	7.47	1.91	7.31	1.94	7.15	1.96	7.08	1.97	7.02	1.99	6.90	2.01	6.79	2.02
					7	8.19	1.97	8.01	2.00	7.85	2.03	7.80	2.04	7.71	2.05	7.58	2.08	7.47	2.10
					10	8.90	2.04	8.72	2.07	8.55	2.10	8.47	2.11	8.40	2.12	8.27	2.15	8.15	2.17
					15	9.79	2.12	9.60	2.15	9.43	2.18	9.34	2.20	9.27	2.21	9.13	2.23	9.00	2.26

12. Capacity Table

Combination (Capacity Index)			Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, DB)													
						14		16		18		20		21		22		24	
						TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
3500	3500		7000	103%	-15	4.47	1.58	4.33	1.61	4.20	1.63	4.14	1.64	4.09	1.64	4.00	1.66	3.92	1.67
					-10	5.35	1.66	5.20	1.69	5.07	1.71	5.01	1.72	4.95	1.73	4.85	1.75	4.77	1.76
					-5	6.23	1.75	6.08	1.77	5.94	1.80	5.87	1.81	5.81	1.82	5.70	1.84	5.61	1.85
					0	7.12	1.83	6.96	1.86	6.81	1.88	6.74	1.89	6.67	1.90	6.56	1.92	6.45	1.94
					2	7.47	1.86	7.31	1.89	7.15	1.91	7.08	1.93	7.02	1.94	6.90	1.96	6.79	1.97
					7	8.19	1.93	8.01	1.95	7.85	1.98	7.80	1.99	7.71	2.00	7.58	2.03	7.47	2.04
					10	8.90	1.99	8.72	2.02	8.55	2.05	8.47	2.06	8.40	2.07	8.27	2.09	8.15	2.11
					15	9.79	2.07	9.60	2.10	9.43	2.13	9.34	2.14	9.27	2.16	9.13	2.18	9.00	2.20
3500	5000		8500	125%	-15	4.58	1.66	4.44	1.69	4.31	1.71	4.25	1.72	4.20	1.73	4.10	1.74	4.02	1.76
					-10	5.49	1.75	5.33	1.77	5.20	1.80	5.14	1.81	5.08	1.82	4.97	1.84	4.89	1.85
					-5	6.39	1.83	6.23	1.86	6.09	1.89	6.02	1.90	5.96	1.91	5.85	1.93	5.75	1.94
					0	7.30	1.92	7.13	1.95	6.98	1.98	6.91	1.99	6.84	2.00	6.72	2.02	6.62	2.04
					2	7.67	1.95	7.49	1.98	7.34	2.01	7.27	2.02	7.20	2.03	7.07	2.06	6.97	2.07
					7	8.40	2.02	8.22	2.05	8.05	2.08	8.00	2.09	7.91	2.11	7.78	2.13	7.66	2.15
					10	9.12	2.09	8.94	2.12	8.77	2.15	8.69	2.16	8.62	2.18	8.48	2.20	8.36	2.22
					15	10.04	2.17	9.84	2.21	9.67	2.24	9.58	2.25	9.51	2.26	9.36	2.29	9.23	2.31
5000	5000		10000	147%	-15	4.58	1.65	4.44	1.68	4.31	1.70	4.25	1.71	4.20	1.72	4.10	1.74	4.02	1.75
					-10	5.49	1.74	5.33	1.77	5.20	1.79	5.14	1.80	5.08	1.81	4.97	1.83	4.89	1.84
					-5	6.39	1.83	6.23	1.85	6.09	1.88	6.02	1.89	5.96	1.90	5.85	1.92	5.75	1.94
					0	7.30	1.91	7.13	1.94	6.98	1.97	6.91	1.98	6.84	1.99	6.72	2.01	6.62	2.03
					2	7.67	1.95	7.49	1.97	7.34	2.00	7.27	2.01	7.20	2.02	7.07	2.05	6.97	2.06
					7	8.40	2.01	8.22	2.04	8.05	2.07	8.00	2.08	7.91	2.10	7.78	2.12	7.66	2.14
					10	9.12	2.08	8.94	2.11	8.77	2.14	8.69	2.15	8.62	2.17	8.48	2.19	8.36	2.21
					15	10.04	2.16	9.84	2.20	9.67	2.23	9.58	2.24	9.51	2.25	9.36	2.28	9.23	2.30
2000	2000	2000	6000	88%	-15	3.78	1.40	3.66	1.42	3.55	1.44	3.51	1.45	3.46	1.45	3.38	1.47	3.32	1.48
					-10	4.53	1.47	4.40	1.49	4.29	1.51	4.24	1.52	4.19	1.53	4.10	1.55	4.03	1.56
					-5	5.27	1.55	5.14	1.57	5.02	1.59	4.97	1.60	4.92	1.61	4.83	1.62	4.75	1.64
					0	6.02	1.62	5.89	1.64	5.76	1.66	5.70	1.67	5.65	1.68	5.55	1.70	5.46	1.72
					2	6.32	1.65	6.18	1.67	6.05	1.69	5.99	1.70	5.94	1.71	5.84	1.73	5.75	1.75
					7	6.93	1.70	6.78	1.73	6.64	1.75	6.60	1.76	6.52	1.77	6.42	1.79	6.32	1.81
					10	7.53	1.76	7.37	1.79	7.24	1.81	7.17	1.82	7.11	1.83	7.00	1.85	6.90	1.87
					15	8.28	1.83	8.12	1.86	7.98	1.88	7.91	1.89	7.84	1.91	7.72	1.93	7.62	1.95
2000	2000	2500	6500	96%	-15	4.41	1.45	4.27	1.48	4.15	1.50	4.09	1.50	4.04	1.51	3.95	1.53	3.87	1.54
					-10	5.28	1.53	5.13	1.55	5.00	1.57	4.94	1.58	4.89	1.59	4.79	1.61	4.70	1.62
					-5	6.15	1.61	6.00	1.63	5.86	1.65	5.80	1.66	5.74	1.67	5.63	1.69	5.54	1.70
					0	7.03	1.68	6.87	1.71	6.72	1.73	6.65	1.74	6.59	1.75	6.47	1.77	6.37	1.78
					2	7.38	1.71	7.21	1.74	7.06	1.76	6.99	1.77	6.93	1.78	6.81	1.80	6.71	1.82
					7	8.08	1.77	7.91	1.80	7.75	1.82	7.70	1.83	7.61	1.84	7.49	1.86	7.38	1.88
					10	8.78	1.83	8.60	1.86	8.44	1.88	8.37	1.89	8.29	1.91	8.16	1.93	8.05	1.94
					15	9.66	1.90	9.48	1.93	9.30	1.96	9.22	1.97	9.15	1.98	9.01	2.00	8.88	2.02

12. Capacity Table

Combination (Capacity Index)			Combination (Total)	Combination (%)	Outdoor Temperature (°C, DB)	Indoor Temperature(°C, DB)													
						14		16		18		20		21		22		24	
						TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
2000	2000	3500	7500	110%	-15	4.58	1.53	4.44	1.55	4.31	1.57	4.25	1.58	4.20	1.59	4.10	1.60	4.02	1.62
					-10	5.49	1.61	5.33	1.63	5.20	1.65	5.14	1.66	5.08	1.67	4.97	1.69	4.89	1.70
					-5	6.39	1.69	6.23	1.71	6.09	1.73	6.02	1.74	5.96	1.75	5.85	1.77	5.75	1.79
					0	7.30	1.76	7.13	1.79	6.98	1.81	6.91	1.83	6.84	1.84	6.72	1.85	6.62	1.87
					2	7.67	1.80	7.49	1.82	7.34	1.85	7.27	1.86	7.20	1.87	7.07	1.89	6.97	1.91
					7	8.40	1.86	8.22	1.89	8.05	1.91	8.00	1.92	7.91	1.93	7.78	1.95	7.66	1.97
					10	9.12	1.92	8.94	1.95	8.77	1.97	8.69	1.99	8.62	2.00	8.48	2.02	8.36	2.04
					15	10.04	2.00	9.84	2.03	9.67	2.05	9.58	2.07	9.51	2.08	9.36	2.10	9.23	2.12
2000	2000	5000	9000	132%	-15	4.58	1.56	4.44	1.58	4.31	1.60	4.25	1.61	4.20	1.62	4.10	1.64	4.02	1.65
					-10	5.49	1.64	5.33	1.66	5.20	1.69	5.14	1.70	5.08	1.71	4.97	1.72	4.89	1.74
					-5	6.39	1.72	6.23	1.75	6.09	1.77	6.02	1.78	5.96	1.79	5.85	1.81	5.75	1.82
					0	7.30	1.80	7.13	1.83	6.98	1.85	6.91	1.86	6.84	1.87	6.72	1.89	6.62	1.91
					2	7.67	1.83	7.49	1.86	7.34	1.89	7.27	1.90	7.20	1.91	7.07	1.93	6.97	1.95
					7	8.40	1.90	8.22	1.92	8.05	1.95	8.00	1.96	7.91	1.97	7.78	2.00	7.66	2.01
					10	9.12	1.96	8.94	1.99	8.77	2.02	8.69	2.03	8.62	2.04	8.48	2.06	8.36	2.08
					15	10.04	2.04	9.84	2.07	9.67	2.10	9.58	2.11	9.51	2.12	9.36	2.15	9.23	2.17
2000	2500	2500	7000	103%	-15	4.58	1.49	4.44	1.52	4.31	1.54	4.25	1.55	4.20	1.55	4.10	1.57	4.02	1.58
					-10	5.49	1.57	5.33	1.60	5.20	1.62	5.14	1.63	5.08	1.64	4.97	1.65	4.89	1.67
					-5	6.39	1.65	6.23	1.67	6.09	1.70	6.02	1.71	5.96	1.72	5.85	1.73	5.75	1.75
					0	7.30	1.73	7.13	1.75	6.98	1.78	6.91	1.79	6.84	1.80	6.72	1.82	6.62	1.83
					2	7.67	1.76	7.49	1.78	7.34	1.81	7.27	1.82	7.20	1.83	7.07	1.85	6.97	1.87
					7	8.40	1.82	8.22	1.85	8.05	1.87	8.00	1.88	7.91	1.89	7.78	1.91	7.66	1.93
					10	9.12	1.88	8.94	1.91	8.77	1.93	8.69	1.95	8.62	1.96	8.48	1.98	8.36	2.00
					15	10.04	1.96	9.84	1.98	9.67	2.01	9.58	2.02	9.51	2.04	9.36	2.06	9.23	2.08
2000	2500	3500	8000	118%	-15	4.58	1.52	4.44	1.54	4.31	1.56	4.25	1.57	4.20	1.58	4.10	1.59	4.02	1.61
					-10	5.49	1.60	5.33	1.62	5.20	1.64	5.14	1.65	5.08	1.66	4.97	1.68	4.89	1.69
					-5	6.39	1.68	6.23	1.70	6.09	1.72	6.02	1.73	5.96	1.74	5.85	1.76	5.75	1.78
					0	7.30	1.76	7.13	1.78	6.98	1.80	6.91	1.82	6.84	1.83	6.72	1.85	6.62	1.86
					2	7.67	1.79	7.49	1.81	7.34	1.84	7.27	1.85	7.20	1.86	7.07	1.88	6.97	1.90
					7	8.40	1.85	8.22	1.88	8.05	1.90	8.00	1.91	7.91	1.92	7.78	1.94	7.66	1.96
					10	9.12	1.91	8.94	1.94	8.77	1.96	8.69	1.98	8.62	1.99	8.48	2.01	8.36	2.03
					15	10.04	1.99	9.84	2.02	9.67	2.04	9.58	2.06	9.51	2.07	9.36	2.09	9.23	2.11
2000	2500	5000	9500	140%	-15	4.58	1.53	4.44	1.55	4.31	1.57	4.25	1.58	4.20	1.59	4.10	1.60	4.02	1.62
					-10	5.49	1.61	5.33	1.63	5.20	1.65	5.14	1.66	5.08	1.67	4.97	1.69	4.89	1.70
					-5	6.39	1.69	6.23	1.71	6.09	1.73	6.02	1.74	5.96	1.75	5.85	1.77	5.75	1.79
					0	7.30	1.76	7.13	1.79	6.98	1.81	6.91	1.83	6.84	1.84	6.72	1.85	6.62	1.87
					2	7.67	1.80	7.49	1.82	7.34	1.85	7.27	1.86	7.20	1.87	7.07	1.89	6.97	1.91
					7	8.40	1.86	8.22	1.89	8.05	1.91	8.00	1.92	7.91	1.93	7.78	1.95	7.66	1.97
					10	9.12	1.92	8.94	1.95	8.77	1.97	8.69	1.99	8.62	2.00	8.48	2.02	8.36	2.04
					15	10.04	2.00	9.84	2.03	9.67	2.05	9.58	2.07	9.51	2.08	9.36	2.10	9.23	2.12
2000	3500	3500	9000	132%	-15	4.58	1.56	4.44	1.58	4.31	1.60	4.25	1.61	4.20	1.62	4.10	1.64	4.02	1.65
					-10	5.49	1.64	5.33	1.66	5.20	1.69	5.14	1.70	5.08	1.71	4.97	1.72	4.89	1.74
					-5	6.39	1.72	6.23	1.75	6.09	1.77	6.02	1.78	5.96	1.79	5.85	1.81	5.75	1.82
					0	7.30	1.80	7.13	1.83	6.98	1.85	6.91	1.86	6.84	1.87	6.72	1.89	6.62	1.91
					2	7.67	1.83	7.49	1.86	7.34	1.89	7.27	1.90	7.20	1.91	7.07	1.93	6.97	1.95
					7	8.40	1.90	8.22	1.92	8.05	1.95	8.00	1.96	7.91	1.97	7.78	2.00	7.66	2.01
					10	9.12	1.96	8.94	1.99	8.77	2.02	8.69	2.03	8.62	2.04	8.48	2.06	8.36	2.08
					15	10.04	2.04	9.84	2.07	9.67	2.10	9.58	2.11	9.51	2.12	9.36	2.15	9.23	2.17

12. Capacity Table

Combination (Capacity Index)			Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, DB)													
						14		16		18		20		21		22		24	
						TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
2000	3500	5000	10500	154%	-15	4.58	1.55	4.44	1.57	4.31	1.59	4.25	1.60	4.20	1.61	4.10	1.63	4.02	1.64
					-10	5.49	1.63	5.33	1.66	5.20	1.68	5.14	1.69	5.08	1.70	4.97	1.71	4.89	1.73
					-5	6.39	1.71	6.23	1.74	6.09	1.76	6.02	1.77	5.96	1.78	5.85	1.80	5.75	1.81
					0	7.30	1.79	7.13	1.82	6.98	1.84	6.91	1.85	6.84	1.86	6.72	1.88	6.62	1.90
					2	7.67	1.82	7.49	1.85	7.34	1.88	7.27	1.89	7.20	1.90	7.07	1.92	6.97	1.94
					7	8.40	1.89	8.22	1.92	8.05	1.94	8.00	1.95	7.91	1.96	7.78	1.99	7.66	2.00
					10	9.12	1.95	8.94	1.98	8.77	2.01	8.69	2.02	8.62	2.03	8.48	2.05	8.36	2.07
					15	10.04	2.03	9.84	2.06	9.67	2.09	9.58	2.10	9.51	2.11	9.36	2.14	9.23	2.16
2500	2500	2500	7500	110%	-15	4.58	1.53	4.44	1.56	4.31	1.58	4.25	1.59	4.20	1.60	4.10	1.61	4.02	1.62
					-10	5.49	1.61	5.33	1.64	5.20	1.66	5.14	1.67	5.08	1.68	4.97	1.70	4.89	1.71
					-5	6.39	1.69	6.23	1.72	6.09	1.74	6.02	1.75	5.96	1.76	5.85	1.78	5.75	1.80
					0	7.30	1.77	7.13	1.80	6.98	1.82	6.91	1.83	6.84	1.85	6.72	1.86	6.62	1.88
					2	7.67	1.80	7.49	1.83	7.34	1.86	7.27	1.87	7.20	1.88	7.07	1.90	6.97	1.92
					7	8.40	1.87	8.22	1.90	8.05	1.92	8.00	1.93	7.91	1.94	7.78	1.96	7.66	1.98
					10	9.12	1.93	8.94	1.96	8.77	1.99	8.69	2.00	8.62	2.01	8.48	2.03	8.36	2.05
					15	10.04	2.01	9.84	2.04	9.67	2.07	9.58	2.08	9.51	2.09	9.36	2.11	9.23	2.13
2500	2500	3500	8500	125%	-15	4.58	1.52	4.44	1.54	4.31	1.56	4.25	1.57	4.20	1.58	4.10	1.59	4.02	1.61
					-10	5.49	1.60	5.33	1.62	5.20	1.64	5.14	1.65	5.08	1.66	4.97	1.68	4.89	1.69
					-5	6.39	1.68	6.23	1.70	6.09	1.72	6.02	1.73	5.96	1.74	5.85	1.76	5.75	1.78
					0	7.30	1.76	7.13	1.78	6.98	1.80	6.91	1.82	6.84	1.83	6.72	1.85	6.62	1.86
					2	7.67	1.79	7.49	1.81	7.34	1.84	7.27	1.85	7.20	1.86	7.07	1.88	6.97	1.90
					7	8.40	1.85	8.22	1.88	8.05	1.90	8.00	1.91	7.91	1.92	7.78	1.94	7.66	1.96
					10	9.12	1.91	8.94	1.94	8.77	1.96	8.69	1.98	8.62	1.99	8.48	2.01	8.36	2.03
					15	10.04	1.99	9.84	2.02	9.67	2.04	9.58	2.06	9.51	2.07	9.36	2.09	9.23	2.11
2500	2500	5000	10000	147%	-15	4.58	1.55	4.44	1.57	4.31	1.59	4.25	1.60	4.20	1.61	4.10	1.63	4.02	1.64
					-10	5.49	1.63	5.33	1.66	5.20	1.68	5.14	1.69	5.08	1.70	4.97	1.71	4.89	1.73
					-5	6.39	1.71	6.23	1.74	6.09	1.76	6.02	1.77	5.96	1.78	5.85	1.80	5.75	1.81
					0	7.30	1.79	7.13	1.82	6.98	1.84	6.91	1.85	6.84	1.86	6.72	1.88	6.62	1.90
					2	7.67	1.82	7.49	1.85	7.34	1.88	7.27	1.89	7.20	1.90	7.07	1.92	6.97	1.94
					7	8.40	1.89	8.22	1.92	8.05	1.94	8.00	1.95	7.91	1.96	7.78	1.99	7.66	2.00
					10	9.12	1.95	8.94	1.98	8.77	2.01	8.69	2.02	8.62	2.03	8.48	2.05	8.36	2.07
					15	10.04	2.03	9.84	2.06	9.67	2.09	9.58	2.10	9.51	2.11	9.36	2.14	9.23	2.16
2500	3500	3500	9500	140%	-15	4.58	1.53	4.44	1.56	4.31	1.58	4.25	1.59	4.20	1.60	4.10	1.61	4.02	1.62
					-10	5.49	1.61	5.33	1.64	5.20	1.66	5.14	1.67	5.08	1.68	4.97	1.70	4.89	1.71
					-5	6.39	1.69	6.23	1.72	6.09	1.74	6.02	1.75	5.96	1.76	5.85	1.78	5.75	1.80
					0	7.30	1.77	7.13	1.80	6.98	1.82	6.91	1.83	6.84	1.85	6.72	1.86	6.62	1.88
					2	7.67	1.80	7.49	1.83	7.34	1.86	7.27	1.87	7.20	1.88	7.07	1.90	6.97	1.92
					7	8.40	1.87	8.22	1.90	8.05	1.92	8.00	1.93	7.91	1.94	7.78	1.96	7.66	1.98
					10	9.12	1.93	8.94	1.96	8.77	1.99	8.69	2.00	8.62	2.01	8.48	2.03	8.36	2.05
					15	10.04	2.01	9.84	2.04	9.67	2.07	9.58	2.08	9.51	2.09	9.36	2.11	9.23	2.13
2500	3500	5000	11000	162%	-15	4.58	1.57	4.44	1.60	4.31	1.62	4.25	1.63	4.20	1.64	4.10	1.65	4.02	1.67
					-10	5.49	1.66	5.33	1.68	5.20	1.70	5.14	1.71	5.08	1.72	4.97	1.74	4.89	1.75
					-5	6.39	1.74	6.23	1.76	6.09	1.79	6.02	1.80	5.96	1.81	5.85	1.83	5.75	1.84
					0	7.30	1.82	7.13	1.85	6.98	1.87	6.91	1.88	6.84	1.89	6.72	1.91	6.62	1.93
					2	7.67	1.85	7.49	1.88	7.34	1.90	7.27	1.92	7.20	1.93	7.07	1.95	6.97	1.96
					7	8.40	1.92	8.22	1.94	8.05	1.97	8.00	1.98	7.91	1.99	7.78	2.02	7.66	2.03
					10	9.12	1.98	8.94	2.01	8.77	2.04	8.69	2.05	8.62	2.06	8.48	2.08	8.36	2.10
					15	10.04	2.06	9.84	2.09	9.67	2.12	9.58	2.13	9.51	2.14	9.36	2.17	9.23	2.19

12. Capacity Table

Combination (Capacity Index)			Combination (Total)	Combination (%)	Outdoor Temperature (°C,DB)	Indoor Temperature(°C, DB)													
						14		16		18		20		21		22		24	
						TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)	TC(kW)	PI(kW)
3500	3500	3500	10500	154%	-15	4.58	1.52	4.44	1.54	4.31	1.56	4.25	1.57	4.20	1.58	4.10	1.59	4.02	1.61
					-10	5.49	1.60	5.33	1.62	5.20	1.64	5.14	1.65	5.08	1.66	4.97	1.68	4.89	1.69
					-5	6.39	1.68	6.23	1.70	6.09	1.72	6.02	1.73	5.96	1.74	5.85	1.76	5.75	1.78
					0	7.30	1.76	7.13	1.78	6.98	1.80	6.91	1.82	6.84	1.83	6.72	1.85	6.62	1.86
					2	7.67	1.79	7.49	1.81	7.34	1.84	7.27	1.85	7.20	1.86	7.07	1.88	6.97	1.90
					7	8.40	1.85	8.22	1.88	8.05	1.90	8.00	1.91	7.91	1.92	7.78	1.94	7.66	1.96
					10	9.12	1.91	8.94	1.94	8.77	1.96	8.69	1.98	8.62	1.99	8.48	2.01	8.36	2.03
					15	10.04	1.99	9.84	2.02	9.67	2.04	9.58	2.06	9.51	2.07	9.36	2.09	9.23	2.11


NOTE

- Cooling capacity is based on 27°CDB / 19°CWB (indoor temperature), 35°CDB (outdoor temperature).
- Heating capacity is based on 20°CDB (indoor temperature), 7°CDB/6°CWB (outdoor temperature).
- The above is the value for connecting with the following indoor units.
 - 2000, 2500, 3500, 5000W class: Wall Mounted A3050 Series [only for AR**MXWSAWKNEU]
- Capacities are based on the following conditions:
 - Corresponding refrigerant piping length : 5m / - Level difference : 0m
- The total ability of connected a indoor unit is up to 7.5kW
- It is impossible to connect the indoor unit for one room only.
- This data is reference data for temperature capacity trend.


13. Installation

Minimum clearances for the outdoor unit

When installing 1 outdoor unit




When installing more than 1 outdoor unit



⚠ CAUTION

- The outdoor unit must be installed according to the specified distances in order to permit accessibility from each side, to guarantee correct operation, maintenance, and repair of the unit. The components of the outdoor unit must be reachable and removable under safe conditions for people and the unit.



- Power supply cord is not supplied with air conditioner.

- Specifications for local wiring power supply cord and branch wiring are in compliance with local cord.

AJ068RCJ3EG	3 Room	50	1phase,220-240	16.6	0.9	17.5	17.5	20.75
--------------------	--------	----	----------------	------	-----	------	------	-------

※ In case you want more information about the controllers and accessories, please refer to the Controller and Accessory TDB on pvi.samsung.com site or Global Partner Portal site.

13. Installation

NOTE

- Power supply cords of parts of appliances for outdoor use shall not be lighter than polychloroprene sheathed flexible cord. (Code designation IEC:60245 IEC 57 / CENELEC: H05RN-F or IEC:60245 IEC 66 / CENELEC: H07RN-F)
- Select power supply cord based on MCA.
- MFA is used to select the circuit breaker and the ground fault circuit interrupter (earth leakage circuit breaker).
- MCA represents maximum input current.
- MFA represents capacity which may accept MCA.

Abbreviations

- MCA : Min. Circuit Amps. (A)
- MFA : Max. Fuse Amps. (A)

Screw	Tighten Torque(kgf.cm)	Position
M4	12.0~18.0	1(L),2(L),L,N,F1,F2


※ In case you want more information about the controllers and accessories, please refer to the Controller and Accessory TDB on pvi.Samsung.com site or Global Partner Portal site.

13. Installation


AJ040/050NCJ2EG

1 Piping outside diameter

Indoor unit	Out unit	Power supply Ø, V, Hz	Outside diameter	
			Liquid	Gas
07/09/12***	AJ040NCJ2EG AJ050NCJ2EG	1,220-240, 50	1/4"	3/8"



Indoor unit	Out unit	Power supply Ø, V, Hz	Outside diameter	
			Liquid	Gas
07/09/12*** AJ016/020/026/035RB*DEG AJ052RB*DEG	AJ052RCJ3EG AJ068RCJ3EG	1,220-240, 50	1/4"	3/8" 1/2"



NOTE

- AJ052RCJ3EG Outdoor unit cannot be connected to the following indoor unit combination.
 - AJ052RBNDeg/AJ052RBMDEG
- AJ068RCJ3EG Outdoor unit cannot be connected to the following indoor unit combination.
 - AJ***RBJDEG
- This product requires no additional refrigerant charge up to the maximum allowable pipe length.

Maximum allowable refrigerant charge amount


AJ040NCJ2EG/EU	980 g
AJ050NCJ2EG/EU	1180 g
AJ052RCJ3EG/EU	1750 g
AJ068RCJ3EG/EU	2200 g

- In addition to table 1, make sure that the indoor and outdoor unit are installed in a space at least of **4m²** to guarantee the regular maintenance or service repair.
- Reference: Table 1 (defined according to EN378-1:2017)

[Unit: m²]

Charge amount (kg)	Installation height(m)	1.224	1.225	1.250	1.500	1.750	2.000	2.250	2.500
NO limitations	0.6	12.77	13.30	19.15	26.06	34.04	43.09	53.19	
	1	4.60	4.79	6.89	9.38	12.26	15.51	19.15	
	1.8	1.42	1.48	2.13	2.90	3.78	4.79	5.91	
	2	1.15	1.20	1.72	2.35	3.06	3.88	4.79	
	2.2	0.95	0.99	1.42	1.94	2.53	3.20	3.96	

- IMPORTANT: it's mandatory to consider either the table 1 or taking into consideration the local law regarding the minimum living space of the premises.
- Minimum installation height of indoor unit is 0.6 m for floor mounted, 1.8 m for wall, 2.2 m for ceiling.
- AJ***NCJ2EG Outdoor unit can be connected to the following indoor unit combination.
 - AR**MXWS****
 - AR**NX*****



※ In case you want more information about the controllers and accessories, please refer to the Controller and Accessory TDB on pvi.Samsung.com site or Global Partner Portal site.

13. Installation

2 Piping length and the height

	1 Room max length	2 Room total max length	Max height between indoor unit & outdoor unit	Max height between indoor units
Dimension	20m	30m	15m	7.5m
Composition	A,B	A+B	(H)	(h)

CAUTION

- 3 m as minimum pipe length: It will reduce noise and vibration.
- Tighten the nuts to the specified torques.
If overtightened, the nuts could be broken so refrigerant may leak.
- Protect or enclose refrigerant tubing to avoid mechanical damage.

NOTE

- The appearance of the unit may be different from the diagram depending on the model.
- You can use the Cool and Heat modes in the following conditions :

Model	Cool	Heat
Outdoor temperature	-5 °C to 46 °C	-15 °C to 24 °C

- It could take maximum 60 minutes to operate for the protection of the compressor, if the outdoor temperature is below -5°C.



2018.12
Ver.2.0

Samsung Electronics Co., LTD.
B2B PM / SE

Head Office (Suwon Korea) 129, Samsung-Ro, Yeongtong-Gu, Suwon City, Gyeonggi-Do, Korea 16677
Website : www.samsung.com, <http://btsp.samsunggsbn.com> Email : airconditioner@samsung.com
Images and data in this book may subject to change without prior notice.